



SAFETY DATA SHEET

EFFECTIVE DATE: 12/01/15

ITEM: Essential Plus Survival Kit

PART #
771

UPC
077403107711

CONTENTS:

SAR Camp Fire Starter SDS
Antiseptic Towelette SDS
Alcohol Prep / Swab SDS
Sting and Bite Pad SDS
Safety Matches SDS

SHIPPING INFORMATION

UN1944 Match, Safety

SAFETY DATA SHEET

1. Product and Company Identification

**Red Signal Flare - No Perchlorate (NPC)
Formulation**

Identification:

The NPC flare will have the following symbol on it:

Synonyms: SAR Campfire Starter #750
Firestarter / Signal Flare
Fire Pit Pro #747



Identified Use: Fire starter, Emergency signal

Use Advised Against: Do not use indoors or inside a vehicle

Manufacturers Information Orion Safety Products
28320 St. Michaels Rd
Easton, MD 21601
800-637-7807
410-822-0318

EMERGENCY

CHEMTREC
1-800-424-9300

2. Hazards Identification

GHS Classifications

Skin Irritation	Category 2	H315
Eye Irritation	Category 2A	H319
STOT - Single Exposure	Category 3	H335

GHS Label Elements

Pictograms



Signal Word **Warning**

Hazard Statements

H315 /319 Causes skin and serious eye irritation
H335 May cause respiratory irritation

Precautionary Statements

P103 Keep out of reach of children
P261 Avoid breathing dust/smoke.
P264 Wash hands thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective eye protection
P370 In case of fire: use water deluge
P501 Dispose of contents / container in accordance with local and national regulations.

P301/315 IF SWALLOWED: Get immediate medical advice /attention.
P302/352 IF ON SKIN: Wash with plenty of soap and water.
P304/340/342 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor / physician.
P305/338/351 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333/313 If skin irritation or rash occurs, get medical advice / attention.

Hazards Not Otherwise Classified (HNOC): produces hot flame

3. Composition / Information on Ingredients

Component	CAS #	EINCS #	%age
Strontium Nitrate	10042-76-9	233-131-9	<75%
Sulfur	7704-34-9	231-722-6	<25%
Potassium Nitrate	7757-79-1	231-818-8	<25%
Paraffinic Oil	64742-54-7	232-384-2	<10%
Potassium Chlorate	3811-04-9	231-100-4	<5%
Waxy sawdust	mixture	none	<5%
Polyvinyl Chloride	9002-86-2	200-831-0	<5%
Shellac	mixture	none	<1%
Charcoal	1333-86-4	231-153-3	<1%

Note: Due to Confidential Business Information i. e "Trade Secrets", the exact percentage of each ingredient has not been disclosed. CBI information will be shared with appropriate authorities if circumstances warrant.

4. First Aid Measures

Description of first aid measures

Inhalation	If contents are inhaled, remove to fresh air. Watch for signs of allergic reaction. If other symptoms develop, get medical aid immediately.
Skin	If contents are contacted, wash with area with soap and water for 15 minutes. Remove contaminated clothing and wash before reuse. Get medical aid immediately if burned or irritation occurs.
Eyes	If contents get into eye, flush with plenty of water for at least 15 minutes, occasionally lifting the upper and lower lids. Remove contact lenses if easily possible. Do not use boric acid to rinse with; sulfur is an acid irritant. Get medical aid immediately.
Ingestion	Get medical aid immediately.

Most important symptoms and effects both acute and delayed See section 2 labeling and section 11

Indication of any immediate medical attention and special treatment needed

Burning flare can cause severe burns if in contact with body. For burns to skin, cool with water and bandage appropriately. Seek medical attention. If eye is burned, cover eye and get medical aid immediately

5. Firefighting Measures

Extinguishing Media	Water deluge	Unsuitable Extinguishing Media	Foam and dry chemical extinguishers and suffocation are ineffective.
Protective Equipment and Precautions for Firefighters	Wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode. Prevent further propagation of fire by spraying unburnt nearby product with water. Combat fire from a sheltered position.		
Specific Hazards Arising from the Chemical	Use copious amounts of water to extinguish fire comprised of flares. Flares contain oxidizers and will continue to burn unless a significant amount of water is used. Do not breathe smoke.		
Further information	No data available		

6. Accidental Release Measures

Personal Precautions / Protective Equipment / Emergency Procedures

Do not breathe contents and avoid contact with skin and eyes. Wear flame retardant clothing with long sleeves, dust mask, rubber or nitrile gloves, safety goggles, safety shoes. Avoid friction on the released product. Keep away from ignition sources.

Environmental Precautions

Prevent dispersion of contents on soil and in water. Prevent contents from spreading or entering into drains, ditches, groundwater or rivers by using appropriate barriers.

Methods for Containment and Clean-up

Use caution when cleaning up spilled product contents. Remove heat, flames, sparks and other sources of ignition. Use non-sparking tools and equipment. Prevent buildup of electrostatic charges by grounding. Clean spills in a manner that does not disperse dust into the air. Do not absorb in sawdust or other combustible absorbents. Pick up spill for recovery or disposal and place in an approved container. Wash away remainder with plenty of water. Collect wash water for approved disposal.

7. Handling and Storage

Precautions for Safe Handling

Hold and point flare away from body when igniting. Exercise caution when using this product since molten flecks may be emitted. Produces hot flame. Burning flare can cause severe burns if in contact with body. Avoid contact with clothing and other combustible materials. Wear eye protection during use. Follow instructions on package. Use outdoors only! Do not ignite or burn product inside a vehicle or building. Avoid inhalation of smoke. Do not dismantle. Do not allow contents to touch eyes, skin or clothing. Do not ingest contents as they may be harmful if swallowed. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Avoid contact with heat, sparks, and flame.

Conditions for Safe Storage, Including Any Incompatibilities

Store away from direct sunlight, heat and incompatible materials. See section 10. Store away from food and beverages. Store away from flammable materials, sources of heat, flame and sparks. Store at ambient temperature. Do not store partially burned flares in a vehicle, warehouse, or any other building. Plastic bags are provided for moisture protection. Keep partially used bags sealed at all times.

8. Exposure Controls / Personal Protection

Control parameters

Exposure Limits	OSHA PEL	ACGIH TLV
Strontium Nitrate	Not Established	Not Established
Sulfur	Not Established	Not Established
Potassium Nitrate	Nuisance dust 15 mg/m ³ .	Nuisance dust 15 mg/m ³ .
Paraffinic Oil	5 mg/m ³	TWA 5 mg/m ³
Potassium Chlorate	No Airborne Exposure Limits established	No Airborne Exposure Limits established
Waxy sawdust	Not Established	Not Established
Polyvinyl Chloride	No known hazardous components above regulatory thresholds in this product.	No known hazardous components above regulatory thresholds in this product.
Shellac	Not Established	Not Established
Charcoal	Nuisance dust 15 mg/m ³ .	Nuisance dust 15 mg/m ³ .

Exposure controls

Engineering Controls

Use product outdoors only! When cleaning up contents, use local and/or general exhaust.

Personal Protective Equipment

Eye / Face Protection

Safety glasses or goggles

Skin Protection

None under normal conditions when using product unless prolonged handling is anticipated. Impervious protective clothing, including gloves, boots, and a lab coat, apron or coveralls, as appropriate, when cleaning up spilled product. Wash hands and face before eating, drinking or using tobacco products.

Respiratory Protection

None under normal conditions when using product. A particulate respirator (NIOSH t N95 or better filters) may be worn during the cleanup of spilled materials.

General Hygiene

Use product outdoors away from combustible products. For cleanup of spilled materials, emergency showers and eye wash stations should be available. Educate and train employees in the safe use and handling of hazardous materials.

9. Physical and Chemical Properties

Appearance (color, physical form, shape): Yellow to grey powder		Melting Point: Not available		Solubility: Not available	
pH: Not available	Boiling Point / Range: Not applicable	Freezing Point: Not applicable	Evaporation Rate: Not applicable		
Vapor Pressure: Not applicable	Odor: No data available	Specific Gravity: Not applicable	Vapor Density: Not applicable		
Flammability: No data available	Odor Threshold: No data available	Flammability Limits: No data available	Flash Point: Not available		
Partition Coefficient: No data available	Viscosity: No data available	Relative Density: No data available			
Auto Ignition Temperature: 360°F	Decomposition Temperature: No data available				

10. Stability and Reactivity

Chemical Stability: Stable	Reactivity: No information available	Possibility of Hazardous Reactions: Hazardous polymerization will not occur
Conditions to Avoid: Combustible materials, heat, flames, sparks and other sources of ignition. Moisture.	Incompatible Materials: Strong acids, strong fuels, ammonia salts, and strong bases. Strong oxidizers; chlorate salts.	Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, sulfur oxides, and nitrogen oxides.

11. Toxicology Information

Ingredient acute toxicity information

Ingredient	Oral LD50	skin LD50	LC50
Strontium Nitrate	Rat: 2750 mg/kg	No information found	No information found
Sulfur	Rat: >2000 mg/kg	Rat: >2000 mg/kg	Rat: 79.23 mg/L 4hr
Potassium Nitrate	Rat: 3750 mg/kg	No information found	No information found
Paraffinic Oil	Rat: >2000 mg/kg	Rat: >2000 mg/kg	No information found
Potassium Chlorate	Rat: 1870 mg/kg	Rabbit: > 2000 mg/kg	No information found
Waxy sawdust	Rat: > 5000 mg/kg	not stated	not stated
Polyvinyl Chloride	no known hazardous components above regulatory thresholds in this product.	no known hazardous components above regulatory thresholds in this product.	no known hazardous components above regulatory thresholds in this product.
Shellac	No information found	No information found	No information found
Charcoal	Rat: 15400 mg/kg	Rabbit: 3 g/kg	No information found

Product toxicological information

Acute Toxicity	Not classified – <i>Acute Toxicity Estimate yields oral LD₅₀ over 5000 mg/kg bw</i>
Skin Irritation / Corrosion	Category 2 – <i>over 10% of ingredients classified as a Category 2</i>
Serious Eye Damage / Irritation	Category 2a – <i>over 10% of ingredients classified as a Category 2a</i>
Respiratory / Skin Sensitization	Not classified (Based on available data, the classification criteria are not met)
Germ Cell Mutagen	Not classified (Based on available data, the classification criteria are not met)
Carcinogen	Not classified (Based on available data, the classification criteria are not met)
Reproductive Toxicity	Not classified (Based on available data, the classification criteria are not met)
STOT – single exposure	Category 3 – respiratory <i>over 10% of ingredients classified as a Category 3 respiratory STOT hazard</i>
STOT – repeated exposure	Not classified (Based on available data, the classification criteria are not met)
Aspiration Hazard	Not classified (Based on available data, the classification criteria are not met)

Likely routes of exposure

Skin, ingestion, inhalation

Symptoms related to the physical, chemical and toxicological characteristics

Contents irritating to eyes due to chemical and physical properties of the mixture. Ingestion of contents may cause gastrointestinal irritation with nausea, vomiting and diarrhea. Individuals with known allergies to sulfide drugs may also have allergic reactions to elemental sulfur.

Delayed and immediate effects and chronic effects from short and long term exposure

Inhalation of contents or smoke from burning flare will cause irritation to the lungs and mucus membrane. Prolonged or repeated skin contact with contents may cause dermatitis.

Interactive effects

No information found

12. Ecological Information

Ingredient toxicity / persistence / degradability / bioaccumulation / mobility in soil and water

Aquatic Toxicity	<u>Strontium Nitrate:</u> <i>Acute toxicity - Fishes, Carassius auratus, LC100, 9,615 mg/l; Chronic toxicity - Fishes, Gasterosteus aculeatus, LC100, 2.912 mg/l</i>
	<u>Sulfur:</u> <i>Toxicity to fish LC50 - Oncorhynchus mykiss (rainbow trout) - > 180 mg/l - 96 h Toxicity to daphnia and other aquatic invertebrates: EC50 - Daphnia magna (Water flea) – > 5,000 mg/l - 48 h</i>
	<u>Potassium Chlorate:</u> <i>fish: LC50 oncorhynchus mykiss (rainbow trout) 1750 mg/l – 96 hr, EC50 daphnia magna (water flea) 1093 mg/l 24 hr</i>
	<u>Paraffinic Oil:</u> <i>Oil Mist, Mineral Lepomis macrochirus (LC50) 96 hour(s) >100 mg/l Oncorhynchus mykiss (LC50) 96 hour(s) >100 mg/l</i>
	<u>Potassium Nitrate:</u> <i>fish: Guppy (Poecilia Reticulata) LC50 180 mg/L (96 h); zooplankton: Daphnia magna LC50 490mg/l – 48hr</i>
Persistence / Degradability	<u>Potassium Nitrate:</u> Soluble in water Persistence is unlikely based on information available.
Bioaccumulation / Accumulation	No information found
Mobility in Environmental Media	<u>Strontium Nitrate:</u> <i>Water:: considerable solubility and mobility; Soil/sediments non-significant adsorption</i> <u>Potassium Nitrate:</u> <i>Will likely be mobile in the environment due to its water solubility.</i>
Other adverse effects	No information found

13. Disposal Considerations

Disposal methods

Flares should be allowed to burn to completion. Partially burned or unburned flares, spilled contents, and ash from burned flares should be disposed of in accordance with federal, state, and local requirements. Consult factory for any additional disposal concerns.

14. Transportation Information

Description	ID Number	shipping name	hazard class	packing group	EX Number	Reportable Quantities	Shipping method
United States							
Bulk flares	NA1325	Fusee	4.1	II	Not applicable	none	Ground only
Retail packaged flares	UN3178	ORM-D / Limited Quantity	Not applicable	Not applicable	Not applicable	none	Ground only
International / Air							
Bulk flares	UN0373	Signal devices, hand	1.4S	II	EX-1992090001	none	Air / ground

Marine Pollutant: no

Special precautions for user: No information available

15. Regulatory Information

US Regulations	TSCA	CERCLA	CWA	CAA	SARA 313	SARA 302	Acute	Chronic	Fire	Reactivity	Pressure
Strontium Nitrate	yes	no	no	no	no	no	yes	no	no	yes	no
Sulfur	yes	no	no	no	no	no	yes	no	yes	no	no
Potassium Nitrate	yes	no	no	no	yes	no	no	no	no	yes	no
Paraffinic Oil	yes	no	no	no	no	no	no	no	no	no	no
Potassium Chlorate	yes	no	no	no	no	no	yes	no	no	yes	no
Waxy sawdust	yes	no	no	no	no	no	no	no	no	no	no
Polyvinyl Chloride	yes	no	no	no	no	no	yes	no	no	no	no
Shellac Mixture	yes	no	no	no	yes	no	unknown	unknown	unknown	unknown	unknown
Charcoal	yes	no	no	no	no	no	no	no	no	no	no

US States	Prop 65	NJ	PA	Canada	WHMIS	DSL	Europe	wgk
Strontium Nitrate	no	1743	no		C Oxidizing materials D1B Toxic materials D2B Toxic materials	yes		2
Sulfur	no	1757	yes		B4 Flammable solid D2B Toxic materials	yes		1 / nwg
Potassium Nitrate	no	1574	yes		C Oxidizing materials	yes		1
Paraffinic Oil	no	1437	no		No results	yes		not listed
Potassium Chlorate	yes	1560	yes		C Oxidizing materials D1B Toxic materials	yes		2
Waxy sawdust	yes	no	no		No results	yes		not listed
Polyvinyl Chloride	no	3622	no		No results	yes		not listed
Shellac Mixture	no	no	no		No results	unknown		not listed
Charcoal	yes	yes	yes		D2A Very toxic materials D2B Toxic materials	yes		nwg

16. Other Information

Revision Information: May 2015

NFPA Rating

Flammability	1
Health	2
Reactivity	1

HMIS Rating

Flammability	1
Health	2
Physical Hazard	1

Key / Legend:

HMIS: hazardous material identification system
 NFPA: national fire protection association
 CAS: Chemical Abstracts Service number
 EINECS: European inventory of existing chemical substances
 OSHA PEL: occupational safety and health administration permissible exposure limit
 NIOSH TLV: national institute of occupational safety and health Threshold Limit Value
 TSCA: toxic substance control act - US

CERCLA: comprehensive environmental response, compensation and liability act - US
 CWA: clean water act - US
 CAA: clean air act - US
 SARA: superfund amendments and reauthorization act - US
 PROP 65: California's Proposition 65 list
 WHMIS: workplace hazardous materials information system - Canada
 DSL: Domestic Substances List - Canada
 WGK: water hazard classes - Germany

Legal Statement

This information is accurate to the best knowledge Orion Safety Products. Orion Safety Products makes no representations or warranties, either express or implied, including without limitation any warranties of merchantability or fitness for a particular purpose, with respect to the information set forth herein or the product to which the information refers. Accordingly, Orion Safety Products will not be responsible for damages resulting from use of or reliance upon this information. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.



Corporate Headquarters
10 Glenshaw Street, Orangeburg, NY 10962
Tel: 845.365.8200 • Fax: 845.365.8201
Toll-Free: 888.DYNAREX

Reviewed on 4/21/15

SAFETY DATA SHEET

SECTION 1. Product and Company Identification

PRODUCT NAME: BZK Antiseptic Towelette
PRODUCT USE: Antiseptic

Product Code: 1303, 1331

Manufacturer's Name: Dynarex Corporation

Manufacturer's Address: 10 Glenshaw Street
Orangeburg, NY 10962

Emergency or Information Phone No.: 888-DYNAREX or 845-365-8200
At other times, contact the local Poison Control Center

SECTION 2. Hazards Identification

Emergency Overview	Contact with liquid may cause eye and skin irritation
Potential short term health effects	
Routes of exposure	Eye, skin contact, skin absorption, Inhalation, Ingestion.
Eyes	May cause irritation.
Skin	In case of skin irritation, discontinue use of the product.
Inhalation	Not a normal route of exposure. May cause respiratory tract irritation.
Ingestion	Not a normal route of exposure. May cause stomach distress, nausea or vomiting.



Corporate Headquarters
 10 Glenshaw Street, Orangeburg, NY 10962
 Tel: 845.365.8200 • Fax: 845.365.8201
 Toll-Free: 888.DYNAREX

Target organs Eyes. Skin

Chronic effects Prolonged or repeated exposure can cause drying defatting and dermatitis.

Signs and symptoms Symptoms may include redness, edema, drying, defatting and cracking of the skin. Symptoms of overexposure may be headache, dizziness, tiredness, nausea.

SECTION 3. Composition/information on Ingredients

Ingredients	CAS Number	%
BZK	8001-54-5	0.13
Water	7732-18-5	99.87

SECTION 4. First-aid measures

First aid procedures

Eye Contact Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.

Skin Contact In case of skin irritation, discontinue use of product.

Inhalation Not a normal route of exposure. If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.

Ingestion Not a normal route of exposure. Do not induce vomiting, Never give anything by mouth if victim is unconscious, or is convulsing. Obtain medical attention.



Corporate Headquarters
10 Glenshaw Street, Orangeburg, NY 10962
Tel: 845.365.8200 • Fax: 845.365.8201
Toll-Free: 888.DYNAREX

Notes to physician

Symptoms may be delayed.

General advice

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Keep out of reach of children. Avoid contact with eyes.

Flammable Limits: N/A

Flash Point: N/A

SECTION 5. Fire-fighting measures

Flash Point: Not Available
Flammable Limits: Not Available
Extinguishing Media: Any
Special Fire Fighting Procedures: None
Unusual Fire and Explosion Hazards: None

SECTION 6. Accidental release measures

Personal precautions: Keep unnecessary personnel away. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak.

Methods for containment: Prevent entry into waterways, sewers, basements or confined areas.

Methods for cleaning up: Pick up and discard towel.

SECTION 7. Handling and storage

Handling: Use good industrial hygiene practices in handling this material.

Storage: Keep out of reach of children. Store in a closed container away from incompatible materials.



Corporate Headquarters
10 Glenshaw Street, Orangeburg, NY 10962
Tel: 845.365.8200 • Fax: 845.365.8201
Toll-Free: 888.DYNAREX

SECTION 8. Exposure controls/personal protection

Engineering controls:	General ventilation normally adequate.
Personal protective equipment	
Eye/Face protection	Follow standard industrial hygiene practices.
Hand protection	Not required.
Skin and body protection	As required by employer code.
Respiratory protection	Where exposure guideline levels may be exceeded, use and approved NIOSH respirator.
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink.

SECTION 9. Physical and chemical properties

Appearance/Odor:	Liquid saturated on wipe
Color:	Clear liquid
Form:	Liquid saturated on wipe
Odor:	Characteristic
Odor Threshold:	Not available
Physical State:	Solid
Boiling Point:	<200°F
Paper Components:	100% Virgin Paper
Specific Gravity:	1

SECTION 10. Stability and reactivity

Chemical Stability: Stable under recommended storage conditions.
Incompatibility: Caustics. Acids. Oxidizers.



Corporate Headquarters
 10 Glenshaw Street, Orangeburg, NY 10962
 Tel: 845.365.8200 • Fax: 845.365.8201
 Toll-Free: 888.DYNAREX

Hazardous Decomposition Products: May include and are not limited to: oxides of carbon; hydrogen chloride.

Hazardous Polymerization: Will not occur.

Conditions to avoid: Do not mix with other chemicals.

SECTION 11. Toxicological information

Effects of acute exposure

Eye	May cause irritation
Skin	In case of skin irritation, discontinue use of the product.
Inhalation	Not a normal route of exposure. May cause respiratory tract irritation.
Ingestion	Not a normal route of exposure. May cause stomach distress, nausea or vomiting.
Sensitization	Non-hazardous by WHMIS/OSHA criteria.
Chronic Effects	Non-hazardous by WHMIS/OSHA criteria.
Carcinogenicity	Non-hazardous by WHMIS/OSHA criteria.
Mutagenicity	Non-hazardous by WHMIS/OSHA criteria.
Reproductive Effects	Non-hazardous by WHMIS/OSHA criteria.
Teratogenicity	Non-hazardous by WHMIS/OSHA criteria.

SECTION 12. Ecological information

Ecotoxicity Not available

Environmental effects Not available

Aquatic toxicity Not available

Persistence / degradability Not available

Bioaccumulation / accumulation Not available



Corporate Headquarters
10 Glenshaw Street, Orangeburg, NY 10962
Tel: 845.365.8200 • Fax: 845.365.8201
Toll-Free: 888.DYNAREX

Partition coefficient Not available

Mobility in environmental media Not available

Chemical fate information Not available

Other adverse effects Not available

SECTION 13. Disposal considerations

Waste codes: Not available

Disposal instructions: Discard after single use.

Review federal, state/provincial, and local government requirements prior to disposal.

Discard with solid waste. Dispose in accordance with all applicable regulations.

Waste from residues / unused products: Not available

Contaminated packaging: Not available

SECTION 14. Transport information

U.S. Department of Transportation (DOT) Not regulated as dangerous goods.

Transportation of Dangerous Goods (TDG - Canada) Not regulated as dangerous goods.

SECTION 15. Regulatory information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US Federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

Occupational Safety and Health Administration (OSHA)



Corporate Headquarters
10 Glenshaw Street, Orangeburg, NY 10962
Tel: 845.365.8200 • Fax: 845.365.8201
Toll-Free: 888.DYNAREX

29 CFR 1910.1200 hazardous No chemical

CERCLA (Superfund) reportable quantity

Benzene: 10.0000
Benzene, methyl-: 1000.0000
Benzene, (chloromethyl)-: 100.0000
Propylene oxide: 100.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - No
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

Section 302 extremely hazardous substance No

Section 311 hazardous chemical No

Clean Air Act (CAA) Not available

Clean Water Act (CWA) Not available

Safe Drinking Water Act (SDWA) Not available

Drug Enforcement Agency (DEA) Not available

Food and Drug Administration (FDA) Not available

State regulations WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

SECTION 16. Other information

Disclaimer:

This Safety Data Sheet, which takes into consideration the requirements of Directive 76/768/EC and subsequent amendments and Directive 1999/45/EC plus subsequent amendments, has been prepared in accordance with Directive (EC) 1907/2006. It is believed to be correct and corresponds to the latest scientific/technical knowledge but all data, instructions, recommendations and/or suggestions are made without guarantee. No warranty, expressed or implied, is made and Dynarex Corp. assumes no legal responsibility or liability resulting from its use.



Corporate Headquarters
10 Glenshaw Street, Orangeburg, NY 10962
Tel: 845.365.8200 • Fax: 845.365.8201
Toll-Free: 888.DYNAREX

Reviewed on 5/4/15

SAFETY DATA SHEET

SECTION 1. Product and Company Identification

PRODUCT NAME: Alcohol Preparation Pads/Swab

RECOMMENDED USE: Topical skin antiseptic

Product Code: AM-20200, 1113, 1114, 1116, PK-1114

Manufacturer's Name: Dynarex Corporation

Manufacturer's Address: 10 Glenshaw Street
Orangeburg, NY 10962

Emergency or Information Phone No.: 888-DYNAREX or 845-365-8200
At other times, contact the local Poison Control Center

SECTION 2. Hazards Identification

Main Hazards:

Highly flammable; irritation to eyes; vapor may cause drowsiness and dizziness

Absorption:

Eye contact; ingestion; inhalation; skin contact

Carcinogenic Status:

Not considered carcinogenic by NTP, IARC, and OSHA

Target Organs:

Central nerves system; skin; eye; liver; respiratory system

Health Effects:



Corporate Headquarters
10 Glenshaw Street, Orangeburg, NY 10962
Tel: 845.365.8200 • Fax: 845.365.8201
Toll-Free: 888.DYNAREX

Eyes – Liquid, mist or vapor will cause conjunctival irritation and possible corneal damage.

Skin – Repeated or prolonged contact may produce defatting of the skin leading to irritation and dermatitis. Liquid may be absorbed through the skin but not in toxicologically significant amounts, unless the contact area is large and under prolonged exposure.

Ingestion – Swallowing a small amount may have the effect of any of these symptoms: irritation of mouth, throat, digestive tract, and central nerves system depression.

Ingestion – A large dose may have the effect of any of these symptoms: dizziness, drowsiness, headache, mental confusion, nerve damage leading to numbness and muscle weakness, fall of blood pressure, liver damage, lung damage.

Inhalation – Exposure to vapor may have the effect of any of these symptoms: irritation of nose, throat and respiratory tract, central nerve system depression.

Inhalation – Exposure to vapor at high concentration may have the effects of any of these symptoms: dizziness, drowsiness, headache, mental confusion, lung damage, fall of blood pressure, liver damage, nerve damage leading to numbness and muscle weakness.

SECTION 3. Composition/information on Ingredients

Hazardous Ingredients (specific)	% Composition	CAS Number
Isopropyl Alcohol (2-Propanol)	70%	67-63-0
Inactive Ingredient		
Water	30%	7732-18-5



Corporate Headquarters
10 Glenshaw Street, Orangeburg, NY 10962
Tel: 845.365.8200 • Fax: 845.365.8201
Toll-Free: 888.DYNAREX

SECTION 4. First-aid measures

Eyes:

Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention if soreness or redness persists.

Skin:

Immediately flood the affected skin area with large quantity of water, preferably under a shower. Remove contaminated clothing and continue washing. Contaminated clothing should be washed thoroughly before re-use. Obtain medical attention if blistering of the skin occurs or redness persists.

Ingestion:

Do not induce vomiting. Have victim drink several large glasses of water to dilute the stomach contents. Give the victim oxygen if he/she has difficulty in breathing. Obtain medical attention immediately.

Inhalation:

Remove the victim from exposure immediately. Give the victim oxygen if he/she has difficulty in breathing. Obtain medical attention immediately.

MEDICAL PERSONNEL:

Monitor the victim for systemic secondary effects on liver and kidney functions. Support and treat as appropriate.

SECTION 5. Fire-fighting measures

Flash Point – 20°C/68°F

Boiling Point – 80°C/176°F



Corporate Headquarters
10 Glenshaw Street, Orangeburg, NY 10962
Tel: 845.365.8200 • Fax: 845.365.8201
Toll-Free: 888.DYNAREX

Extinguishing Media – Dry Chemical or Alcohol Type Foam, Carbon Dioxide

Be aware of the possibility of re-ignition. Keep containers and surroundings cool with water spray.

Unusual Fire and Explosion Hazards –

Class 3 Flammability. Vapor can travel a considerable distance to a source of ignition and flashback. Flashback can occur if air temperature exceeds flash point. Be aware the possibility of re-ignition.

Special Fire Fighting Procedures –

Handle as Flammable Liquid. Use Respiratory Protection. Wear full protective clothing for Fire Fighting Personnel.

SECTION 6. Accidental release measures

- Flush spills with water.
- Contain and absorb using soil, sand, or other inert material.
- Vapor can accumulate in low areas. Consider the need for evacuation.
- Prevent the material from entering drains or water courses.

SECTION 7. Handling and storage

- Eliminate all sources of ignition. Store away from heat.
- Store in well ventilated area.
- Handle as flammable liquid. Follow local, state and federal regulations.
- Avoid inhaling vapor. Avoid contact with eyes, skin and clothing.
- Wear eye protection if splashing is expected.
- Wear appropriate protective clothing.
- Use respirator if exposure level is high when handling bulk liquid.
- Keep container tightly closed when not in use.



Corporate Headquarters
10 Glenshaw Street, Orangeburg, NY 10962
Tel: 845.365.8200 • Fax: 845.365.8201
Toll-Free: 888.DYNAREX

SECTION 8. Exposure controls/personal protection

- OSHA Occupation Exposure Standards PEL 400ppm (980mg/m³) 8h TWA
- UK EH40: OES 400ppm (980mg/m³) 8h TWA
- UK EH40: OES 500ppm (1225mg/m³) 15min TWA
- ACGIH: TLV 200ppm (980mg/m³) 8h TWA
- ACGIH: STEL 400ppm (1225mg/m³) 15min TWA
- Personal Protective Equipment
 - Gloves
 - Eye
 - Clothing

SECTION 9. Physical and chemical properties

Appearance – Liquid Saturated Towelette / Pad / Swab
Color – Clear
Odor – Alcohol
Vapor Density – 2.1 (Air = 1)
Viscosity (cSt) – 2.9 cps at <@2> °C

Evaporation Rate – Environmental Dependent
Water Solubility – Complete
Specific Gravity – 0.8405

SECTION 10. Stability and reactivity

Stability – Stable under normal conditions
Conditions to Avoid – None
Incompatibility – None
Hazardous Decomposition or By-product – Oxides of carbon



Corporate Headquarters
10 Glenshaw Street, Orangeburg, NY 10962
Tel: 845.365.8200 • Fax: 845.365.8201
Toll-Free: 888.DYNAREX

Polymerization –

Will Not Occur.

SECTION 11. Toxicological information

Acute Toxicity

- Low level of acute toxicity predicted.
- May be harmful by skin absorption.
- Oral LD50 (rat) 5045mg/kg.
- Dermal LD50 (rabbit) 12800mg/kg.
- Inhalation LCLO (rat) 1600ppm 4h.

Chronic Toxicity / Carcinogenicity

- Material not expected to cause long-term adverse health effects.
- Material not classifiable as to its carcinogenicity to humans (Group 3).
- Chronic / Sub-chronic studies resulted in adverse effects to:
 - Liver, spleen, biochemical effects, brain tissue degeneration, changes in reflex behavior, sensory nerve damage.

Genealogy Toxicity

- Material is not expected to cause any mutagenic effects.

Reproductive / Developmental Toxicity

- Material is not expected to cause reproductive or developmental health effects.
- Experimental studies in animals have provided some evidence of embryo / fetus toxicity and birth defects only at does producing marked maternal toxicity.

SECTION 12. Ecological information

- Mobility



Corporate Headquarters
10 Glenshaw Street, Orangeburg, NY 10962
Tel: 845.365.8200 • Fax: 845.365.8201
Toll-Free: 888.DYNAREX

- If released to soil, IPA is expected to have very high mobility
- Persistence / Degradability
- IPA is readily degraded in aerobic aqueous systems
- Bio-accumulation

- Low potential for bio-concentration in aquatic organisms

SECTION 13. Disposal considerations

- Transfer into suitable containers for recovery or disposal.
- Dispose in accordance with all applicable local and national regulations.
- Do not remove labels from container until the container has been cleaned.
- Do not cut, puncture or weld on or near the container.
- Do not incinerate closed containers.
- Empty containers may contain hazardous residues

SECTION 14. Transport information

- DOT CFR 172.101
- Not regulated per 49 CFR 173.4 Small Quantity Exemption

SECTION 15. Regulatory information

This product is compliant with the following:

- EU Label: Classification and labeling have been performed according to EU Directive 67/548/EEC and 99/45/EC including amendments
- EU Hazard Symbol and Indication of Danger
- F – Highly flammable
- Xi – Irritant
- R11 – Highly flammable



Corporate Headquarters
10 Glenshaw Street, Orangeburg, NY 10962
Tel: 845.365.8200 • Fax: 845.365.8201
Toll-Free: 888.DYNAREX

- R36 – Irritating to eyes
- R67 – Vapors may cause drowsiness and dizziness
- S2 – Keep out of reach of children
- S7 – Keep container tightly closed
- S16 – Keep away from sources of ignition – No smoking
- S24 / S25 – Avoid contact with skin and eyes
- S26 – In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- US (Federal and State) Regulations and International Chemical Registration Laws TSCA listing
- This product contains ingredients that are listed on or exempt from listing on the EPA Toxic Substance Control Act Chemical Inventory
- This product does not contain any chemicals subject to EPA Title III of the SARA Listing in Sections 302 and 304
- All ingredients in this product are listed on the European Inventory of Existing Commercial Chemical Substance (EINECS Listing) or are exempted from listing
- All ingredients in this product are listed on the Canada Domestic Substance List (DSL Listing)

SECTION 16. Other information

Disclaimer:

This Safety Data Sheet, which takes into consideration the requirements of Directive 76/768/EC and subsequent amendments and Directive 1999/45/EC plus subsequent amendments, has been prepared in accordance with Directive (EC) 1907/2006. It is believed to be correct and corresponds to the latest scientific/technical knowledge but all data, instructions, recommendations and/or suggestions are made without guarantee. No warranty, expressed or implied, is made and Dynarex Corp. assumes no legal responsibility or liability resulting from its use.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Trade name : Medicaine® Sting and Bite Relief

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : OTC drug used as a topical analgesic
 Use of the substance/mixture : For professional use only

1.3. Details of the supplier of the safety data sheet

James Alexander Corporation
 845 Route 94 Blairstown
 NJ 07825

Tel: (908) 362-9266

Note: The CHEMTREC emergency number is to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals. All non-emergency questions should be directed to JAC at (908) 362-9266.

1.4. Emergency telephone number

Emergency number : Chemtrec (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 2 H225
 Eye Irrit. 2A H319
 STOT SE 3 H335
 STOT SE 3 H336

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapour
 H319 - Causes serious eye irritation
 H335 - May cause respiratory irritation
 H336 - May cause drowsiness or dizziness

Precautionary statements (GHS-US) : P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
 P233 - Keep container tightly closed
 P240 - Ground/bond container and receiving equipment
 P241 - Use explosion-proof electrical, lighting, ventilating equipment
 P242 - Use only non-sparking tools
 P243 - Take precautionary measures against static discharge
 P261 - Avoid breathing dust, fume, mist, spray, vapours
 P264 - Wash hands thoroughly after handling
 P271 - Use only outdoors or in a well-ventilated area
 P280 - Wear eye protection, protective clothing, protective gloves
 P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 P304+P340 - IF INHALED: remove victim to fresh air and keep at rest in a position comfortable for breathing
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P312 - Call a POISON CENTER/doctor/physician if you feel unwell
 P337+P313 - If eye irritation persists: get medical advice/attention

Medicaine[®] Sting and Bite Relief

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

P370+P378 - In case of fire: Use dry chemical, foam, carbon dioxide for extinction
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to comply with applicable local, national and international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Polyethylene glycol	(CAS No) 25322-68-3	50 - 55	STOT SE 3, H335
Isopropyl alcohol	(CAS No) 67-63-0	20 - 25	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
L-Menthol	(CAS No) 2216-51-5	1	Skin Irrit. 2, H315 Eye Irrit. 2A, H319

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. If breathing stops, give artificial respiration. In case of breathing difficulties administer oxygen. by trained personnel. Seek medical attention immediately.
- First-aid measures after skin contact : Immediately flush skin with plenty of water for at least 15 minutes. Remove/Take off immediately all contaminated clothing. Do not rub the skin and eyes after direct contact with the product. Seek medical attention immediately. Wash contaminated clothing before reuse.
- First-aid measures after eye contact : In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately get medical attention.
- First-aid measures after ingestion : Contact a Poison Control Center immediately. Give no more than 2 glasses of water and induce vomiting by giving 30 cc (2 tablespoons) of syrup of ipecac. If victim is a child, give no more than 1 glass of water and 15cc (1 tablespoon) syrup of ipecac. If syrup of ipecac is unavailable, give 2 glasses of water and induce vomiting by touching finger to back of victim's throat. Do not give anything by mouth to an unconscious or convulsing person. Get immediate medical attention. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory irritation. May cause drowsiness or dizziness. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
- Symptoms/injuries after skin contact : Repeated or prolonged skin contact may cause irritation.
- Symptoms/injuries after eye contact : Causes serious eye irritation.
- Symptoms/injuries after ingestion : Irritating to the gastrointestinal tract. May cause abdominal pain and vomiting (sometimes bloody). Ingestion may cause central nervous system depression, low blood pressure, rapid heart beat and liver damage. Early to moderate central nervous system depression may be evidenced by giddiness, headache, dizziness and nausea. In extreme cases, unconsciousness, respiratory depression and death may occur. Liver damage may be evidenced by loss of appetite, jaundice (yellowish skin color) and sometimes pain in the upper abdomen on the right side.

4.3. Indication of any immediate medical attention and special treatment needed

Individuals with pre-existing skin disorders, eye problems, or impaired respiratory function may be more susceptible to the effects of overexposure.

Medicaine[®] Sting and Bite Relief

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Alcohol resistant foam. Dry powder. Carbon dioxide. Sand.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapour.
Explosion hazard : May form flammable/explosive vapour-air mixture.
Reactivity : Thermal decomposition generates : Corrosive vapours. Reacts violently with acids. An exothermic reaction may occur.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protective equipment for firefighters : Do not enter fire area without proper protective equipment, including respiratory protection.
Other information : Containers may swell and Burst during a fire due to internal pressure caused by heat. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. Alcohols burn with a pale blue flame which may be extremely hard to see under normal lighting conditions. Personnel may be able to feel the heat of the fire without seeing flames. Extreme caution must be exercised in fighting alcohol fires.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Eliminate all ignition sources if safe to do so. Use special care to avoid static electric charges. No naked lights. No smoking. Stop leak if safe to do so. No action shall be taken involving any personal risk or without suitable training. Wear protective clothing. For further information refer to section 8 : Exposure-controls/personal protection.

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

- Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Consult the appropriate authorities about waste disposal. Ensure all national/local regulations are observed.

6.4. Reference to other sections

- See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.
Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Personal protective equipment should be selected based upon the conditions under which this product is handled or used. Use personal protective equipment as required. Provide good ventilation in process area to prevent formation of vapour. Do not breathe gas, fumes, vapour or spray. No naked lights. No smoking. Use only non-sparking tools. Never use pressure to empty container. Ground/bond container and receiving equipment. Take care to allow internal pressure to escape from container before releasing closures. Remove closure carefully; internal pressure may be present. Keep closure up to prevent leakage. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Medicaine[®] Sting and Bite Relief

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Ensure the ventilation system is regularly maintained and tested. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of mists and/or vapors below the recommended exposure limits. Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. A washing facility/water for eye and skin cleaning purposes should be present. Comply with applicable regulations.
- Storage conditions : Keep only in the original container in a cool well ventilated place. Keep in fireproof place. Keep container tightly closed. Protect containers against physical damage. Detached outside storage is preferable. Inside storage should be in an NFPA approved flammable liquids storage room or cabinet. Store in corrosion-proof area at temperatures below 77 °F (25°C). Store away from direct sunlight or other heat sources.
- Incompatible materials : Avoid mixing with acids, most common metals, strong oxidizing agents, brass, zinc, chlorine, aluminum, copper, bronze, mercury, dimethyl sulfate and acetyl chloride.
- Storage temperature : < 25 °C Store at temperatures below 77 °F (25 °C)

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Isopropyl alcohol (67-63-0)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	400 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm

8.2. Exposure controls

- Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of mists and/or vapors below the recommended exposure limits. Use explosion-proof ventilating equipment.
- Personal protective equipment : Avoid all unnecessary exposure. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to OSHA regulations. For certain operations, additional Personal Protection Equipment (PPE) may be required. Protective goggles. Gloves. Protective clothing.



- Hand protection : Wear protective gloves. rubber gloves. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.
- Eye protection : Chemical goggles or face shield.
- Skin and body protection : Wear suitable protective clothing. Chemical resistant safety shoes.
- Respiratory protection : Wear a self-contained breathing apparatus and appropriate personal protective equipment (PPE). Suggestions provided in this section for exposure control and specific types of protective equipment are based on readily available information. Users should consult with the specific manufacturer to confirm the performance of their protective equipment. Specific situations may require consultation with industrial hygiene, safety, or engineering professionals. Care must be taken to assure that any respirator chosen is capable of protecting the user from both ammonia and ethyl alcohol vapors.
- Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Clear.
- Colour : Green.
- Odour : Odor of isopropyl alcohol, residual odor of menthol.

Medicaine[®] Sting and Bite Relief

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Odour threshold	: No data available
pH	: 8.5
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 35 °C (>95 °F)
Flash point	: 16.6 °C (62 °F)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.029 (Specific Gravity @ 25 °C)
Solubility	: Soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates : Corrosive vapours. Reacts violently with acids. An exothermic reaction may occur.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

Avoid mixing with acids, most common metals, strong oxidizing agents, brass, zinc, chlorine, aluminum, copper, bronze, mercury, dimethyl sulfate and acetyl chloride.

10.6. Hazardous decomposition products

Thermal decomposition generates : Fume. Carbon monoxide. Carbon dioxide. May release flammable gases. Corrosive vapours. Ammonia. Nitrogen oxides. release of highly flammable gases/vapours hydrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified
(Based on available data, the classification criteria are not met)

Isopropyl alcohol (67-63-0)	
LD50 oral rat	4396 mg/kg
LD50 dermal rabbit	12800 mg/kg
LC50 inhalation rat (ppm)	16000 ppm (Exposure time: 8 h)
ATE CLP (oral)	4396.000 mg/kg bodyweight
ATE CLP (dermal)	12800.000 mg/kg bodyweight

Medicaine[®] Sting and Bite Relief

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

L-Menthol (2216-51-5)	
LD50 oral rat	3300 mg/kg
ATE CLP (oral)	3300.000 mg/kg bodyweight

Polyethylene glycol (25322-68-3)	
LD50 dermal rabbit	> 20 ml/kg

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: 8.5
Serious eye damage/irritation	: Causes serious eye irritation. pH: 8.5
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)

Isopropyl alcohol (67-63-0)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
Specific target organ toxicity (single exposure)	: May cause respiratory irritation. May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause respiratory irritation. May cause drowsiness or dizziness. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/injuries after skin contact	: Repeated or prolonged skin contact may cause irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: Irritating to the gastrointestinal tract. May cause abdominal pain and vomiting (sometimes bloody). Ingestion may cause central nervous system depression, low blood pressure, rapid heart beat and liver damage. Early to moderate central nervous system depression may be evidenced by giddiness, headache, dizziness and nausea. In extreme cases, unconsciousness, respiratory depression and death may occur. Liver damage may be evidenced by loss of appetite, jaundice (yellowish skin color) and sometimes pain in the upper abdomen on the right side.

SECTION 12: Ecological information

12.1. Toxicity

Isopropyl alcohol (67-63-0)	
LC50 fishes 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

L-Menthol (2216-51-5)	
LC50 fishes 1	18.9 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

12.2. Persistence and degradability

Medicaine[®] Sting and Bite Relief	
Persistence and degradability	Not established.

Medicaine[®] Sting and Bite Relief

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

12.3. Bioaccumulative potential

Medicaine [®] Sting and Bite Relief	
Bioaccumulative potential	Not established.
Isopropyl alcohol (67-63-0)	
Log Pow	0.05 (at 25 °C)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not re-use empty containers. Ensure all national/local regulations are observed. Consult the appropriate authorities about waste disposal.

Additional information : Handle empty containers with care because residual vapours are flammable.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1993 Flammable liquids, n.o.s. (contains isopropanol), 3, II

UN-No.(DOT) : 1993

DOT NA no. : UN1993

DOT Proper Shipping Name : Flammable liquids, n.o.s.
(contains isopropanol)

Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



DOT Symbols : G - Identifies PSN requiring a technical name

Packing group (DOT) : II - Medium Danger

DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Packaging Non Bulk (49 CFR 173.xxx) : 202

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

Medicaine[®] Sting and Bite Relief

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Additional information

Other information : No supplementary information available.

ADR

Transport document description :

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Isopropyl alcohol (67-63-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on SARA Section 313 (Specific toxic chemical listings)

EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
--------------------------	--

SARA Section 313 - Emission Reporting	1.0 % (only if manufactured by the strong acid process, no supplier notification)
---------------------------------------	---

L-Menthol (2216-51-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Polyethylene glycol (25322-68-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Isopropyl alcohol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

L-Menthol (2216-51-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Polyethylene glycol (25322-68-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

Isopropyl alcohol (67-63-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

L-Menthol (2216-51-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

Polyethylene glycol (25322-68-3)

Listed on the EU - No-Longer Polymers List (67/548/EEC)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

Medicaine[®] Sting and Bite Relief

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

15.2.2. National regulations

Isopropyl alcohol (67-63-0)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on Industrial Safety and Health Law Substances (ISHL)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the Canadian Ingredient Disclosure List

L-Menthol (2216-51-5)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on Industrial Safety and Health Law Substances (ISHL)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)

Polyethylene glycol (25322-68-3)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)

15.3. US State regulations

No additional information available

SECTION 16: Other information

Other information : None.


Full text of H-phrases: see section 16:

Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapour
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



SDS US (GHS HazCom 2012)

Medicaine[®] Sting and Bite Relief

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

This Material Safety Data Sheet is intended only as a guide to the appropriate precautionary handling of the material by a person trained in, or supervised by a person trained in, the safe handling of chemical materials. James Alexander Corporation (JAC), expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose with respect to the product or information provided herein. All information appearing herein is based upon data obtained from the manufacturer(s) and/or recognized technical sources. While the information is believed to be accurate, JAC makes no representations as to its accuracy or sufficiency. Conditions of use are beyond JAC's control and therefore, users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein and does not relate to its use in combination with any other material or in any other process.

SAFETY MATCHES

Material Safety Data Sheet

(essentially similar to OSHA form 20)

Manufactured by: Atlas Match, LLC
1801 South Airport Circle
Eules, Texas 76040

Phone: (817) 354-7474

Last revision Date: September 1, 2009

Product Information

Generic ID: Matches, Safety, Book or Strike on Box UN 1944
Brand Name: Atlas Book Matches, Advertising Book Matches and, various stock and special design names.

Hazard Class: Flammable Solid
Label Required: None (exception 49CFR 173.186c)

Hazardous Ingredients

<u>Ingredient</u>	<u>Percent</u>	<u>PEL</u>	<u>Hazard</u>
Potassium Chlorate	3.0%	NE	Strong Oxidizer
Red Phosphorous	<1.0%	NE	Flammable Solid

Physical Data

Appearance and Odor: Odorless manufactured article – wood or paper stem with matchhead.
Solubility in Water: Non-paper components are partially soluble
Specific Gravity: < 1.0 (water = 1.0)
Boiling Point: NA
Vapor Pressure and Density: NA
Percent Volatile: 0 to 7% moisture
Evaporation Rate: NA

Fire and Explosion Hazard Data

Flash Point: NA
Flammable Limits: NA
Auto-ignition Point: Approx. 375 degrees F, Stable at 200 degrees F for 8 hours
Extinguishing Media: Water or ABC dry chemical extinguisher

Special Fire Fighting Procedures

1. Do not open sealed packages until fire is controlled, in order to limit oxygen availability.
2. Smoke from significant fire involvement will contain Oxides of Carbon and Sulfur Dioxide which is hazardous (TLV 2ppm), use self contained breathing apparatus.

Unusual Fire/Explosion Hazards

Possibility of ignition if subjected to extreme shock or friction.

Health Hazard Data

Threshold Limit Value: None known for product
Effects of overexposure: Contact with product while functioning can result in thermal burn.
First Aid Procedure: Burns should be immersed in cold water (unless area is extensive and 3rd degree) to relieve pain. Cover with sterile dressing and seek medical attention if required.

Reactivity Data

Stability: Stable
Conditions to avoid: Avoid temperature over 200 degrees F and extreme shock.
Incompatibility: Exposure to water or extreme dampness may effect performance; strong acids and phosphorus (red or yellow forms) may cause ignition.
Hazardous Polymerization: Will not occur.

Spill or Leak Procedures

For spills including loose matches or broke cases

Keep unnecessary personnel, open flames (including flares), heat sources and sparks away from area. Wet spilled material thoroughly before attempting clean up. Place in non-flammable container and submerge in water for one hour before disposal.

For unopened cases

Evaluate each case for possible ignition, looking for signs of smoke or warmth. Do not open any case which is warm or smoking, wet it down and dispose of when cool. Full cases not affected can be considered safe to use.

Disposal

Dispose of matches after at least one hour submersion under water by incineration or landfilling in accordance with local, state and federal regulations.

California Users-Special Instructions:

The match tips in this product contain perchlorate materials. Special handling may apply in California.
See: www.dtsc.ca.gov/hazardouswaste/perchlorate.

Special Precautions

Protective equipment: None normally required
Ventilation: Natural is sufficient for normal use
Precautions for handling and storage: Store in a cool, dry location. Avoid crushing or extreme mechanical shock.
Other precautions: Close book before striking. Strike away from face and body.

The information accumulated herein is believed to be accurate, but is not warranted to be. Recipients are advised to confirm in advance of need that the information is current, applicable and suitable to their circumstances.

NEW SPECIAL PERMIT

Application No.	Docket No.	Applicant	Regulation(s) Affected	Nature of Special Permit Thereof
14420-N	Garden State Tobacco d/ b/a H.J. Bailey Co., Neptune, NJ.	49 CFR 173.186(c)	To authorize the transportation in commerce of strike anywhere matches in non-DOT specification packages not exceeding 50 pounds each by private motor carrier not subject to the Hazardous Materials Regulations, except for marking. (mode 1).