

SAFETY DATA SHEET

EFFECTIVE DATE: 06/06/17

ITEM: Roadside Emergency Kit

PART # UPC 8900 039147089005 8900S same

CONTENTS:

Alcohol Prep / Swab SDS
Antiseptic Towelette SDS
Red Emergency Flare SDS
Lightstick SDS
Moist Towelette SDS
Sting and Bite Pad SDS



Reviewed on 5/4/15

SAFETY DATA SHEET

SECTION 1. Product and Company Identification

PRODUCT NAME: Alcohol Preparation Pads/Swab

RECOMMENDED USE: Topical skin antiseptic

Product Code: AM-20200, 1113, 1114, 1116, PK-1114

Manufacturer's Name: Dynarex Corporation

Manufacturer's Address: 10 Glenshaw Street

Orangeburg, NY 10962

Emergency or Information 888-DYNAREX or 845-365-8200

Phone No.: At other times, contact the local Poison Control Center

SECTION 2. Hazards Identification

Main Hazards:

Highly flammable; irritation to eyes; vapor may cause drowsiness and dizziness

Absorption:

Eye contact; ingestion; inhalation; skin contact

Carcinogenic Status:

Not considered carcinogenic by NTP, IARC, and OSHA

Target Organs:

Central nerves system; skin; eye; liver; respiratory system

Health Effects:





Corporate Headquarters
10 Glenshaw Street, Orangeburg, NY 10962
Tel: 845.365.8200 • Fax: 845.365.8201

Toll-Free: 888.DYNAREX

- Eyes Liquid, mist or vapor will cause conjunctival irritation and possible corneal damage.
- Skin Repeated or prolonged contact may produce defatting of the skin leading to irritation and dermatitis. Liquid may be absorbed through the skin but not in toxicologically significant amounts, unless the contact area is large and under prolonged exposure.
- Ingestion Swallowing a small amount may have the effect of any of these symptoms: irritation of mouth, throat, digestive tract, and central nerves system depression.
- Ingestion A large dose may have the effect of any of these symptoms: dizziness, drowsiness, headache, mental confusion, nerve damage leading to numbness and muscle weakness, fall of blood pressure, liver damage, lung damage.
- Inhalation Exposure to vapor may have the effect of any of these symptoms: irritation of nose, throat and respiratory tract, central nerve system depression.
- Inhalation Exposure to vapor at high concentration may have the effects of any of these symptoms: dizziness, drowsiness, headache, mental confusion, lung damage, fall of blood pressure, liver damage, nerve damage leading to numbness and muscle weakness.

SECTION 3. Composition/information on Ingredients

Hazardous Ingredients (specific)	% Composition	CAS Number
Isopropyl Alcohol (2-Propanol)	70%	67-63-0
Inactive Ingredient		
Water	30%	7732-18-5





10 Glenshaw Street, Orangeburg, NY 10962 Tel: 845.365.8200 • Fax: 845.365.8201

Toll-Free: 888.DYNAREX

SECTION 4. First-aid measures

Eves:

Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention if soreness or redness persists.

Skin:

Immediately flood the affected skin area with large quantity of water, perferably under a shower. Remove contaminated clothing and continue washing. Contaminated clothing should be washed throughly before re-use. Obtain medical attention if blistering of the skin occures or redness persists.

Ingestion:

Do not induce vomiting. Have victim drink serval large glasses of water to dilute the stomach contents. Give the victim oxygen if he/she has difficulty in breathing. Obtain medical attention immediately.

Inhalation:

Remove the victim from exposure immediately. Give the victim oxygen if he/she has difficulty in breathing. Obtain medical attention immediately.

MEDICAL PERSONNEL:

Monitor the victim for systemic secondary effects on liver and kidney functions. Support and treat as appropriate.

SECTION 5. Fire-fighting measures

Flash Point – 20°C/68°F

Boiling Point – 80°C/176°F





Corporate Headquarters

10 Glenshaw Street, Orangeburg, NY 10962 Tel: 845.365.8200 • Fax: 845.365.8201

Toll-Free: 888.DYNAREX

Extinguishing Media – Dry Chemical or Alcohol Type Foam, Carbon Dioxide

Be aware of the possibility of re-ignition. Keep containers and surroundings cool with water spray.

Unusual Fire and Explosion Hazards –

Class 3 Flammability. Vapor can travel a considerable distance to a source of ignition and flashback. Flashback can occur if air temperature exceeds flash point. Be aware the possibility of re-ignition.

Special Fire Fighting Procedures –

Handle as Flammable Liquid. Use Respiratory Protection. Wear full protective clothing for Fire Fighting Personnel.

SECTION 6. Accidental release measures

- Flush spills with water.
- Contain and absorb using soil, sand, or other inert material.
- Vapor can accumulate in low areas. Consider the need for evacuation.
- Prevent the material from entering drains or water courses.

SECTION 7. Handling and storage

- Eliminate all sources of ignition. Store away from heat.
- Store in well ventilated area.
- Handle as flammable liquid. Follow local, state and federal regulations.
- Avoid inhaling vapor. Avoid contact with eyes, skin and clothing.
- Wear eye protection if splashing is expected.
- Wear appropriate protective clothing.
- Use respirator if exposure level is high when handling bulk liquid.
- Keep container tightly closed when not in use.





SECTION 8. Exposure controls/personal protection

- OSHA Occupation Exposure Standards PEL 400ppm (980mg/m3) 8h TWA
- UK EH40: OES 400ppm (980mg/m3) 8h TWA
- UK EH40: OES 500ppm (1225mg/m3) 15min TWA
- ACGIH: TLV 200ppm (980mg/m3) 8h TWA
- ACGIH: STEL 400ppm (1225mg/m3) 15min TWA
- Personal Protective Equipment
 - Gloves
 - Eye
 - Clothing

SECTION 9. Physical and chemical properties

Appearance – Liquid Saturated Towelette / Pad / Swab

Color – Clear Odor – Alcohol Vapor Density – 2.1 (Air = 1)

Viscosity (cSt) – 2.9 cps at <@2> °C

Evaporation Rate – Environmental Dependent

Water Solubility – Complete Specific Gravity – 0.8405

SECTION 10. Stability and reactivity

Stability – Stable under normal conditions

Conditions to Avoid – None Incompatibility – None

Hazardous Decomposition or By-product – Oxides of carbon





Polymerization -

Will Not Occur.

SECTION 11. Toxicological information

Acute Toxicity

- Low level of acute toxicity predicted.
- May be harmful by skin absorption.
- Oral LD50 (rat) 5045mg/kg.
- Dermal LD50 (rabbit) 12800mg/kg.
- Inhalation LCLO (rat) 1600ppm 4h.

Chronic Toxicity / Carcinogenicity

- Material not expected to cause long-term adverse health effects.
- Material not classifiable as to its carcinogenicity to humans (Group 3).
- Chronic / Sub-chronic studies resulted in adverse effects to:
 - Liver, spleen, biochemical effects, brain tissue degeneration, changes in reflex behavior, sensory nerve damage.

Genealogy Toxicity

Material is not expected to cause any mutagenic effects.

Reproductive / Developmental Toxicity

- Material is not expected to cause reproductive or developmental health effects.
- Experimental studies in animals have provided some evidence of embryo / fetus toxicity and birth defects only at does producing marked maternal toxicity.

SECTION 12. Ecological information

Mobility





Corporate Headquarters 10 Glenshaw Street, Orangeburg, NY 10962

Tel: 845.365.8200 • Fax: 845.365.8201

Toll-Free: 888.DYNAREX

- If released to soil, IPA is expected to have very high mobility
- Persistence / Degradability
- IPA is readily degraded in aerobic aqueous systems
- Bio-accumulation
- Low potential for bio-concentration in aquatic organisms

SECTION 13. Disposal considerations

- Transfer into suitable containers for recovery or disposal.
- Dispose in accordance with all applicable local and national regulations.
- Do not remove labels from container until the container has been cleaned.
- Do not cut, puncture or weld on or near the container.
- Do not incinerate closed containers.
- Empty containers may contain hazadous residues

SECTION 14. Transport information

- DOT CFR 172.101
- Not regulated per 49 CFR 173.4 Small Quantity Exemption

SECTION 15. Regulatory information

This product is compliant with the following:

- EU Label: Classification and labeling have been performed according to EU Directive 67/548/EEC and 99/45/EC including amendments
- EU Hazard Symbol and Indication of Danger
- F Highly flammable
- Xi Irritant
- R11 Highly flammable





Corporate Headquarters

10 Glenshaw Street, Orangeburg, NY 10962

Tel: 845.365.8200 • Fax: 845.365.8201

Toll-Free: 888.DYNAREX

- R36 Irritating to eyes
- R67 Vapors may cause drowsiness and dizziness
- S2 Keep out of reach of children
- S7 Keep container tightly closed
- S16 Keep away from sources of ignition No smoking
- S24 / S25 Avoid contact with skin and eyes
- S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- US (Federal and State) Regulations and International Chemical Registration Laws TSCA listing
- This product contains ingredients that are listed on or exempt from listing on the EPA Toxic Substance Control Act Chemical Inventory
- This product does not contain any chemicals subject to EPA Title III of the SARA Listing in Sections 302 and 304
- All ingredients in this product are listed on the European Inventory of Existing Commercial Chemical Substance (EINECS Listing) or are exempted from listing
- All ingredients in this product are listed on the Canada Domestic Substance List (DSL Listing)

SECTION 16. Other information

Disclaimer:

This Safety Data Sheet, which takes into consideration the requirements of Directive 76/768/EC and subsequent amendments and Directive 1999/45/EC plus subsequent amendments, has been prepared in accordance with Directive (EC) 1907/2006. It is believed to be correct and corresponds to the latest scientific/technical knowledge but all data, instructions, recommendations and/or suggestions are made without guarantee. No warranty, expressed or implied, is made and Dynarex Corp. assumes no legal responsibility or liability resulting from its use.





Reviewed on 4/21/15

SAFETY DATA SHEET

SECTION 1. Product and Company Identification

PRODUCT NAME: BZK Antiseptic Towelette

PRODUCT USE: Antiseptic

Product Code: 1303, 1331

Manufacturer's Name: Dynarex Corporation

Manufacturer's Address: 10 Glenshaw Street
Orangeburg, NY 10962

Emergency or Information 888-DYNAREX or 845-365-8200

Phone No.: At other times, contact the local Poison Control Center

SECTION 2. Hazards Identification

Emergency Overview Contact with liquid may cause eye and skin irritation

Potential short term health effects

Routes of exposure Eye, skin contact, skin absorption, Inhalation, Ingestion.

Eyes May cause irritation.

Skin In case of skin irritation, discontinue use of the product.

Inhalation Not a normal route of exposure. May cause respiratory tract

irritation.

Ingestion Not a normal route of exposure. May cause stomach

distress, nausea or vomiting.





Corporate Headquarters
10 Glenshaw Street, Orangeburg, NY 10962
Tel: 845.365.8200 • Fax: 845.365.8201

Toll-Free: 888.DYNAREX

Target organs Eyes. Skin

Chronic effects Prolonged or repeated exposure can cause drying defatting

and dermatitis.

Signs and symptoms Symptoms may include redness, edema, drying, defatting

and cracking of the skin. Symptoms of overexposure may

be headache, dizziness, tiredness, nausea.

SECTION 3. Composition/information on Ingredients

Ingredients	CAS Number	%
BZK	8001-54-5	0.13
Water	7732-18-5	99.87

SECTION 4. First-aid measures

First aid procedures

Eye Contact Flush with cool water. Remove contact lenses, if

applicable, and continue flushing. Obtain medical

attention if irritation persists.

Skin Contact In case of skin irritation, discontinue use of product.

Inhalation Not a normal route of exposure. If symptoms

develop move victim to fresh air. If symptoms

persist, obtain medical attention.

Ingestion Not a normal route of exposure. Do not induce

vomiting, Never give anything by mouth if victim is unconscious, or is convulsing. Obtain medical

attention.





Corporate Headquarters

10 Glenshaw Street, Orangeburg, NY 10962 Tel: 845.365.8200 • Fax: 845.365.8201

Toll-Free: 888.DYNAREX

Notes to physician Symptoms may be delayed.

General advice If you feel unwell, seek medical advice (show the

label where possible). Ensure that medical

personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Keep out of reach of children. Avoid contact with eyes.

Flammable Limits: N/A Flash Point: N/A

SECTION 5. Fire-fighting measures

Flash Point: Not Available Flammable Limits: Not Available

Extinguishing Media: Any

Special Fire Fighting Procedures: None Unusual Fire and Explosion Hazards: None

SECTION 6. Accidental release measures

Personal precautions: Keep unnecessary personnel away. Do not touch or walk

through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak.

Methods for containment: Prevent entry into waterways, sewers, basements or

confined areas.

Methods for cleaning up: Pick up and discard towel.

SECTION 7. Handling and storage

Handling: Use good industrial hygiene practices in handling this

material.

Storage: Keep out of reach of children. Store in a closed container

away from incompatible materials.





SECTION 8. Exposure controls/personal protection

Engineering controls: General ventilation normally adequate.

Personal protective

equipment

Eye/Face protection Follow standard industrial hygiene practices.

Hand protection Not required.

Skin and body protection As required by employer code.

Respiratory protection Where exposure guideline levels may be exceeded, use

and approved NIOSH respirator.

General hygiene Handle in accordance with good industrial hygiene and

considerations safety practice. When using do not eat or drink.

SECTION 9. Physical and chemical properties

Appearance/Odor: Liquid saturated on wipe

Color: Clear liquid

Form: Liquid saturated on wipe

Odor: Characteristic
Odor Threshold: Not available

Physical State: Solid **Boiling Point:** <200°F

Paper Components: 100% Virgin Paper

Specific Gravity: 1

SECTION 10. Stability and reactivity

Chemical Stability: Stable under recommended storage conditions.

Incompatibility: Caustics. Acids. Oxidizers.





Corporate Headquarters 10 Glenshaw Street, Orangeburg, NY 10962

Tel: 845.365.8200 • Fax: 845.365.8201 Toll-Free: 888.DYNAREX

Hazardous Decomposition Products: May include and are not limited to: oxides of carbon;

hydrogen chloride.

Hazardous Polymerization: Will not occur.

Conditions to avoid: Do not mix with other chemicals.

SECTION 11. Toxicological information

Effects of acute exposure

Eye May cause irritation

Skin In case of skin irritation, discontinue use of the

product.

Inhalation Not a normal route of exposure. May cause

respiratory tract irritation.

Ingestion Not a normal route of exposure. May cause

stomach distress, nausea or vomiting.

SensitizationNon-hazardous by WHMIS/OSHA criteria.Chronic EffectsNon-hazardous by WHMIS/OSHA criteria.CarcinogenicityNon-hazardous by WHMIS/OSHA criteria.MutagenicityNon-hazardous by WHMIS/OSHA criteria.Reproductive EffectsNon-hazardous by WHMIS/OSHA criteria.TeratogenicityNon-hazardous by WHMIS/OSHA criteria.

SECTION 12. Ecological information

Ecotoxicity Not available

Environmental effects Not available

Aquatic toxicity Not available

Persistence / degradability Not available

Bioaccumulation / accumulation Not available





Corporate Headquarters 10 Glenshaw Street, Orangeburg, NY 10962 Tel: 845.365.8200 • Fax: 845.365.8201

Toll-Free: 888.DYNAREX

Partition coefficient Not available

Mobility in environmental media Not available

Chemical fate information Not available

Other adverse effects Not available

SECTION 13. Disposal considerations

Waste codes: Not available

Disposal instructions: Discard after single use.

Review federal, state/provincial, and local government requirements prior to disposal.

Discard with solid waste. Dispose in accordance with all applicable regulations.

Waste from residues / unused products: Not available

Contaminated packaging: Not available

SECTION 14. Transport information

U.S. Department of Transportation (DOT) Not regulated as dangerous goods.

Transportation of Dangerous Goods (TDG - Canada) Not regulated as dangerous goods.

SECTION 15. Regulatory information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US Federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

Occupational Safety and Health Administration (OSHA)





Corporate Headquarters

10 Glenshaw Street, Orangeburg, NY 10962 Tel: 845.365.8200 • Fax: 845.365.8201

Toll-Free: 888.DYNAREX

29 CFR 1910.1200 hazardous No chemical

CERCLA (Superfund) reportable quantity

Benzene: 10.0000

Benzene, methyl-: 1000.0000 Benzene, (chloromethyl)-: 100.0000 Propylene oxide: 100.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Section 302 extremely hazardous substance No

Section 311 hazardous chemical No

Clean Air Act (CAA) Not available

Clean Water Act (CWA) Not available

Safe Drinking Water Act (SDWA) Not available

Drug Enforcement Agency (DEA) Not available

Food and Drug Administration (FDA) Not available

State regulations WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

SECTION 16. Other information

Disclaimer:

This Safety Data Sheet, which takes into consideration the requirements of Directive 76/768/EC and subsequent amendments and Directive 1999/45/EC plus subsequent amendments, has been prepared in accordance with Directive (EC) 1907/2006. It is believed to be correct and corresponds to the latest scientific/technical knowledge but all data, instructions, recommendations and/or suggestions are made without guarantee. No warranty, expressed or implied, is made and Dynarex Corp. assumes no legal responsibility or liability resulting from its use.





Fluorescent material

1. Identification

(a) Product identifier

Fluorescent material Product name:

(b) Other means of identification

Product description: GLOW STICK, GLOW BRACELET, GLOW NECKLACE, GLOW

CUP, GLOW WAND WITH ASST COLORS

RED/GREEN/BLUE/YELLOW/PINK/ORANGE/PURPLE/WHITE/A

QUA

(c) Recommended use of the chemical and restrictions on use

Recommended use: Used in decoration. Restriction on use: No information available.

(d) Details of the supplier of the product

Company name Xiamen Long Afterglow Co.,Ltd

Address: NO.1043, Tong Ji Road, Tong An Area, Xiamen, Fujian Province,

China

E-mail: Tommy@glo-noveltv.com

Telephone: +86-592-3675699 +86-592-3675400 Fax:

(e) Emergency phone number

+86-592-3675699

2. Hazard(s) identification

(a) Classification of the chemical

This product is not classified as hazardous.

(b) Label elements

This product is not classified as hazardous.

Pictogram(s): No pictogram is used. No signal word is used. Signal word: Hazard statements: No hazard statements.

Precautionary statements: No precautionary statements.

(c) Description of any hazards not otherwise classified

No information available.

(d) Ingredient with unknown acute toxicity

No information available.

This technical report may only be quoted in full. Any use for advertising purposes must be granted in writing. This report is the result of a single examination of the object in question and is not generally applicable evaluation of the quality of other products in regular production.

Guangzhou 510656 P.R. China Tel.: +86 20 3832 0668, Fax: +86 20 3832 0478



Fluorescent material

3. Composition/information on ingredients

(a) Mixtures information

Chemical name	CAS No.	Concentration
Dimethyl Phthalate	131-11-3	58.5%
Butyl Benzoate	136-60-7	28.5%
CPPO	75203-51-9	4.7%
Hydrogen Peroxide	7722-84-1	2.2%
H2O	7732-18-5	6.0%
Fluorescer	10075-85-1	0.1%

4. First-aid measures

(a) Description of first aid measures

Inhalation: Move to fresh air in case of accidental inhalation of vapours or

decomposition products. If you feel unwell, seek medical advice.

Skin contact: Wash off with soap and plenty of water. If skin irritation persists, call a

physician.

Eye contact: Rinse with plenty of water immediately, also under the eyelids, for at

least 15 minutes. If eye irritation persists, consult a specialist.

Ingestion: Rinse mouth. Do not induce vomiting. Call a physician immediately.

(b) Most important symptoms/effects, acute and delayed

No information available.

(c) Immediate medical attention and special treatment

Treat symptomatically. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire-fighting measures

(a) Extinguishing media

Suitable extinguishing media: Use carbon dioxide, dry extinguishing media,

water spray, water.

Unsuitable extinguishing media: No information available.

(b) Special hazards arising from the chemical

Combustion produces toxic or irritating gases and fumes.

(c) Special protective equipment and precautions for fire-fighters

Firefighters must wear fire resistant protective equipment. Wear self-contained breathing apparatus.

Tel.: +86 20 3832 0668, Fax: +86 20 3832 0478



Fluorescent material

6. Accidental release measures

(a) Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

(b) Methods and materials for containment and cleaning up

For large amounts: Transfer product into suitable containers.

For residues: Pick up with suitable absorbent material (e.g. sand, sawdust, general-purpose binder, kieselguhr). Dispose of absorbed material in accordance with regulations

7. Handling and storage

(a) Precautions for safe handling

Ensure thorough ventilation of stores and work areas.

(b) Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

8. Exposure controls/personal protection

(a) Control parameters

	OSHA		NIC	DSH
Component	PEL-TWA	PEL-STEL	REL-TWA	REL-STEL
131-11-3	5 mg/m3	Not Established	5 mg/m3	Not Established
136-60-7	Not Established	Not Established	Not Established	Not Established
75203-51-9	Not Established	Not Established	Not Established	Not Established
7722-84-1	1.4 mg/m3	Not Established	1.4 mg/m3	Not Established
7732-18-5	Not Established	Not Established	Not Established	Not Established
10075-85-1	Not Established	Not Established	Not Established	Not Established

(b) Appropriate engineering controls

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

(c) Personal protective equipment

Respiratory protection: The following respirators and maximum use concentrations

are drawn from NIOSH and/or OSHA.

50 mg/m3

Any air-purifying full-facepiece respirator equipped with an N95, R95, or P95 filter. The following filters may also be used:

N99, R99, P99, N100, R100 or P100.

125 mg/m3

Tel.: +86 20 3832 0668, Fax: +86 20 3832 0478



Fluorescent material

Any supplied-air respirator operated in a continuous-flow mode.

Any powered, air-purifying respirator with a high-efficiency particulate filter.

250 mg/m3

Any air-purifying, full-facepiece respirator equipped with an N100, R100, or P100 filter.

Any self-contained breathing apparatus with a full facepiece. Any supplied-air respirator with a full facepiece.

2000 mg/m3

Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode.

Emergency or planned entry into unknown concentrations or IDLH conditions

Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive-pressure mode.

Escape

Any air-purifying, full-facepiece respirator equipped with an N100, R100, or P100 filter.

Any appropriate escape-type, self-contained breathing

apparatus.

Hand protection: Wear appropriate chemical resistant gloves.

Eye/face protection: Wear splash resistant safety goggles. Provide an emergency

eye wash fountain and quick drench shower in the immediate

work area.

Skin/body protection: Wear appropriate chemical resistant clothing.

9. Physical and chemical properties

(a) Appearance	Liquid
(b) Odor	Not available.
(c) Odor threshold	Not available.
(d) pH	Not available.
(e) Melting point/freezing point	Not available.
(f) Initial boiling point and boiling range	Not available.



Fluorescent material

(g) Flash point >200°F (93.3°C) Closed Cup

(h) Evaporation rate Not available.

(i) Flammability No

(j) Upper/lower flammability or explosive limits Not available. (k) Vapor pressure Not available. (I) Vapor density Not available. (m) Relative density Not available. (n) Solubility(ies) Not available. (o) Partition coefficient: n-octanol/water Not available. (p) Auto-ignition temperature Not available. (q) Decomposition temperature Not available. (r) Viscosity Not available.

10. Stability and reactivity

(a) Reactivity

Stable under recommended storage and handling conditions (see section 7, handling and storage).

(b) Chemical stability

Stable under normal conditions.

(c) Possibility of hazardous reactions

Will not polymerize.

(d) Conditions to avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

(e) Incompatible materials

Acids, bases, oxidizing materials.

(f) Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO₂) and other toxic vapors.

11. Toxicological information

(a) Information on the likely routes of exposure

Inhalation:Not available.Ingestion:Not available.Skin contact:Not available.Eye contact:Redness.

Tel.: +86 20 3832 0668, Fax: +86 20 3832 0478

Page 5 of 9



Fluorescent material

(b) Information on toxicological characteristics

Acute toxicity: 131-11-3 Oral LD50 Rat 6800 mg/kg (Source:

IUCLID)

136-60-7 No data available. 75203-51-9 No data available.

7722-84-1 Oral LD50 Rat 801 mg/kg (Source: IUCLID)

Dermal LD50 Rat 4060 mg/kg (Source: IUCLID); Dermal LD50 Rabbit 2000 mg/kg

(Source: IUCLID)

Inhalation LC50 Rat 2 g/m3 4 h (Source:

IUCLID)

10075-85-1 No data available.

Skin No data available.

corrosion/irritation:

Serious eye No data available.

damage/irritation:

Respiratory No data available.

sensitization:

skin sensitization: No data available.

Carcinogenicity: Not listed by IARC and NTP.

Germ Cell No data available.

Mutagenicity:

Reproductive Toxicity: No data available. STOT-Single No data available.

Exposure:

STOT-Repeated No data available.

Exposure:

Aspiration Hazard: No data available.

12. Ecological information

(a) Ecotoxicity

131-11-3 Freshwater Fish: 96 Hr LC50 Pimephales promelas: 39 mg/L [flow-

through]; 96 Hr LC50 Lepomis macrochirus: 49.5 mg/L; 96 Hr LC50 Lepomis macrochirus: 37 - 69 mg/L [static]; 96 Hr LC50 Pimephales promelas: 121 mg/L [static]; 96 Hr LC50 Leuciscus idus: 100 - 220 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 56

mg/L [flow-through]

Water Flea: 48 Hr EC50 Daphnia magna: 33 mg/L

Freshwater Algae: 96 Hr EC50 Pseudokirchneriella subcapitata: 20.6 - 45.8 mg/L; 72 Hr EC50 Pseudokirchneriella subcapitata:



Fluorescent material

28.4 - 71 mg/L; 96 Hr EC50 Pseudokirchneriella subcapitata: 142 mg/L [static]; 96 Hr EC50 Skeletonema costatum: 26.1 mg/L; 72 Hr

EC50 Desmodesmus subspicatus: 204 mg/L

136-60-7 No data available. 75203-51-9 No data available.

7722-84-1 Freshwater Fish: 96 Hr LC50 Pimephales promelas: 16.4 mg/L; 96

Hr LC50 Lepomis macrochirus: 18 - 56 mg/L [static]; 96 Hr LC50

Oncorhynchus mykiss: 10.0 - 32.0 mg/L [static]

Water Flea: 24 Hr EC50 Daphnia magna: 7.7 mg/L; 48 Hr EC50

Daphnia magna: 18 - 32 mg/L [Static]

Freshwater Algae: 72 Hr EC50 Chlorella vulgaris: 2.5 mg/L

10075-85-1 No data available.

(b) Persistence and Degradability

Based on best current information, there is no data known associated with this product.

(c) Bioaccumulative potential

Based on best current information, there is no data known associated with this product.

(d) Mobility in soil

Based on best current information, there is no data known associated with this product.

(e) Other adverse effects

No information available.

13. Disposal considerations

(a) Safe handling and methods of disposal

Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): U102. Dispose in accordance with all applicable regulations.

14. Transport information

(a) UN number	Not regulated as dangerous goods.
(b) UN Proper shipping name	Not regulated as dangerous goods.
(c) Transport hazard class(es)	Not regulated as dangerous goods.
(d) Packing group (if	Not regulated as dangerous goods.
applicable)	
(e) Marine pollutant (Yes/No)	No
(f) Transport in bulk (according	No information available.
to Annex II of MARPOL 73/78	
and the IBC Code)	
(g) Special precautions	No information available.

Jiangsu TÜV Product Service Ltd. Guangzhou Branch TÜV SÜD Group

Tel.: +86 20 3832 0668, Fax: +86 20 3832 0478

5F, Communication Building, 163 Pingyun Rd, Huangpu West Ave. Guangzhou 510656 P.R. China

Engineer: Echo He 2013-12-23

Page 7 of 9



Fluorescent material

15. Regulatory information

(a) Safety, health and environmental regulations specific for the product in question

CAS No.	USA TSCA	EU EINECS	Korea ECL	China IECSC	Canada DSL
131-11-3	Listed	Listed	Listed	Listed	Listed
136-60-7	Listed	Listed	Listed	Listed	Listed
75203-51-9	Not listed	Listed	Listed	Not listed	Not listed
7722-84-1	Listed	Listed	Listed	Listed	Listed
7732-18-5	Listed	Listed	Listed	Listed	Listed
10075-85-1	Listed	Listed	Listed	Not listed	NDSL
Remark: The ab	Remark: The above-mentioned search results are based on the Non-Confidential Inventory.				

16. Other information, including date of preparation or last revision

(a) Preparation and revision information

Date of previous revision: Not applicable. Date of this revision: 23/12/2013

Revision summary: The first New SDS

(b) Abbreviations and acronyms

NIOSH The National Institute for Occupational Safety and Health

OSHA The United States Occupational Safety and Health Administration

TWA time-weighted average STEL Short term exposure limit

TSCA Toxic Substances Control Act, The American chemical inventory

DSL Domestic Substances List

EINECS European Inventory of Existing Commercial chemical Substances

ECL Existing Chemicals List, the Korean chemical inventory IECSC Inventory of existing chemical substances in China

IARC International agency for research on cancer

NTP National Toxicology Program

(c) Disclaimer

The information in this SDS is provided all the relevant data fully and truly. However, the information is provided without any warranty on their absolute extensiveness and accuracy. This SDS was prepared to provide safety preventive measures for the users who have got professional training. The personal user who obtained this SDS should make independent judgment for the applicability of this SDS under special conditions. In these special cases, we do not assume responsibility for the damage.

------ End of the SDS ------



Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Jiangsu TÜV Product Service Ltd. Guangzhou Branch

TÜV SÜD Group

Engineer:

_____ Technical Report checked:

Kevin Zhang

Kevir

SANFACON INDUSTRIES

MATERIAL SAFETY DATA SHEET January, 2008

TOWELETTE, PRE-MOISTENED, LEMON-SCENTED

Section I: Identification

Identity (As used on Label and List):

MOIST TOWELETTE WITH LEMON FRAGRANCE

Ingredients: 98.8% water

1% lemon fragrance

0.01% BZK (Benzalkonium)

0.01% soap

Physical Description: A pre-moistened towelette made with virgin paper, individually packaged in a moisture-proof pouch.

Manufacturer's Name:

SANFACON INDUSTRIES INC.

Address:

1980 5th street St-Romuald, Québec, Canada G6W 5M6

Section II: Hazardous Ingredients

Hazardous components: N/A

Section III: Physical/Chemical Characteristics

Boiling Point: N/A Specific Gravity: +/- 1.0 Vapour Pressure: N/A Melting Point: N/A Vapour Density: N/A Evaporation Rate: N/A

Solubility in Water: Complete

Appearance and Colour: Clear liquid with lemon scent

Section IV: Fire and Explosion Hazard Data

Flash Point: N/A Flammable Limits: N/A

Extinguishing Media: N/A

Special Fire Fighting Procedures: NONE Unusual Fire & Explosion Hazards: NONE

Section V: Health Hazard Data

Routes of Entry: Inhalation: N/A

Skin: Topically applied

Ingestion: N/A

Health Hazards: N/A Carcinogenicity: N/A

Information/Emergency: Monday through Friday, 8 a.m. to 5 p.m., (800) 463-5591

or contact the local Poison Control Centre.

Caution: If accidentally splashed in eyes, rinse thoroughly with cold water; may

cause discomfort. No need for first aid if swallowed or inhaled.

Signs and Symptoms of Exposure:

SAFE AS A TOPICAL SKIN CLEANSER

Disclaimer:

Sanfacon acknowledges hat the information contained herein is assumed accurate and complete, and illustrates the product to the best of their knowledge. No warranty, expressed or implied, is made and Sanfacon assumes no legal responsibility or liability resulting from its use.



Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 06/02/2014 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product form : Mixture

Trade name Medicaine Sting and Bite Relief

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : OTC drug used as a topical analgesic

Use of the substance/mixture : For professional use only

Details of the supplier of the safety data sheet

James Alexander Corporation 845 Route 94 Blairstown NJ 07825

Tel: (908) 362-9266

Note: The CHEMTREC emergency number is to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals. All non-emergency questions should be directed to JAC at (908) 362-9266.

Emergency telephone number

Emergency number : Chemtrec (800) 424-9300

SECTION 2: Hazards identification

Classification of the substance or mixture

GHS-US classification

Flam. Liq. 2 H225 Eye Irrit. 2A H319 STOT SE 3 H335 STOT SE 3 H336

2.2. **Label elements**

GHS-US labelling

Hazard pictograms (GHS-US)





GHS02 GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) H225 - Highly flammable liquid and vapour

H319 - Causes serious eve irritation H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness

Precautionary statements (GHS-US) P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical, lighting, ventilating equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge P261 - Avoid breathing dust, fume, mist, spray, vapours

P264 - Wash hands thoroughly after handling P271 - Use only outdoors or in a well-ventilated area

P280 - Wear eye protection, protective clothing, protective gloves

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower

P304+P340 - IF INHALED: remove victim to fresh air and keep at rest in a position comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P312 - Call a POISON CENTER/doctor/physician if you feel unwell P337+P313 - If eye irritation persists: get medical advice/attention

06/06/2014 EN (English) Page 1

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

P370+P378 - In case of fire: Use dry chemical, foam, carbon dioxide for extinction

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

 $P501 - Dispose \ of \ contents/container \ to \ comply \ with \ applicable \ local, \ national \ and \ international \ and \ inter$

regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Polyethylene glycol	(CAS No) 25322-68-3	50 - 55	STOT SE 3, H335
Isopropyl alcohol	(CAS No) 67-63-0	20 - 25	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
L-Menthol	(CAS No) 2216-51-5	1	Skin Irrit. 2, H315 Eye Irrit. 2A, H319

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation

: Remove to fresh air and keep at rest in a position comfortable for breathing. If breathing stops, give artificial respiration. In case of breathing difficulties administer oxygen. by trained personnel. Seek medical attention immediately.

First-aid measures after skin contact

Immediately flush skin with plenty of water for at least 15 minutes. Remove/Take off immediately all contaminated clothing. Do not rub the skin and eyes after direct contact with the product. Seek medical attention immediately. Wash contaminated clothing before reuse.

First-aid measures after eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately get medical attention.

First-aid measures after ingestion

Contact a Poison Control Center immediately. Give no more than 2 glasses of water and induce vomiting by giving 30 cc (2 tablespoons) of syrup of ipecac. If victim is a child, give no more than 1 glass of water and 15cc (1 tablespoon) syrup of ipecac. If syrup of ipecac is unavailable, give 2 glasses of water and induce vomiting by touching finger to back of victim's throat. Do not give anything by mouth to an unconscious or convulsing person. Get immediate medical attention. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation

: May cause respiratory irritation. May cause drowsiness or dizziness. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.

Symptoms/injuries after skin contact

: Repeated or prolonged skin contact may cause irritation.

Symptoms/injuries after eye contact

: Causes serious eye irritation.

Symptoms/injuries after ingestion

: Irritating to the gastrointestinal tract. May cause abdominal pain and vomiting (sometimes bloody). Ingestion may cause central nervous system depression, low blood pressure, rapid heart beat and liver damageEarly to moderate central nervous system depression may be evidenced by giddiness, headache, dizziness and nausea. In extreme cases, unconsciousness, respiratory depression and death may occur. Liver damage may be evidenced by loss of appetite, jaundice (yellowish skin color) and sometimes pain in the upper abdomen on the right side.

4.3. Indication of any immediate medical attention and special treatment needed

Individuals with pre-existing skin disorders, eye problems, or impaired respiratory function may be more susceptible to the effects of overexposure.

06/06/2014 EN (English) 2/10

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Dry powder. Carbon dioxide. Sand

Unsuitable extinguishing media : Do not use a heavy water stream.

Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.

Explosion hazard : May form flammable/explosive vapour-air mixture.

Reactivity Thermal decomposition generates: Corrosive vapours. Reacts violently with acids. An

exothermic reaction may occur.

Advice for firefighters 5.3.

: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any Firefighting instructions

chemical fire. Prevent fire-fighting water from entering environment.

Protective equipment for firefighters : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information Containers may swell and Burst during a fire due to internal pressure caused by heat. Vapours

are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. Alcohols burn with a pale blue flame which may be extremely hard to see under normal lighting conditions. Personnel may be able to feel the heat of the fire without seeing flames. Extreme caution must be exercised in fighting alcohol fires.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures : Eliminate all ignition sources if safe to do so. Use special care to avoid static electric charges. No

naked lights. No smoking. Stop leak if safe to do so. No action shall be taken involving any personal risk or without suitable training. Wear protective clothing. For further information refer to

section 8: Exposure-controls/personal protection.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Ventilate area. **Emergency procedures**

6.2. **Environmental precautions**

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Methods and material for containment and cleaning up

: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Consult the appropriate authorities about waste disposal. Ensure all national/local regulations are observed.

Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapours are flammable.

Precautions for safe handling

Methods for cleaning up

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Personal protective equipment should be selected based upon the conditions under which this product is handled or used. Use personal protective equipment as required. Provide good ventilation in process area to prevent formation of vapour. Do not breathe gas, fumes, vapour or spray. No naked lights. No smoking. Use only non-sparking tools. Never use pressure to empty container. Ground/bond container and receiving equipment. Take care to allow internal pressure to escape from container before releasing closures. Remove closure carefully; internal pressure may be present. Keep closure up to prevent leakage. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene measures

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

06/06/2014 EN (English) 3/10

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Ensure the ventilation system is regularly maintained and tested. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of mists and/or vapors below the recommended exposure limits. Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. A washing facility/water for eye and skin cleaning purposes should be present. Comply with applicable regulations.

Storage conditions

Keep only in the original container in a cool well ventilated place. Keep in fireproof place. Keep container tightly closed. Protect containers against physical damage. Detached outside storage is preferable. Inside storage should be in an NFPA approved flammable liquids storage room or cabinet. Store in corrosion-proof area at temperatures below 77 °F (25°C). Store away from direct sunlight or other heat sources.

Incompatible materials

Storage temperature

: Avoid mixing with acids, most common metals, strong oxidizing agents, brass, zinc, chlorine, aluminum, copper, bronze, mercury, dimethyl sulfate and acetyl chloride.

: < 25 °C Store at temperatures below 77 °F (25 °C)

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Isopropyl alcohol (67-63-0)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	400 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	980 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm

8.2. Exposure controls

Appropriate engineering controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of mists and/or vapors below the recommended exposure limits. Use explosion-proof ventilating equipment.

Personal protective equipment

: Avoid all unnecessary exposure. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to OSHA regulations. For certain operations, additional Personal Protection Equipment (PPE) may be required. Protective goggles. Gloves. Protective clothing.







Hand protection

: Wear protective gloves. rubber gloves. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Eye protection

: Chemical goggles or face shield.

Skin and body protection

: Wear suitable protective clothing. Chemical resistant safety shoes.

Respiratory protection

Wear a self-contained breathing apparatus and appropriate personal protective equipment (PPE). Suggestions provided in this section for exposure control and specific types of protective equipment are based on readily available information. Users should consult with the specific manufacturer to confirm the performance of their protective equipment. Specific situations may require consultation with industrial hygiene, safety, or engineering professionals. Care must be taken to assure that any respirator chosen is capable of protecting the user from both ammonia and ethyl alcohol vapors.

and ethyl alcohol vapors.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear.
Colour : Green.

Odour : Odor of isopropyl alcohol, residual odor of menthol.

06/06/2014 EN (English) 4/10

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Odour threshold : No data available

pH : 8.5

Relative evaporation rate (butyl acetate=1) : No data available Melting point : No data available : No data available Freezing point : > 35 °C (>95 °F) Boiling point : 16.6 °C (62 °F) Flash point Auto-ignition temperature : No data available Decomposition temperature : No data available Flammability (solid, gas) : No data available : No data available Vapour pressure Relative vapour density at 20 °C : No data available

Density : 1.029 (Specific Gravity @ 25 °C)

Solubility Soluble in water. Log Pow No data available Log Kow : No data available Viscosity, kinematic No data available : No data available Viscosity, dynamic Explosive properties : No data available Oxidising properties No data available **Explosive limits** : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Relative density

Thermal decomposition generates: Corrosive vapours. Reacts violently with acids. An exothermic reaction may occur.

: No data available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

Avoid mixing with acids, most common metals, strong oxidizing agents, brass, zinc, chlorine, aluminum, copper, bronze, mercury, dimethyl sulfate and acetyl chloride.

10.6. Hazardous decomposition products

Thermal decomposition generates: Fume. Carbon monoxide. Carbon dioxide. May release flammable gases. Corrosive vapours. Ammonia. Nitrogen oxides. release of highly flammable gases/vapours hydrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

(Based on available data, the classification criteria are not met)

Isopropyl alcohol (67-63-0)	
LD50 oral rat	4396 mg/kg
LD50 dermal rabbit	12800 mg/kg
LC50 inhalation rat (ppm)	16000 ppm (Exposure time: 8 h)
ATE CLP (oral)	4396.000 mg/kg bodyweight
ATE CLP (dermal)	12800.000 mg/kg bodyweight

06/06/2014 EN (English) 5/10

Safety Data Sheet according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

L-Menthol (2216-51-5)	
LD50 oral rat	3300 mg/kg
ATE CLP (oral)	3300.000 mg/kg bodyweight
Polyethylene glycol (25322-68-3)	
LD50 dermal rabbit	> 20 ml/kg
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
	pH: 8.5
Serious eye damage/irritation	: Causes serious eye irritation. pH: 8.5
Respiratory or skin sensitisation	: Not classified
	(Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified
	(Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified
	(Based on available data, the classification criteria are not met)
Isopropyl alcohol (67-63-0)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
	(Based on available data, the classification criteria are not met)
Specific target organ toxicity (single exposure)	: May cause respiratory irritation. May cause drowsiness or dizziness.
Specific target organ toxicity (repeated	: Not classified
exposure)	(Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified
	(Based on available data, the classification criteria are not met)
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause respiratory irritation. May cause drowsiness or dizziness. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/injuries after skin contact	: Repeated or prolonged skin contact may cause irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: Irritating to the gastrointestinal tract. May cause abdominal pain and vomiting (sometime bloody). Ingestion may cause central nervous system depression, low blood pressure, rapic heart beat and liver damageEarly to moderate central nervous system depression may be evidenced by giddiness, headache, dizziness and nausea. In extreme cases, unconsciousness respiratory depression and death may occur. Liver damage may be evidenced by loss cappetite, jaundice (yellowish skin color) and sometimes pain in the upper abdomen on the right side.

SECTION 12: Ecological information

Toxicity 12.1.

Isopropyl alcohol (67-63-0)	
LC50 fishes 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
L-Menthol (2216-51-5)	
LC50 fishes 1	18.9 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

Persistence and degradability 12.2.

Medicaine® Sting and Bite Relief	
Persistence and degradability	Not established.

06/06/2014 EN (English) 6/10

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

12.3. **Bioaccumulative potential**

Medicaine [®] Sting and Bite Relief					
Bioaccumulative potential	Not established.				
Isopropyl alcohol (67-63-0)					
Log Pow	0.05 (at 25 °C)				

Mobility in soil

No additional information available

Other adverse effects 12.5.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not re-use empty

containers. Ensure all national/local regulations are observed. Consult the appropriate authorities

about waste disposal.

Additional information : Handle empty containers with care because residual vapours are flammable.

Avoid release to the environment. Ecology - waste materials

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1993 Flammable liquids, n.o.s. (contains isopropanol), 3, II

UN-No.(DOT) : 1993 DOT NA no. UN1993

DOT Proper Shipping Name : Flammable liquids, n.o.s.

(contains isopropanol)

Department of Transportation (DOT) Hazard

Classes

: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



DOT Symbols : G - Identifies PSN requiring a technical name

Packing group (DOT) : II - Medium Danger

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite DOT Special Provisions (49 CFR 172.102)

(31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal...... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / (1 + a (tr - tf)) Where: tr is the maximum mean bulk temperature

during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when

the flash point of the hazardous material transported is greater than 0 C (32 F).

TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous

material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) 150 DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242 DOT Quantity Limitations Passenger aircraft/rail : 5 L (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

06/06/2014 7/10 EN (English)

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Additional information

Other information

: No supplementary information available.

ADR

Transport document description

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Isopropyl alcohol (67-63-0)							
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)							
EPA TSCA Regulatory Flag T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.							
SARA Section 313 - Emission Reporting 1.0 % (only if manufactured by the strong acid process, no supplier notification)							

L-Menthol (2216-51-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Polyethylene glycol (25322-68-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Isopropyl alcohol (67-63-0)	
Listed on the Canadian DSL (Domestic Sustance	s List) inventory.
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects

L-Menthol (2216-51-5)

Listed on the Canadian DSL (Domestic Sustances List) inventory.

Polyethylene glycol (25322-68-3)

Listed on the Canadian DSL (Domestic Sustances List) inventory.

EU-Regulations

Isopropyl alcohol (67-63-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

L-Menthol (2216-51-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

Polyethylene glycol (25322-68-3)

Listed on the EU - No-Longer Polymers List (67/548/EEC)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

06/06/2014 EN (English) 8/10

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

15.2.2. National regulations

Isopropyl alcohol (67-63-0)

Listed on the AICS (the Australian Inventory of Chemical Substances)

Listed on Inventory of Existing Chemical Substances (IECSC)

Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.

Listed on Industrial Safety and Health Law Substances (ISHL)

Listed on the Korean ECL (Existing Chemical List) inventory.

Listed on New Zealand - Inventory of Chemicals (NZIoC)

Listed on Inventory of Chemicals and Chemical Substances (PICCS)

Listed on the Canadian Ingredient Disclosure List

L-Menthol (2216-51-5)

Listed on the AICS (the Australian Inventory of Chemical Substances)

Listed on Inventory of Existing Chemical Substances (IECSC)

Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.

Listed on Industrial Safety and Health Law Substances (ISHL)

Listed on the Korean ECL (Existing Chemical List) inventory.

Listed on New Zealand - Inventory of Chemicals (NZIoC)

Listed on Inventory of Chemicals and Chemical Substances (PICCS)

Polyethylene glycol (25322-68-3)

Listed on the AICS (the Australian Inventory of Chemical Substances)

Listed on Inventory of Existing Chemical Substances (IECSC)

Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.

Listed on the Korean ECL (Existing Chemical List) inventory.

Listed on New Zealand - Inventory of Chemicals (NZIoC)

Listed on Inventory of Chemicals and Chemical Substances (PICCS)

15.3. US State regulations

No additional information available

SECTION 16: Other information

Other information : None.

Full text of H-phrases: see section 16:

tt of 11 princeoe. eee eeetieri 10.	
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapour
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt

medical attention is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all

ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.

2 0

SDS US (GHS HazCom 2012)

06/06/2014 EN (English) 9/10

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

This Material Safety Data Sheet is intended only as a guide to the appropriate precautionary handling of the material by a person trained in, or supervised by a person trained in, the safe handling of chemical materials. James Alexander Corporation (JAC), expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose with respect to the product or information provided herein. All information appearing herein is based upon data obtained from the manufacturer(s) and/or recognized technical sources. While the information is believed to be accurate, JAC makes no representations as to its accuracy or sufficiency. Conditions of use are beyond JAC's control and therefore, users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein and does not relate to its use in combination with any other material or in any other process.

06/06/2014 EN (English) 10/10



SAFETY DATA SHEET

Product and Company Identification

Red Emergency Flare - No Perchlorate (NPC) Identification:

> The NPC flare will have the following symbol on it: **Formulation**

Synonyms: **Emergency Road Flare**

Railway Flare

NSN#: 1370-01-009-2593

Identified Use: Emergency signal **Use Advised Against:** Do not use indoors or inside a vehicle

Manufacturers Information Orion Safety Products

28320 St. Michaels Rd Easton, MD 21601 800-637-7807 410-822-0318

EMERGENCY CHEMTREC 1-800-424-9300

2. **Hazards Identification**

GHS Classifications

Skin Irritation Category 2 H315 Eve Irritation Category 2A H319 Category 3 STOT - Single Exposure H335

GHS Label Elements

Pictograms

Hazard Statements

P305/338/351

P333/313

H315 /319 Causes skin and serious eye irritation May cause respiratory irritation H335

Signal Word

Precautionary Statements

P103 Keep out of reach of children Avoid breathing dust/smoke. P261 P264 Wash hands thoroughly after handling. P270

Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective eye protection

P370 In case of fire: use water deluge P501 Dispose of contents / container in accordance with local and national regulations.

P301/315 IF SWALLOWED: Get immediate medical advice /attention. P302/352 IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove victim to fresh air and keep at rest in a position P304/340/342 comfortable for breathing If experiencing respiratory symptoms: Call a

POISON CENTER or doctor / physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

If skin irritation or rash occurs, get medical advice / attention.

Hazards Not Otherwise Classified (HNOC): produces hot flame

Composition / Information on Ingredients

Component	CAS#	EINCS #	%age
Strontium Nitrate	10042-76-9	233-131-9	<75%
Sulfur	7704-34-9	231-722-6	<25%
Potassium Nitrate	7757-79-1	231-818-8	<25%
Paraffinic Oil	64742-54-7	232-384-2	<10%
Potassium Chlorate	3811-04-9	231-100-4	<5%
Waxy sawdust	mixture	none	<5%
Polyvinyl Chloride	9002-86-2	200-831-0	<5%
Shellac	mixture	none	<1%
Charcoal	1333-86-4	231-153-3	<1%

Note: Due to Confidential Business Information i. e "Trade Secrets", the exact percentage of each ingredient has not been disclosed. CBI information will be shared with appropriate authorities if circumstances warrant.

First Aid Measures

Description of first aid measures

Inhalation If contents are inhaled, remove to fresh air. Watch for signs of allergic reaction. If other symptoms develop, get medical aid

Skin If contents are contacted, wash with area with soap and water for 15 minutes. Remove contaminated clothing and wash before

reuse. Get medical aid immediately if burned or irritation occurs.

If contents get into eye, flush with plenty of water for at least 15 minutes, occasionally lifting the upper and lower lids. Remove Eyes

contact lenses if easily possible. Do not use boric acid to rinse with; sulfur is an acid irritant. Get medical aid immediately.

Ingestion Get medical aid immediately.

no pc flare Page 1 of 5 04 2017



Most important symptoms and effects both acute and delayed

See section 2 labeling and section 11

Indication of any immediate medical attention and special treatment needed

Burning flare can cause severe burns if in contact with body. For burns to skin, cool with water and bandage appropriately. Seek medical attention. If eye is burned, cover eye and get medical aid immediately

5. Firefighting Measures

Extinguishing Media

Water deluge

Unsuitable Extinguishing Media

Foam and dry chemical extinguishers and suffocation are ineffective.

Protective Equipment and

Precautions for Firefighters

Wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode. Prevent further propagation of fire by spraying unburnt nearby product with water. Combat fire from a sheltered position.

Specific Hazards Arising from the Chemical Use copious amounts of water to extinguish fire comprised of flares. Flares contain oxidizers and will continue to

burn unless a significant amount of water is used. Do not breathe smoke.

No data available **Further information**

6. Accidental Release Measures

Personal Precautions / Protective Equipment / Emergency Procedures

Do not breathe contents and avoid contact with skin and eyes. Wear flame retardant clothing with long sleeves, dust mask, rubber or nitrile gloves, safety goggles, safety shoes. Avoid friction on the released product. Keep away from ignition sources.

Environmental Precautions

Prevent dispersion of contents on soil and in water. Prevent contents from spreading or entering into drains, ditches, groundwater or rivers by using appropriate barriers.

Methods for Containment and Clean-up

Use caution when cleaning up spilled product contents. Remove heat, flames, sparks and other sources of ignition. Use non-sparking tools and equipment. Prevent buildup of electrostatic charges by grounding. Clean spills in a manner that does not disperse dust into the air. Do not absorb in sawdust or other combustible absorbents. Pick up spill for recovery or disposal and place in an approved container. Wash away remainder with plenty of water. Collect wash water for approved disposal.

7. Handling and Storage

Precautions for Safe Handling

Hold and point flare away from body when igniting. Exercise caution when using this product since molten flecks may be emitted. Produces hot flame. Burning flare can cause severe burns if in contact with body. Avoid contact with clothing and other combustible materials. Wear eye protection during use. Follow instructions on package. Use outdoors only! Do not ignite or burn product inside a vehicle or building. Avoid inhalation of smoke. Do not dismantle. Do not allow contents to touch eyes, skin or clothing. Do not ingest contents as they may be harmful if swallowed. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Avoid contact with heat, sparks, and flame.

Conditions for Safe Storage, **Including Any Incompatibilities**

Store away from direct sunlight, heat and incompatible materials. See section 10. Store away from food and beverages. Store away from flammable materials, sources of heat, flame and sparks. Store at ambient temperature. Do not store partially burned flares in a vehicle, warehouse, or any other building. Plastic bags are provided for moisture protection. Keep partially used bags sealed at all times.

8. Exposure Controls / **Personal Protection**

Control parameters

Sulfur Potassium Nitrate

Paraffinic Oil

Potassium Chlorate

Exposure Limits Strontium Nitrate

OSHA PEL Not Established Not Established Nuisance dust 15 mg/m³. 5 mg/m3

No Airborne Exposure Limits established

Not Established Waxy sawdust No known hazardous components above Polyvinyl Chloride regulatory thresholds in this product. Shellac

Not Established Nuisance dust 15 mg/m³.

ACGIH TLV Not Established Not Established Nuisance dust 15 mg/m³.

TWA 5 mg/m3 No Airborne Exposure Limits established Not Established

No known hazardous components above regulatory

thresholds in this product. Not Established Nuisance dust 15 mg/m³.

Charcoal **Exposure controls**

Engineering Controls

Use product outdoors only! When cleaning up contents, use local and/or general exhaust.

Personal Protective Equipment

Eye / Face Protection Safety glasses or goggles

> Skin Protection None under normal conditions when using product unless prolonged handling is anticipated. Impervious protective

clothing, including gloves, boots, and a lab coat, apron or coveralls, as appropriate, when cleaning up spilled

product. Wash hands and face before eating, drinking or using tobacco products.

Respiratory Protection None under normal conditions when using product. A particulate respirator (NIOSH t N95 or better filters) may be

worn during the cleanup of spilled materials.

General Hygiene Use product outdoors away from combustible products. For cleanup of spilled materials, emergency showers and eye wash stations should be available. Educate and train employees in the safe use and handling of hazardous

materials.

Page 2 of 5 04 2017 no pc flare



9. Physical and Chemical Properties

Yellow to grey powder Appearance (color, physical form, shape):

Not available Not available Not available pH: **Melting Point:** Solubility: Not applicable Freezing Point: Not applicable Not applicable **Boiling Point / Range: Evaporation Rate:** Vapor Pressure: Not applicable Specific Gravity Not applicable Vapor Density: Not applicable No data available No data available Odor Threshold: Not available Odor: Flash Point: No data available No data available No data available Flammability: Flammability Limits: Relative Density:

No data available No data available **Partition Coefficient:** Viscosity:

Auto Ignition Temperature: 360°F **Decomposition Temperature:** No data available

10. Stability and Reactivity

Possibility of Hazardous Hazardous polymerization will not occur Chemical Stability Stable No information available Reactivity:

Reactions

Hazardous Decomposition Products

Conditions to Avoid Combustible materials, heat, flames, sparks and other sources of ignition. Moisture.

Incompatible Materials Strong acids, strong fuels, ammonia salts, and strong bases. Strong oxidizers; chlorate salts.

Carbon monoxide, carbon dioxide, sulfur oxides, and nitrogen oxides.

Toxicology Information

Ingredient acute toxicity information

Ingredient Oral LD50 skin LD50 LC50 No information found Strontium Nitrate Rat: 2750 mg/kg No information found Sulfur Rat:>2000 mg/kg Rat:>2000 mg/kg Rat: 79.23 mg/L 4hr Potassium Nitrate Rat: 3750 mg/kg No information found No information found Paraffinic Oil Rat: >2000 mg/kg Rat: >2000 mg/kg No information found Potassium Chlorate Rat: 1870 mg/kg Rabbit: > 2000 mg/kg No information found Waxy sawdust Rat: > 5000 mg/kg not stated not stated no known hazardous components above no known hazardous components above Polyvinyl Chloride Rat: > 5000 mg/kg regulatory thresholds in this product. regulatory thresholds in this product. Shellac Rat: 10000 mg/kg No information found No information found Charcoal Rat: 15400 mg/kg Rabbit: 3 g/kg No information found

Product toxicological information

Acute Toxicity Not classified - Acute Toxicity Estimate yields oral LD50 over 5000 mg/kg bw

Skin Irritation / Corrosion Category 2 – over 10% of ingredients classified as a Category 2 Serious Eye Damage / Irritation Category 2a - over 10% of ingredients classified as a Category 2a

Respiratory / Skin Sensitization Not classified (Based on available data, the classification criteria are not met) Germ Cell Mutagen Not classified (Based on available data, the classification criteria are not met)

Carcinogen Not classified (Based on available data, the classification criteria are not met) **Reproductive Toxicity** Not classified (Based on available data, the classification criteria are not met)

STOT - single exposure Category 3 – respiratory over 10% of ingredients classified as a Category 3 respiratory STOT hazard

STOT - repeated exposure Not classified (Based on available data, the classification criteria are not met) **Aspiration Hazard** Not classified (Based on available data, the classification criteria are not met)

Likely routes of exposure Skin, ingestion, inhalation

Symptoms related to the physical, chemical and toxicological

characteristics

Contents irritating to eyes due to chemical and physical properties of the mixture. Ingestion of contents may cause gastrointestinal irritation with nausea, vomiting and diarrhea. Individuals with known allergies to sulfide drugs may also have allergic reactions

Delayed and immediate effects and chronic effects from short and long term exposure

Interactive effects

to elemental sulfur. Inhalation of contents or smoke from burning flare will cause irritation to the lungs and mucus membrane. Prolonged or

repeated skin contact with contents may cause dermatitis.

No information found

12. **Ecological Information**

Ingredient toxicity / persistence / degradability / bioaccumulation / mobility in soil and water

Strontium Nitrate: Acute toxicity - Fishes, Carassius auratus, LC100, 9,615 mg/l; Chronic toxicity - Fishes, Gasterosteus Aquatic Toxicity

aculeatus, LC100, 2.912 mg/l

Sulfur: Toxicity to fish LC50 - Oncorhynchus mykiss (rainbow trout) -> 180 mg/l - 96 h Toxicity to daphnia and other

aquatic invertebrates: EC50 - Daphnia magna (Water flea) - > 5,000 mg/l - 48 h

Potassium Chlorate: fish: LC50 oncorhynchus mykiss (rainbow trout) 1750 mg/l – 96 hr, EC50 daphnia magna (water flea) 1093 mg/l 24 hr

Paraffinic Oil: Oil Mist, Mineral Lepomis macrochirus (LC50) 96 hour(s) >100 mg/l Oncorhynchus mykiss (LC50) 96 hour(s) >100 mg/l

Potassium Nitrate: fish: Guppy (Poecilia Reticulata) LC50 180 mg/L (96 h); zooplankton: Daphnia magna

LC50 490mg/l - 48hr

Persistence / Degradability Bioaccumulation / Accumulation Mobility in Environmental Media

Potassium Nitrate: Soluble in water Persistence is unlikely based on information available.

No information found

Strontium Nitrate: Water:: considerable solubility and mobility; Soil/sediments non-significant adsorption

Potassium Nitrate: Will likely be mobile in the environment due to its water solubility.

Other adverse effects No information found

Page 3 of 5 04 2017 no pc flare



13. **Disposal Considerations**

Disposal methods

Flares should be allowed to burn to completion. Partially burned or unburned flares, spilled contents, and ash from burned flares should be disposed of in accordance with federal, state, and local requirements. Consult factory for any additional disposal concerns.

14.	4. Transportation Information									
	<u>Description</u>	ID Number	shipping name	hazard class	packing group	EX Number	Reportable Quantities	Shipping method		
Dome Shipn					<u> </u>					
	No inner packaging	*NA1325	Fusee	4.1	II	EX1992090001	none	Ground only		
R	etail Packaging	**UN3178	Flammable solid, inorganic (highway flares or fusees)	4.1	II	EX2002110114	none	Ground only		
<u>Intern</u>	ational / Air									
lı	nner Packaging (bag)	UN0373	Signal devices, hand	1.48		EX1992090001	none	Air / ground		

^{*} As noted on EX1992090001

Marine Pollutant: no

Special precautions for user: No information available

15. Reg	ulatory	<i>I</i> nforr	nation									
US Regulat	tions	TSCA	CERCLA	CWA	CAA	SARA 313	SARA 302	Acute	Chronic	Fire	Reactivity	Pressure
Strontium Nitrate		yes	no	no	no	no	no	yes	no	no	yes	no
Sulfur		yes	no	no	no	no	no	yes	no	yes	no	no
Potassium Nitrate		yes	no	no	no	yes	no	no	no	no	yes	no
Paraffinic Oil		yes	no	no	no	no	no	no	no	no	no	no
Potassium Chlorate		yes	no	no	no	no	no	yes	no	no	yes	no
Waxy sawdust		yes	no	no	no	no	no	no	no	no	no	no
Polyvinyl Chloride		yes	no	no	no	no	no	yes	no	no	no	no
Shellac Mixture		yes	no	no	no	yes	no	unknown	unknown	unknown	unknown	Unknown
Charcoal		yes	no	no	no	no	no	no	no	no	no	No
US States	Prop 65	NJ	PA	Canada			WHMIS		DSL	Eu	ırope	Wgk
Strontium Nitrate	no	1743	no		C O		erials D1B To: Foxic material	xic materials D2B	yes			2
Sulfur	no	1757	yes		B4 F	- lammable	solid D2B	Toxic materials	yes			1 / nwg
Potassium Nitrate	no	1574	yes			CO	xidizing mate	erials	yes			1
Paraffinic Oil	no	1437	no				No results	3	yes			not listed
Potassium Chlorate	yes	1560	yes		CC	xidizing ma	aterials D1B	Toxic materials	yes			2
Waxy sawdust	yes	No	no				No results	3	yes			not listed
Polyvinyl Chloride	no	3622	no				No results	3	yes			not listed
Shellac Mixture	no	No	no				No results	3	unknown			not listed
Charcoal	yes	Yes	yes				ery toxic m Toxic mate		yes			Nwg

Other Information

Revision Information:

NFPA	Rating	HMIS	Rating
Flammability	1	Flammability	1
Health	2	Health	2
Reactivity	1	Physical Hazard	1

Key / Legend:

HMIS: hazardous material identification system NFPA: national fire protection association CAS: Chemical Abstracts Service number EINECS: European inventory of existing chemical substances OSHA PEL: occupational safety and health administration permissible exposure limit NIOSH TLV: national institute of occupational safety and health Threshold Limit Value
TSCA: toxic substance control act - US

CERCLA: comprehensive environmental response, compensation and liability act – US
CWA: clean water act - US
CAA: clean air act - US

SARA: superfund amendments and reauthorization act – US

PROP 65:California's Proposition 65 list WHMIS: workplace hazardous materials information system - Canada DSL: Domestic Substances List - Canada WGK: water hazard classes - Germany

^{**} According to 49CFR, Exception for Class 4, flares properly packaged and classed as UN3178, Flammable solid, inorganic (highway flares or fusees), may be renamed "Consumer Commodity" and reclassed as ORM-D and offered for transportation and transported in accordance with the applicable provisions of that subchapter.



Legal Statement

This information is accurate to the best knowledge Orion Safety Products. Orion Safety Products makes no representations or warranties, either express or implied, including without limitation any warranties of merchantability or fitness for a particular purpose, with respect to the information set forth herein or the product to which the information refers. Accordingly, Orion Safety Products will not be responsible for damages resulting from use of or reliance upon this information. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.