

SAFETY DATA SHEET

EFFECTIVE DATE: 02/16/18

ITEM: Basic Auto Safety Kit (Non Pyro)

PART # 8939 UPC 039147089395

CONTENTS:

Alcohol Wipe
Antiseptic Towelette
Batteries
Sting & Bite Pad



Reviewed on 5/4/15

SAFETY DATA SHEET

SECTION 1. Product and Company Identification

PRODUCT NAME: Alcohol Preparation Pads/Swab

RECOMMENDED USE: Topical skin antiseptic

Product Code: AM-20200, 1113, 1114, 1116, PK-1114

Manufacturer's Name: Dynarex Corporation

Manufacturer's Address: 10 Glenshaw Street
Orangeburg, NY 10962

Emergency or Information 888-DYNAREX or 845-365-8200

Phone No.: At other times, contact the local Poison Control Center

SECTION 2. Hazards Identification

Main Hazards:

Highly flammable; irritation to eyes; vapor may cause drowsiness and dizziness

Absorption:

Eye contact; ingestion; inhalation; skin contact

Carcinogenic Status:

Not considered carcinogenic by NTP, IARC, and OSHA

Target Organs:

Central nerves system; skin; eye; liver; respiratory system

Health Effects:





Corporate Headquarters
10 Glenshaw Street, Orangeburg, NY 10962
Tel: 845.365.8200 • Fax: 845.365.8201

Toll-Free: 888.DYNAREX

- Eyes Liquid, mist or vapor will cause conjunctival irritation and possible corneal damage.
- Skin Repeated or prolonged contact may produce defatting of the skin leading to irritation and dermatitis. Liquid may be absorbed through the skin but not in toxicologically significant amounts, unless the contact area is large and under prolonged exposure.
- Ingestion Swallowing a small amount may have the effect of any of these symptoms: irritation of mouth, throat, digestive tract, and central nerves system depression.
- Ingestion A large dose may have the effect of any of these symptoms: dizziness, drowsiness, headache, mental confusion, nerve damage leading to numbness and muscle weakness, fall of blood pressure, liver damage, lung damage.
- Inhalation Exposure to vapor may have the effect of any of these symptoms: irritation of nose, throat and respiratory tract, central nerve system depression.
- Inhalation Exposure to vapor at high concentration may have the effects of any of these symptoms: dizziness, drowsiness, headache, mental confusion, lung damage, fall of blood pressure, liver damage, nerve damage leading to numbness and muscle weakness.

SECTION 3. Composition/information on Ingredients

Hazardous Ingredients (specific)	% Composition	CAS Number
Isopropyl Alcohol (2-Propanol)	70%	67-63-0
Inactive Ingredient		
Water	30%	7732-18-5





Corporate Headquarters

10 Glenshaw Street, Orangeburg, NY 10962

Tel: 845.365.8200 • Fax: 845.365.8201

Toll-Free: 888.DYNAREX

SECTION 4. First-aid measures

Eves:

Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention if soreness or redness persists.

Skin:

Immediately flood the affected skin area with large quantity of water, perferably under a shower. Remove contaminated clothing and continue washing. Contaminated clothing should be washed throughly before re-use. Obtain medical attention if blistering of the skin occures or redness persists.

Ingestion:

Do not induce vomiting. Have victim drink serval large glasses of water to dilute the stomach contents. Give the victim oxygen if he/she has difficulty in breathing. Obtain medical attention immediately.

Inhalation:

Remove the victim from exposure immediately. Give the victim oxygen if he/she has difficulty in breathing. Obtain medical attention immediately.

MEDICAL PERSONNEL:

Monitor the victim for systemic secondary effects on liver and kidney functions. Support and treat as appropriate.

SECTION 5. Fire-fighting measures

Flash Point – 20°C/68°F

Boiling Point – 80°C/176°F





Corporate Headquarters

10 Glenshaw Street, Orangeburg, NY 10962 Tel: 845.365.8200 • Fax: 845.365.8201

Toll-Free: 888.DYNAREX

Extinguishing Media – Dry Chemical or Alcohol Type Foam, Carbon Dioxide

Be aware of the possibility of re-ignition. Keep containers and surroundings cool with water spray.

Unusual Fire and Explosion Hazards –

Class 3 Flammability. Vapor can travel a considerable distance to a source of ignition and flashback. Flashback can occur if air temperature exceeds flash point. Be aware the possibility of re-ignition.

Special Fire Fighting Procedures –

Handle as Flammable Liquid. Use Respiratory Protection. Wear full protective clothing for Fire Fighting Personnel.

SECTION 6. Accidental release measures

- Flush spills with water.
- Contain and absorb using soil, sand, or other inert material.
- Vapor can accumulate in low areas. Consider the need for evacuation.
- Prevent the material from entering drains or water courses.

SECTION 7. Handling and storage

- Eliminate all sources of ignition. Store away from heat.
- Store in well ventilated area.
- Handle as flammable liquid. Follow local, state and federal regulations.
- Avoid inhaling vapor. Avoid contact with eyes, skin and clothing.
- Wear eye protection if splashing is expected.
- Wear appropriate protective clothing.
- Use respirator if exposure level is high when handling bulk liquid.
- Keep container tightly closed when not in use.





SECTION 8. Exposure controls/personal protection

- OSHA Occupation Exposure Standards PEL 400ppm (980mg/m3) 8h TWA
- UK EH40: OES 400ppm (980mg/m3) 8h TWA
- UK EH40: OES 500ppm (1225mg/m3) 15min TWA
- ACGIH: TLV 200ppm (980mg/m3) 8h TWA
- ACGIH: STEL 400ppm (1225mg/m3) 15min TWA
- Personal Protective Equipment
 - Gloves
 - Eye
 - Clothing

SECTION 9. Physical and chemical properties

Appearance – Liquid Saturated Towelette / Pad / Swab

Color – Clear Odor – Alcohol Vapor Density – 2.1 (Air = 1)

Viscosity (cSt) – 2.9 cps at <@2> °C

Evaporation Rate – Environmental Dependent

Water Solubility – Complete Specific Gravity – 0.8405

SECTION 10. Stability and reactivity

Stability – Stable under normal conditions

Conditions to Avoid – None Incompatibility – None

Hazardous Decomposition or By-product – Oxides of carbon





Polymerization -

Will Not Occur.

SECTION 11. Toxicological information

Acute Toxicity

- Low level of acute toxicity predicted.
- May be harmful by skin absorption.
- Oral LD50 (rat) 5045mg/kg.
- Dermal LD50 (rabbit) 12800mg/kg.
- Inhalation LCLO (rat) 1600ppm 4h.

Chronic Toxicity / Carcinogenicity

- Material not expected to cause long-term adverse health effects.
- Material not classifiable as to its carcinogenicity to humans (Group 3).
- Chronic / Sub-chronic studies resulted in adverse effects to:
 - Liver, spleen, biochemical effects, brain tissue degeneration, changes in reflex behavior, sensory nerve damage.

Genealogy Toxicity

Material is not expected to cause any mutagenic effects.

Reproductive / Developmental Toxicity

- Material is not expected to cause reproductive or developmental health effects.
- Experimental studies in animals have provided some evidence of embryo / fetus toxicity and birth defects only at does producing marked maternal toxicity.

SECTION 12. Ecological information

Mobility





Corporate Headquarters 10 Glenshaw Street, Orangeburg, NY 10962

Tel: 845.365.8200 • Fax: 845.365.8201

Toll-Free: 888.DYNAREX

- If released to soil, IPA is expected to have very high mobility
- Persistence / Degradability
- IPA is readily degraded in aerobic aqueous systems
- Bio-accumulation
- Low potential for bio-concentration in aquatic organisms

SECTION 13. Disposal considerations

- Transfer into suitable containers for recovery or disposal.
- Dispose in accordance with all applicable local and national regulations.
- Do not remove labels from container until the container has been cleaned.
- Do not cut, puncture or weld on or near the container.
- Do not incinerate closed containers.
- Empty containers may contain hazadous residues

SECTION 14. Transport information

- DOT CFR 172.101
- Not regulated per 49 CFR 173.4 Small Quantity Exemption

SECTION 15. Regulatory information

This product is compliant with the following:

- EU Label: Classification and labeling have been performed according to EU Directive 67/548/EEC and 99/45/EC including amendments
- EU Hazard Symbol and Indication of Danger
- F Highly flammable
- Xi Irritant
- R11 Highly flammable





Corporate Headquarters

10 Glenshaw Street, Orangeburg, NY 10962

Tel: 845.365.8200 • Fax: 845.365.8201

Toll-Free: 888.DYNAREX

- R36 Irritating to eyes
- R67 Vapors may cause drowsiness and dizziness
- S2 Keep out of reach of children
- S7 Keep container tightly closed
- S16 Keep away from sources of ignition No smoking
- S24 / S25 Avoid contact with skin and eyes
- S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- US (Federal and State) Regulations and International Chemical Registration Laws TSCA listing
- This product contains ingredients that are listed on or exempt from listing on the EPA Toxic Substance Control Act Chemical Inventory
- This product does not contain any chemicals subject to EPA Title III of the SARA Listing in Sections 302 and 304
- All ingredients in this product are listed on the European Inventory of Existing Commercial Chemical Substance (EINECS Listing) or are exempted from listing
- All ingredients in this product are listed on the Canada Domestic Substance List (DSL Listing)

SECTION 16. Other information

Disclaimer:

This Safety Data Sheet, which takes into consideration the requirements of Directive 76/768/EC and subsequent amendments and Directive 1999/45/EC plus subsequent amendments, has been prepared in accordance with Directive (EC) 1907/2006. It is believed to be correct and corresponds to the latest scientific/technical knowledge but all data, instructions, recommendations and/or suggestions are made without guarantee. No warranty, expressed or implied, is made and Dynarex Corp. assumes no legal responsibility or liability resulting from its use.





Reviewed on 9/16/15

SAFETY DATA SHEET

SECTION 1. Product and Company Identification

PRODUCT NAME: BZK Antiseptic Towelette

PRODUCT USE: Antiseptic **Product Code:** 1303, 1331

Manufacturer's Name: Dynarex Corporation

Manufacturer's Address: 10 Glenshaw Street
Orangeburg, NY 10962

Emergency or Information 888-DYNAREX or 845-365-8200

Phone No.: At other times, contact the local Poison Control Center

SECTION 2. Hazards Identification

Physical hazards
Health hazards

• Environmental hazards

OHSA defined hazards

Not classified
Not determined
Not classified

Label elements

• Hazard symbol None

Signal word Not availableHazard statement Not available

 Precautionary statement

Prevention
 Response
 Storage
 Disposal
 Not available
 Not available
 Not available
 Not available
 None known

Hazard(s) not otherwise classified (HNOC)

Supplemental information None





Corporate Headquarters 10 Glenshaw Street, Orangeburg, NY 10962 Tel: 845.365.8200 • Fax: 845.365.8201

Toll-Free: 888.DYNAREX

SECTION 3. Composition/information on Ingredients

Ingredients	CAS Number	%
BZK	8001-54-5	0.13
Water	7732-18-5	99.87

SECTION 4. First-aid measures

First aid procedures

Eye Contact Flush with cool water. Remove contact lenses, if

applicable, and continue flushing. Obtain medical

attention if irritation persists.

Skin Contact In case of skin irritation, discontinue use of product.

Inhalation Not a normal route of exposure. If symptoms

develop move victim to fresh air. If symptoms

persist, obtain medical attention.

Ingestion Not a normal route of exposure. Do not induce

vomiting, Never give anything by mouth if victim is unconscious, or is convulsing. Obtain medical

attention.

Notes to physician Symptoms may be delayed.

General advice If you feel unwell, seek medical advice (show the

label where possible). Ensure that medical

personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Keep out of reach of children. Avoid contact with eyes.

Flammable Limits: N/A Flash Point: N/A





SECTION 5. Fire-fighting measures

Flash Point: Not Available Flammable Limits: Not Available Extinguishing Media: Any

Special Fire Fighting Procedures: None **Unusual Fire and Explosion Hazards:** None

SECTION 6. Accidental release measures

Personal precautions: Keep unnecessary personnel away. Do not touch or walk

through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak.

Methods for containment: Prevent entry into waterways, sewers, basements or

confined areas.

Methods for cleaning up: Pick up and discard towel.

SECTION 7. Handling and storage

Handling: Use good industrial hygiene practices in handling this

material.

Storage: Keep out of reach of children. Store in a closed container

away from incompatible materials.

SECTION 8. Exposure controls/personal protection

Engineering controls: General ventilation normally adequate.

Personal protective

equipment





Corporate Headquarters

10 Glenshaw Street, Orangeburg, NY 10962 Tel: 845.365.8200 • Fax: 845.365.8201

Toll-Free: 888.DYNAREX

Eye/Face protection Follow standard industrial hygiene practices.

Hand protection Not required.

Skin and body protection As required by employer code.

Respiratory protection Where exposure guideline levels may be exceeded, use

and approved NIOSH respirator.

General hygiene Handle in accordance with good industrial hygiene and

considerations safety practice. When using do not eat or drink.

SECTION 9. Physical and chemical properties

Appearance/Odor: Liquid saturated on wipe

Color: Clear liquid

Form: Liquid saturated on wipe

Odor: Characteristic
Odor Threshold: Not available

Physical State: Solid **Boiling Point:** <200°F

Paper Components: 100% Virgin Paper

Specific Gravity: 1

SECTION 10. Stability and reactivity

Chemical Stability: Stable under recommended storage conditions.

Incompatibility: Caustics. Acids. Oxidizers.

Hazardous Decomposition Products: May include and are not limited to: oxides of carbon;

hydrogen chloride.

Hazardous Polymerization: Will not occur.

Conditions to avoid: Do not mix with other chemicals.

SECTION 11. Toxicological information

Effects of acute exposure

Eye May cause irritation





Corporate Headquarters 10 Glenshaw Street, Orangeburg, NY 10962 Tel: 845.365.8200 • Fax: 845.365.8201

Toll-Free: 888.DYNAREX

Skin In case of skin irritation, discontinue use of the

product.

Inhalation Not a normal route of exposure. May cause

respiratory tract irritation.

Ingestion Not a normal route of exposure. May cause

stomach distress, nausea or vomiting.

SensitizationNon-hazardous by WHMIS/OSHA criteria.Chronic EffectsNon-hazardous by WHMIS/OSHA criteria.CarcinogenicityNon-hazardous by WHMIS/OSHA criteria.MutagenicityNon-hazardous by WHMIS/OSHA criteria.Reproductive EffectsNon-hazardous by WHMIS/OSHA criteria.TeratogenicityNon-hazardous by WHMIS/OSHA criteria.

SECTION 12. Ecological information

Ecotoxicity Not available

Environmental effects Not available

Aquatic toxicity Not available

Persistence / degradability Not available

Bioaccumulation / accumulation Not available

Partition coefficient Not available

Mobility in environmental media Not available

Chemical fate information Not available

Other adverse effects Not available

SECTION 13. Disposal considerations

Waste codes: Not available





Corporate Headquarters

10 Glenshaw Street, Orangeburg, NY 10962

Tel: 845.365.8200 • Fax: 845.365.8201

Toll-Free: 888.DYNAREX

Disposal instructions: Discard after single use.

Review federal, state/provincial, and local government requirements prior to disposal.

Discard with solid waste. Dispose in accordance with all applicable regulations.

Waste from residues / unused products: Not available

Contaminated packaging: Not available

SECTION 14. Transport information

U.S. Department of Transportation (DOT) Not regulated as dangerous goods.

Transportation of Dangerous Goods (TDG - Canada) Not regulated as dangerous goods.

SECTION 15. Regulatory information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US Federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous No chemical

CERCLA (Superfund) reportable quantity

Benzene: 10.0000

Benzene, methyl-: 1000.0000 Benzene, (chloromethyl)-: 100.0000 Propylene oxide: 100.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No Delayed Hazard - No





Corporate Headquarters
10 Glenshaw Street, Orangeburg, NY 10962
Tel: 845.365.8200 • Fax: 845.365.8201

Toll-Free: 888.DYNAREX

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Section 302 extremely hazardous substance No

Section 311 hazardous chemical No

Clean Air Act (CAA) Not available

Clean Water Act (CWA) Not available

Safe Drinking Water Act (SDWA) Not available

Drug Enforcement Agency (DEA) Not available

Food and Drug Administration (FDA) Not available

State regulations WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

SECTION 16. Other information

Disclaimer:

This Safety Data Sheet, which takes into consideration the requirements of Directive 76/768/EC and subsequent amendments and Directive 1999/45/EC plus subsequent amendments, has been prepared in accordance with Directive (EC) 1907/2006. It is believed to be correct and corresponds to the latest scientific/technical knowledge but all data, instructions, recommendations and/or suggestions are made without guarantee. No warranty, expressed or implied, is made and Dynarex Corp. assumes no legal responsibility or liability resulting from its use.



Spectrum Brands, Inc. Rayovac Division 3001 Deming Way Middleton, WI 53562-1431

Phone: (608) 275-3340 Fax: (608) 275-4577 http://www.rayovac.com



The Safety Data Sheet is supplied as a service to you. For other related information, please visit: http://www.rayovac.com

1. IDENTIFICATION

PRODUCT NAME: Alkaline Battery Mercury Free

SIZES: All sizes

EMERGENCY HOTLINE: 800-424-9300 (24 hr, Chemtrec)

EDITION DATE: 08/11/2014

2. HAZARD IDENTIFICATION

We would like to inform our customers that these batteries are exempt articles and are not subject to the 29 CFR 1910.1200 OSHA requirements, Canadian WHMIS requirements or GHS requirements.

Emergency Overview

OSHA Hazards-not applicable

Target Organs-not applicable

GHS Classification-not applicable

GHS Label Elements, including precautionary Statement-not applicable

Pictogram-not applicable

Signal words-not applicable

Hazard statements-not applicable

Precautionary statements-not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME	CAS#	%	TLV*/**TWA
Manganese Dioxide	1313-13-9	32-38	C5.0 mg/m ³
Steel	7439-89-6	19-23	
Zinc	7440-66-6	11-16	5 mg/m³ (as ZnO Fume)
Potassium Hydroxide	1310-58-3	5-9	Solution Not Listed
Graphite	7782-42-5	3-5	15 mppcf
Barium Sulfate	7727-43-7	<5	15 mg/m ³
Water, paper, plastic, other		Balance	

^{*}Source: OSHA 29 CFR 1910.1000 Table Z-1, 2 or 3 11-01-2012

4. FIRST AID INFORMATION

THRESHOLD LIMIT VALUE (TLV) AND SOURCE: NA

EFFECTS OF OVEREXPOSURE: None in normal use

EMERGENCY FIRST AID PROCEDURES:

Skin and Eyes:

Do not pick up a shorting battery as it may cause a burn. Get immediate medical attention when eyes may have been exposed to battery contents from a ruptured battery. Wash skin with soap and water.

Swallowing:

If you or your doctor suspects that a battery has been ingested-for assistance in the US call the NATIONAL BATTERY INGESTION HOTLINE any time at (202) 625-3333: in Canada call 416-813-5900.

For more information, please visit:

http://www.nema.org/Policy/Environmental-Stewardship/Documents/batteryingest.pdf

5. FIRE FIGHTING MEASURES

FLASH POINT: NA
LOWER (LEL): NA
FLAMMABLE LIMITS IN AIR (%): NA
UPPER (UEL): NA

EXTINGUISHING MEDIA: Use water, foam, or dry powder as

appropriate.

AUTO-IGNITION: NA

SPECIAL FIRE FIGHTING PROCEDURES: As with any fire, wear self-contained breathing apparatus to avoid inhalation of hazardous decomposition products (See section 2).

SPECIAL FIRE OR EXPLOSION HAZARDS: DO NOT RECHARGE. As a typical sealed battery they may rupture when exposed to excessive heat; this could result in the release of flammable or corrosive materials.

6. ACCIDENTAL RELEASE MEASURES

TO CONTAIN AND CLEAN UP LEAKS OR SPILLS: In the event of a battery rupture, prevent skin contact and collect all released material in a plastic lined metal container.

REPORTING PROCEDURE: Report all spills in accordance with Federal, State and Local reporting requirements.

7. HANDLING AND STORAGE

Store batteries in a dry place. Storing unpackaged cells together with other combustible materials could result in cell shorting and heat build-up. Do not recharge. Do not puncture or abuse.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

RESPIRATORY PROTECTION (SPECIFY TYPE): NA
VENTILATION: Local Exhaust: NA

Mechanical (General): NA
Special: NA

Other: NA

PROTECTIVE GLOVES:

EYE PROTECTION:

OTHER PROTECTIVE CLOTHING:

NA

9. Physical and Chemical Properties

Boiling Point @ 760 mm Hg (°C):	NA	Percent Volatile by Volume (%):		NA
Vapor Pressure (mm Hg @ 25°C):	NA	Evaporation Rate (Butyl Acetate = 1): NA		NA
Vapor Density (Air = 1):	NA	Physical State: NA		NA
Density (grams/cc):	NA	Solubility in Water (% by Weight): NA		NA
pH:	NA	Appearance and Odor:	Geometric so	lid object

10. STABILITY AND REACTIVITY

STABLE OR UNSTABLE: Stable
INCOMPATIBILITY (MATERIALS TO AVOID): NA
HAZARDOUS DECOMPOSITION PRODUCTS: NA
DECOMPOSITION TEMPERATURE (0°F): NA

HAZARDOUS POLYMERIZATION: Will Not Occur

CONDITIONS TO AVOID: Avoid electrical shorting, puncturing or deforming

11. TOXICOLOGICAL INFORMATION

INGREDIENT NAME	CAS#	%	TLV*/**TWA
Manganese Dioxide	1313-13-9	32-38	C5.0 mg/m ³
Steel	7439-89-6	19-23	
Zinc	7440-66-6	11-16	5 mg/m³ (as ZnO Fume)
Potassium Hydroxide	1310-58-3	5-9	Solution Not Listed
Graphite	7782-42-5	3-5	15 mppcf
Barium Sulfate	7727-43-7	<5	15 mg/m ³
Water, paper, plastic, other		Balance	

^{*}Source: OSHA 29 CFR 1910.1000 Table Z-1, 2 or 3 11-01-2012

12. ECOLOGICAL INFORMATION

Consumers should dispose of discharged batteries through waste disposal services or legitimate collection outlets. Those collecting batteries should follow state and federal regulations. Partially discharged damaged batteries can overheat and cause fires in the presence of other combustible materials.

13. DISPOSAL CONSIDERATIONS

Always comply with Federal, state or local requirements. All Rayovac Alkaline batteries have been tested per Federal hazardous waste testing requirements (TCLP). The TCLP tests show Rayovac alkaline batteries are not hazardous waste.

http://www.nema.org/Policy/Environmental-

Stewardship/Documents/Companies%20Claiming%20to%20Recycle.MARCH2005.pdf

14. TRANSPORTATION INFORMATION

TRANSPORTATION-SHIPPING: Alkaline Batteries are considered dry-cell batteries and they are non-dangerous goods for transportation. These batteries must be packed in a way to prevent short circuits or generation of a dangerous quantity of heat.

USDOT - See Special Provision 130.

IMO/Ocean - Not Listed.

ICAO/IATA – See Special Provision A123. This special provision also states to put the words "not restricted" and "special provision A123" on the air waybill when an air waybill is issued.

15. REGULATORY INFORMATION

SARA 313: Notification is not required because these products are article(s) that do not release a covered toxic chemical under the normal conditions of storage, use, or handling.

NOTICE: The information and recommendations set forth are made in good faith and are believed to be accurate at the date of preparation. Spectrum Brands Inc. (Rayovac) makes no warranty expressed or implied.

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

P370+P378 - In case of fire: Use dry chemical, foam, carbon dioxide for extinction

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container to comply with applicable local, national and international

regulation.

Other hazards 2.3.

No additional information available

Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

Substance

Not applicable

Full text of H-phrases: see section 16

3.2. **Mixture**

Name	Product identifier	%	GHS-US classification
Polyethylene glycol	(CAS No) 25322-68-3	50 - 55	STOT SE 3, H335
Isopropyl alcohol	(CAS No) 67-63-0	20 - 25	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
L-Menthol	(CAS No) 2216-51-5	1	Skin Irrit. 2, H315 Eye Irrit. 2A, H319

SECTION 4: First aid measures

Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation

: Remove to fresh air and keep at rest in a position comfortable for breathing. If breathing stops, give artificial respiration. In case of breathing difficulties administer oxygen. by trained personnel. Seek medical attention immediately

First-aid measures after skin contact

: Immediately flush skin with plenty of water for at least 15 minutes. Remove/Take off immediately all contaminated clothing. Do not rub the skin and eyes after direct contact with the product. Seek medical attention immediately. Wash contaminated clothing before reuse.

First-aid measures after eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately get medical attention.

First-aid measures after ingestion

Contact a Poison Control Center immediately. Give no more than 2 glasses of water and induce vomiting by giving 30 cc (2 tablespoons) of syrup of ipecac. If victim is a child, give no more than 1 glass of water and 15cc (1 tablespoon) syrup of ipecac. If syrup of ipecac is unavailable, give 2 glasses of water and induce vomiting by touching finger to back of victim's throat. Do not give anything by mouth to an unconscious or convulsing person. Get immediate medical attention. Immediately call a POISON CENTER or doctor/physician.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation

: May cause respiratory irritation. May cause drowsiness or dizziness. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.

Symptoms/injuries after skin contact

Repeated or prolonged skin contact may cause irritation.

Symptoms/injuries after eye contact

Causes serious eye irritation.

Symptoms/injuries after ingestion

Irritating to the gastrointestinal tract. May cause abdominal pain and vomiting (sometimes bloody). Ingestion may cause central nervous system depression, low blood pressure, rapid heart beat and liver damageEarly to moderate central nervous system depression may be evidenced by giddiness, headache, dizziness and nausea. In extreme cases, unconsciousness, respiratory depression and death may occur. Liver damage may be evidenced by loss of appetite, jaundice (yellowish skin color) and sometimes pain in the upper abdomen on the right

4.3. Indication of any immediate medical attention and special treatment needed

Individuals with pre-existing skin disorders, eye problems, or impaired respiratory function may be more susceptible to the effects of overexposure.

06/06/2014 2/10 EN (English)

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Dry powder. Carbon dioxide. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.

Explosion hazard : May form flammable/explosive vapour-air mixture.

Reactivity Thermal decomposition generates: Corrosive vapours. Reacts violently with acids. An

exothermic reaction may occur.

Advice for firefighters 5.3.

Other information

: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any Firefighting instructions

chemical fire. Prevent fire-fighting water from entering environment.

Protective equipment for firefighters : Do not enter fire area without proper protective equipment, including respiratory protection.

> Containers may swell and Burst during a fire due to internal pressure caused by heat. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. Alcohols burn with a pale blue flame which may be extremely hard to see under normal lighting conditions. Personnel may be able to feel the heat of the fire without seeing flames. Extreme caution must be exercised in fighting alcohol fires.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures : Eliminate all ignition sources if safe to do so. Use special care to avoid static electric charges. No

naked lights. No smoking. Stop leak if safe to do so. No action shall be taken involving any personal risk or without suitable training. Wear protective clothing. For further information refer to

section 8: Exposure-controls/personal protection.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Ventilate area. **Emergency procedures**

6.2. **Environmental precautions**

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Methods and material for containment and cleaning up

: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Consult the appropriate authorities about waste disposal. Ensure all national/local regulations are observed.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapours are flammable.

Precautions for safe handling

Methods for cleaning up

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Personal protective equipment should be selected based upon the conditions under which this product is handled or used. Use personal protective equipment as required. Provide good ventilation in process area to prevent formation of vapour. Do not breathe gas, fumes, vapour or spray. No naked lights. No smoking. Use only non-sparking tools. Never use pressure to empty container. Ground/bond container and receiving equipment. Take care to allow internal pressure to escape from container before releasing closures. Remove closure carefully; internal pressure may be present. Keep closure up to prevent leakage. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene measures

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

06/06/2014 EN (English) 3/10

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Ensure the ventilation system is regularly maintained and tested. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of mists and/or vapors below the recommended exposure limits. Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. A washing facility/water for eye and skin cleaning purposes should be present. Comply with applicable regulations.

Storage conditions

Keep only in the original container in a cool well ventilated place. Keep in fireproof place. Keep container tightly closed. Protect containers against physical damage. Detached outside storage is preferable. Inside storage should be in an NFPA approved flammable liquids storage room or cabinet. Store in corrosion-proof area at temperatures below 77 °F (25°C). Store away from direct sunlight or other heat sources.

Incompatible materials

Storage temperature

: Avoid mixing with acids, most common metals, strong oxidizing agents, brass, zinc, chlorine, aluminum, copper, bronze, mercury, dimethyl sulfate and acetyl chloride.

: < 25 °C Store at temperatures below 77 °F (25 °C)

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Isopropyl alcohol (67-63-0)		
USA ACGIH ACGIH TWA (ppm)		200 ppm
USA ACGIH ACGIH STEL (ppm)		400 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	980 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm

8.2. Exposure controls

Appropriate engineering controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of mists and/or vapors below the recommended exposure limits. Use explosion-proof ventilating equipment.

Personal protective equipment

: Avoid all unnecessary exposure. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to OSHA regulations. For certain operations, additional Personal Protection Equipment (PPE) may be required. Protective goggles. Gloves. Protective clothing.







Hand protection

: Wear protective gloves. rubber gloves. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Eye protection

: Chemical goggles or face shield.

Skin and body protection

: Wear suitable protective clothing. Chemical resistant safety shoes.

Respiratory protection

Wear a self-contained breathing apparatus and appropriate personal protective equipment (PPE). Suggestions provided in this section for exposure control and specific types of protective equipment are based on readily available information. Users should consult with the specific manufacturer to confirm the performance of their protective equipment. Specific situations may require consultation with industrial hygiene, safety, or engineering professionals. Care must be taken to assure that any respirator chosen is capable of protecting the user from both ammonia and ethyl alcohol vapors.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear.
Colour : Green.

Odour : Odor of isopropyl alcohol, residual odor of menthol.

06/06/2014 EN (English) 4/10

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Odour threshold : No data available

pH : 8.5

Relative evaporation rate (butyl acetate=1) : No data available Melting point : No data available : No data available Freezing point Boiling point : $> 35 \, ^{\circ}\text{C} \, (>95 \, ^{\circ}\text{F})$: 16.6 °C (62 °F) Flash point Auto-ignition temperature : No data available Decomposition temperature : No data available Flammability (solid, gas) : No data available : No data available Vapour pressure Relative vapour density at 20 °C : No data available

Density : 1.029 (Specific Gravity @ 25 °C)

Soluble in water. Solubility Log Pow No data available Log Kow : No data available Viscosity, kinematic No data available : No data available Viscosity, dynamic Explosive properties : No data available Oxidising properties No data available : No data available **Explosive limits**

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Relative density

Thermal decomposition generates: Corrosive vapours. Reacts violently with acids. An exothermic reaction may occur.

: No data available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

Avoid mixing with acids, most common metals, strong oxidizing agents, brass, zinc, chlorine, aluminum, copper, bronze, mercury, dimethyl sulfate and acetyl chloride.

10.6. Hazardous decomposition products

Thermal decomposition generates: Fume. Carbon monoxide. Carbon dioxide. May release flammable gases. Corrosive vapours. Ammonia. Nitrogen oxides. release of highly flammable gases/vapours hydrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

(Based on available data, the classification criteria are not met)

Isopropyl alcohol (67-63-0)	
LD50 oral rat	4396 mg/kg
LD50 dermal rabbit	12800 mg/kg
LC50 inhalation rat (ppm)	16000 ppm (Exposure time: 8 h)
ATE CLP (oral) 4396.000 mg/kg bodyweight	
ATE CLP (dermal) 12800.000 mg/kg bodyweight	

06/06/2014 EN (English) 5/10

Medicaine[®] Sting and Bite Relief

Safety Data Sheet according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

L-Menthol (2216-51-5)	
LD50 oral rat	3300 mg/kg
ATE CLP (oral)	3300.000 mg/kg bodyweight
Polyethylene glycol (25322-68-3)	
LD50 dermal rabbit	> 20 ml/kg
Skin corrosion/irritation	: Not classified
	(Based on available data, the classification criteria are not met)
	pH: 8.5
Serious eye damage/irritation	: Causes serious eye irritation.
	pH: 8.5
Respiratory or skin sensitisation	: Not classified
	(Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified
	(Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified
	(Based on available data, the classification criteria are not met)
Isopropyl alcohol (67-63-0)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
	(Based on available data, the classification criteria are not met)
Specific target organ toxicity (single exposure)	: May cause respiratory irritation. May cause drowsiness or dizziness.
Specific target organ toxicity (repeated	: Not classified
exposure)	(Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified
, topiration nazara	(Based on available data, the classification criteria are not met)
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause respiratory irritation. May cause drowsiness or dizziness. Depression of the centra nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/injuries after skin contact	: Repeated or prolonged skin contact may cause irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: Irritating to the gastrointestinal tract. May cause abdominal pain and vomiting (sometimes bloody). Ingestion may cause central nervous system depression, low blood pressure, rapic heart beat and liver damageEarly to moderate central nervous system depression may be evidenced by giddiness, headache, dizziness and nausea. In extreme cases, unconsciousness respiratory depression and death may occur. Liver damage may be evidenced by loss o appetite, jaundice (yellowish skin color) and sometimes pain in the upper abdomen on the righ side.

SECTION 12: Ecological information

Toxicity 12.1.

Isopropyl alcohol (67-63-0)				
LC50 fishes 19640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])EC50 Daphnia 113299 mg/l (Exposure time: 48 h - Species: Daphnia magna)LC50 fish 211130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])				
		L-Menthol (2216-51-5)		
		LC50 fishes 1 18.9 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])		

Persistence and degradability

Medicaine® Sting and Bite Relief	
Persistence and degradability	Not established.

06/06/2014 EN (English) 6/10

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

12.3. Bioaccumu	lative r	otential
-----------------	----------	----------

Medicaine® Sting and Bite Relief		
Bioaccumulative potential	Not established.	
Isopropyl alcohol (67-63-0)		
Log Pow	0.05 (at 25 °C)	

Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not re-use empty

containers. Ensure all national/local regulations are observed. Consult the appropriate authorities

about waste disposal.

Additional information : Handle empty containers with care because residual vapours are flammable.

Avoid release to the environment. Ecology - waste materials

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1993 Flammable liquids, n.o.s. (contains isopropanol), 3, II

UN-No.(DOT) : 1993 DOT NA no. UN1993

DOT Proper Shipping Name : Flammable liquids, n.o.s.

(contains isopropanol)

Department of Transportation (DOT) Hazard

Classes

: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



DOT Symbols : G - Identifies PSN requiring a technical name

Packing group (DOT) : II - Medium Danger

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite DOT Special Provisions (49 CFR 172.102)

(31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal............... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / (1 + a (tr - tf)) Where: tr is the maximum mean bulk temperature

during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when

the flash point of the hazardous material transported is greater than 0 C (32 F).

TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) 150 DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242 DOT Quantity Limitations Passenger aircraft/rail : 5 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

06/06/2014 7/10 EN (English)

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Additional information

Other information

: No supplementary information available.

ADR

Transport document description

ransport accument accomption

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Isopropyl alcohol (67-63-0)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.	
SARA Section 313 - Emission Reporting	1.0 % (only if manufactured by the strong acid process, no supplier notification)	

L-Menthol (2216-51-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Polyethylene glycol (25322-68-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Isopropyl alcohol (67-63-0)		
Listed on the Canadian DSL (Domestic Sustances List) inventory.		
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects	

L-Menthol (2216-51-5)

Listed on the Canadian DSL (Domestic Sustances List) inventory.

Polyethylene glycol (25322-68-3)

Listed on the Canadian DSL (Domestic Sustances List) inventory.

EU-Regulations

Isopropyl alcohol (67-63-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

L-Menthol (2216-51-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

Polyethylene glycol (25322-68-3)

Listed on the EU - No-Longer Polymers List (67/548/EEC)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

06/06/2014 EN (English) 8/10

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

15.2.2. **National regulations**

Isopropyl alcohol (67-63-0)

Listed on the AICS (the Australian Inventory of Chemical Substances)

Listed on Inventory of Existing Chemical Substances (IECSC)

Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.

Listed on Industrial Safety and Health Law Substances (ISHL)

Listed on the Korean ECL (Existing Chemical List) inventory.

Listed on New Zealand - Inventory of Chemicals (NZIoC)

Listed on Inventory of Chemicals and Chemical Substances (PICCS)

Listed on the Canadian Ingredient Disclosure List

L-Menthol (2216-51-5)

Listed on the AICS (the Australian Inventory of Chemical Substances)

Listed on Inventory of Existing Chemical Substances (IECSC)

Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.

Listed on Industrial Safety and Health Law Substances (ISHL)

Listed on the Korean ECL (Existing Chemical List) inventory.

Listed on New Zealand - Inventory of Chemicals (NZIoC)

Listed on Inventory of Chemicals and Chemical Substances (PICCS)

Polyethylene glycol (25322-68-3)

Listed on the AICS (the Australian Inventory of Chemical Substances)

Listed on Inventory of Existing Chemical Substances (IECSC)

Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.

Listed on the Korean ECL (Existing Chemical List) inventory.

Listed on New Zealand - Inventory of Chemicals (NZIoC)

Listed on Inventory of Chemicals and Chemical Substances (PICCS)

15.3. US State regulations

No additional information available

SECTION 16: Other information

Other information : None.

Full text of H-phrases: see section 16:

Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapour
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

NFPA health hazard

: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt

medical attention is given.

NFPA fire hazard

: 3 - Liquids and solids that can be ignited under almost all

ambient conditions.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.

SDS US (GHS HazCom 2012)

06/06/2014 EN (English) 9/10

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

This Material Safety Data Sheet is intended only as a guide to the appropriate precautionary handling of the material by a person trained in, or supervised by a person trained in, the safe handling of chemical materials. James Alexander Corporation (JAC), expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose with respect to the product or information provided herein. All information appearing herein is based upon data obtained from the manufacturer(s) and/or recognized technical sources. While the information is believed to be accurate, JAC makes no representations as to its accuracy or sufficiency. Conditions of use are beyond JAC's control and therefore, users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein and does not relate to its use in combination with any other material or in any other process.

06/06/2014 EN (English) 10/10