

# **SAFETY DATA SHEET**

Effective Date: JULY 2019

ITEM: Inland Alert/Locate Kit

**PART #** 543 **UPC** 077403105434

# CONTENTS

Marine Hand Held Red Flare (HHRF) SDS

Marine Hand Held Orange Smoke Signal (HHOS) SDS

Air Horn SDS

# SHIPPING INFORMATION

UN0373, Signal devices, hand 1.4S (ERG 114) EX1986040106 EX1997080126



#### SAFETY DATA SHEET

# 1. Product and Company Identification

# Marine Handheld Red Flare (HHRF)

**Identified Use:** Emergency signal Use Advised Against: Do not use indoors or inside of a vehicle.

Manufacturer's Information: Orion Safety Products

3157 N 500 W **EMERGENCY** CHEMTREC Peru, Indiana 46970 **RESPONSE** 1-800-424-9300 US 1-800-851-5260 1-703-527-3887 Int'l (11) 1-765-472-4375

# 2. Hazards Identification

**GHS Classifications** Explosive Category 1.4

Category 2 Skin Irritation Perchlorate Material-special handling may apply, Eye Irritation Category 2A see www.dtsc.ca.gov/hazardouswaste/perchlorate. STOT-Single Exposure Category 3

**GHS Label Elements** 

**Hazard Statements** 

H204 Fire or projection hazard H315 Causes skin irritation Causes serious eye irritation H319 H335 May cause respiratory irritation **Pictograms** 





#### Signal Word Warning

Precaut	ionary Statements	P370	In case of fire; use water deluge.
P102	Keep out of reach of children.	P301/315	IF SWALLOWED: Get immediate medical advice /attention.
P103	Read carefully and follow all instructions	P302/352	IF ON SKIN: Wash with plenty of soap and water.
P210	Keep away from heat/sparks/open flames/hot surfaces.	P304/340/342	IF INHALED: Remove victim to fresh air and keep at rest in a position
F210	No smoking		comfortable for breathing. If experiencing respiratory symptoms: Call a
P232	Protect from moisture		POISON CENTER or doctor/physician.
P261	Avoid breathing dust/fumes.	P305/338/351	IF IN EYES: Rinse cautiously with water for several minutes. Remove
P264	Wash hands thoroughly after handling.		contact lenses, if present and easy to do. Continue rinsing.
P270	Do not eat, drink or smoke when using this product.	P332/313	If skin irritation or rash occurs, get medical advice/attention.
P271	Use only outdoors.	P501	Dispose of contents / container in accordance with local and national
P280	Wear protective eye protection.		Regulations.

Hazards Not Otherwise Classified (HNOC): produces hot flame

#### 3. Composition / Information on Ingredients

Component	CAS#	EINCS#	Percentage
Strontium Nitrate	10042-76-9	233-131-6	<50%
Sulfur	7704-34-9	231-722-6	<25%
Potassium Perchlorate	7778-74-7	231-912-9	<20%
Polyethylene	9002-88-4	none	<5%
Potassium Chlorate	3811-04-9	231-100-4	<5%

Note: Due to Confidential Business Information, "Trade Secrets", the exact percentage of each ingredient has not been disclosed.

CBI information will be shared with appropriate authorities if circumstances warrant.

#### 4. First Aid Measures

### Description of first aid measures

If contents are inhaled, remove to fresh air. Watch for signs of allergic reaction. If other symptoms develop, Inhalation

get medical aid immediately.

If contents are contacted, wash with area with soap and water for 15 minutes. Remove contaminated clothing Skin and wash before reuse. Get medical aid if irritation occurs.

If contents get into eyes, flush with plenty of water for at least 15 minutes, occasionally lifting the upper and lower lids. Remove contact lenses if easily possible. Get medical aid immediately.

Ingestion Get medical aid immediately.

Most important symptoms and effects both acute and delayed See section 2 labeling and section 11

No data available Indication of any immediate medical attention and special treatment needed



# 5. Firefighting Measures

Extinguishing Media Water deluge Unsuitable Extinguishing Media Foam and dry chemical extinguishers and suffocation are ineffective.

Protective Equipment and Precautions for Firefighters

Wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode. Prevent further propagation of fire by spraying unburnt

nearby product with water. Combat fire from a sheltered position.

Specific Hazards Arising
Only use outdoors. Flame and sparks are ejected out the open end of the flare when it functions. Do not point flare at any

from the Chemical part of the body or flammable material.

Further Information No data available

#### 6. Accidental Release Measures

#### Personal Precautions / Protective Equipment / Emergency Procedures

Do not breathe smoke or contents. Avoid contact with skin and eyes. Wear flame retardant clothing with long sleeves, dust mask, rubber or nitrile gloves, safety goggles, safety shoes when cleaning up contents. Avoid friction on the released product. Keep away from ignition sources.

#### **Environmental Precautions**

Prevent dispersion of contents on soil and in water. Prevent contents from spreading or entering into drains, ditches, groundwater or rivers by using appropriate barriers.

#### Methods for Containment and Clean-up

Use caution when cleaning up spilled contents. Remove heat, flames, sparks and other sources of ignition. Use non-sparking tools and equipment. Prevent buildup of electrostatic charges by grounding. Clean spills in a manner that does not disperse dust into the air. When cleaning up contents, use local and/or general exhaust. Clean up avoiding dust generation and place in a well identified container. Do not absorb in sawdust or other combustible absorbents. Wash away remainder with plenty of water. Collect wash water for approved disposal.

### 7. Handling and Storage

#### **Precautions for Safe Handling**

Hold and point signal away from body when igniting. Hold signal downwind when burning. Avoid breathing smoke. Avoid contact with clothing and other combustible materials. Use outdoors only! Do not ignite or burn product inside a vehicle, boat cabin or building. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Avoid contact with skin and eyes. Avoid contact with heat, sparks, and flame. Signals should be allowed to burn to completion. Unburned and partially burned signals contain potassium perchlorate which should not be allowed to come into contact with surface and ground water. Perchlorate Material-special handling may apply. See <a href="https://www.dtsc.ca.gov/hazardouswaster/perchlorate">www.dtsc.ca.gov/hazardouswaster/perchlorate</a>.

#### Conditions for Safe Storage, Including Any Incompatibilities

Store in a dry place away from direct sunlight, heat and incompatible materials. Store away from food and beverages. Store away from flammable materials, sources of heat, flame and sparks. Store at ambient temperature. Do not store partially burned signals in a vehicle, boat, closed container, warehouse, or any other building.

### 8. Exposure Controls / Personal Protection

#### **Control Parameters**

**Exposure Limits OSHA PEL ACGIH TLV** Strontium Nitrate Not established Not established Sulfur Not established Not established Potassium Perchlorate Nuisance dust, 15 mg/m3 Nuisance dust, 15 mg/m3 Polyethylene 15 mg/m<sup>3</sup> TWA 10 mg/m<sup>3</sup> TWA Potassium Chlorate Not established Not established

#### **Exposure Controls**

Engineering Controls Use product outdoors only! When cleaning up contents, use local and/or general exhaust.

Eye / Face Protection Safety glasses or goggles

Skin Protection None under normal conditions when using product unless prolonged handling is anticipated. Impervious protective

clothing, including gloves, boots, and a lab coat, apron or coveralls, as appropriate, when cleaning up spilled product.

Wash hands and face before eating, drinking or using tobaccoproducts

Respiratory Protection None under normal conditions when using product. A particulate respirator (NIOSH t N95 or better filters)

may be worn during the cleanup of spilled contents.

General Hygiene Use product outdoors away from combustible products. For cleanup of spilled contents, emergency showers and eye

wash stations should be available. Educate and train employees in the safe use and handling of hazardous materials. Maintain good housekeeping and safety practices. Do not let contents accumulate in storage or work areas. Clean

spills up promptly.

### 9. Physical and Chemical Properties

Appearance (color, physical form, shape): Grey powde

рН: No data available Melting Point: No data available Solubility: No data available Boiling Point / Range: Freezing Point: Not applicable Not applicable **Evaporation Rate:** Not applicable Vapor Pressure: Not applicable Specific Gravity: Not applicable Vapor Density: Not applicable Odor: No data available Odor Threshold: No data available Flash Point: No data available Flammability: No data available Flammability Limits: No data available Relative Density: No data available

Partition Coefficient: No data available Viscosity: No data available

Auto Ignition Temperature: No data available Decomposition Temperature: No data available



# 10. Stability and Reactivity

Chemical Stability: Stable Reactivity: No information available Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid Combustible materials, heat, flames, sparks and other sources of ignition. Moisture. Incompatible Materials
Strong acids, strong fuels, ammonia salts and strong bases.

Hazardous Decomposition Products Carbon monoxide, carbon dioxide, sulfur oxides and nitrogen oxides.

#### 11. Toxicology Information

Ingredient acute toxicity information

LC50 Toxicology Oral LD50 Skin LD50 Strontium Nitrate Rat: 1892 mg/kg Not stated Not stated Rat: 5050 mg/kg Sulfur Rat:>2020 mg/kg Rat:>5.49 mg/L air concentration Potassium Perchlorate Rat: 2100 mg/kg Not stated Not stated

Polyethylene Rat: 4000 mg/kg Not stated Not stated
Potassium Chlorate Rat: 4000 mg/kg 2000 mg/kg (Rabbit) No information found

Product toxicological information

Acute Toxicity
Skin Irritation / Corrosion
Serious Eye Damage / Irritation
Respiratory / Skin Sensitization
Germ Cell Mutagen
Carcinogen
Reproductive Toxicity

Not classified – Acute Toxicity Estimate yields oral LD50 over 5000 mg/kg bw
Category 2 – over 10% of ingredients classified as a Category 2 skin irritant
Category 2A – over 10% of ingredients classified as a Category 2A eye irritant
Not classified (Based on available data, the classification criteria are not met)
Not classified (Based on available data, the classification criteria are not met)
Not classified (Based on available data, the classification criteria are not met)

Carcinogen
Reproductive Toxicity
STOT – single exposure
STOT – repeated exposure

Aspiration Hazard Not classified (Based on available data, the classification criteria are not met)

Likely routes of exposure Skin, ingestion, inhalation

Symptoms related to the physical, chemical and toxicological characteristics Contents irritating to eyes due to chemical and physical properties of the mixture. Ingestion of contents may cause gastrointestinal irritation with nausea, vomiting and diarrhea. Individuals with known allergies to sulfide drugs may also have allergic reactions to elemental sulfur.

Delayed and immediate effects and chronic effects from short and long term exposure Interactive effects

Inhalation of contents or smoke from burning flare will cause irritation to the lungs and mucus membrane. Prolonged or repeated skin contact with contents may cause dermatitis.

No information found

### 12. Ecological Information

Ingredient toxicity / persistence / degradability / bioaccumulation / mobility in soil and water

Aquatic Toxicity Potassium Chlorate: fish: LC50 oncorhynchus mykiss (rainbow trout) 1750 mg/l – 96 hr, EC50 daphnia

magna (water flea) 1093 mg/l 24 hr

Strontium Nitrate: Acute toxicity - Fishes, Carassius auratus, LC100, 9,615 mg/l; Chronic toxicity - Fishes,

Gasterosteus aculeatus, LC100, 2.912 mg/l

Sulfur: Toxicity to fish LC50 - Oncorhynchus mykiss (rainbow trout) -> 180 mg/l - 96 h Toxicity to dapnia

and other aquatic invertebrates: EC50 - Daphnia magna (Water flea) - > 5,000 mg/l - 48 h

Persistence / Degradability No information found Bioaccumulation / Accumulation No information found

Mobility in Environmental Media Strontium Nitrate: Water:: considerable solubility and mobility; Soil/sediments non-significant adsorption

Other adverse effects No information found

#### 13. Disposal Considerations (for spills and leakage)

Dispose of contaminated product and materials used in cleaning up spills or leaks in the manner approved for pyrotechnic material. Consult appropriate federal, state and local regulatory agencies to ascertain proper disposal procedures. Open burning is the preferred method of disposal for pyrotechnic materials. Allow flares to burn to completion. Refer to California Code of Regulations, Title 33, Sections 67384.1-67384.10 for additional information on handling and disposal of potassium perchlorate containing materials.

### 14. Transportation Information

	ID Number	Proper Shipping Name	Hazard Class	Packing Group	EX Number	Reportable Quantities
Domestic & International	UN0373	Signal devices, hand	1.48	n/a	EX1986040106	none
Marine pollutant: no	)		Special precar	utions for user:	no information availa	able



# 15. Regulatory Information

US Regulations	TS CA	CERC	LA	CWA	CAA	SARA 313	SARA 302	Acute	Chronic	Fire	Reactivity	Pressure
Strontium Nitrate	yes	no		no	no	yes	no	yes	no	no	yes	no
Sulfur	yes	no		no	no	no	no	yes	no	yes	no	no
Potassium Perchlorate	yes	no		no	no	no	no	yes	no	no	yes	no
Polyethylene	yes	no		no	no	no	no	no	no	no	no	no
Potassium Chlorate	yes	no		no	no	no	no	yes	no	no	yes	no
US States		Prop 65	NJ	PA	Can	ıada	W	/HMIS		DLS	Europe	Wgk
Strontium Nitrate		no	1743	no			D1B To	ing materials xic materials		yes		2
Sulfur		no	1757	yes			B4 Flam	xic materials nmable solid xic materials		yes		1 / nwg
Potassium Perchlora	te	no	1577	yes			C Oxidizi	ng mateerial	S	yes		1

#### 16. Other Information

Polyethylene

Potassium Chlorate

Revision Information: March 2019

NFPA Rating		HMIS Rating	
Flammability	2	Flammability	1
Health	2	Health	3
Reactivity	1	Physical Hazard	1

no

no

no

1560

no

yes

Key / Legend

HMIS: hazardous material identification system NFPA: national fire protection association CAS: Chemical Abstracts Service number EINECS: European inventory of existing chemical substances OSHA PEL: occupational safety and health

D1B Toxic materials

Not controlled

C Oxidizing materials

D1B Toxic materials

administration permissible exposure limit
NIOSH TLV: national institute of occupational safety
and health Threshold Limit Value
NTP: National Toxicology Program

IARC: International Agency for Research on Cancer

CWA: clean water act - US

TSCA: toxic substance control act - US

Not listed

2

CERCLA: comprehensive environmental response compensation and liability act – US

CAA: clean air act - US

SARA: superfund amendments and reauthorization

act - US

yes

yes

PROP 65:California's Proposition 65 list WHMIS: workplace hazardous materials information system - Canada

DSL: Domestic Substances List - Canada WGK: water hazard classes - Germany

#### Legal Statement

This information is accurate to the best knowledge of Orion Safety Products. Orion Safety Products makes no representations or warranties, either express or implied, including without limitation any warranties of merchantability or fitness for a particular purpose, with respect to the information set forth herein or the product to which the information refers. Accordingly, Orion Safety Products will not be responsible for damages resulting from use of or reliance upon this information. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation



# SAFETY DATA SHEET

### 1. Product and Company Identification

Marine Hand Held Orange Smoke Signal (HHOS)

Identified Use: Emergency signal Use Advised Against: Do not use indoors or inside of a vehicle.

Manufacturers Information: Orion Safety Products

3157 N 500 W EMERGENCY CHEMTREC
Peru, Indiana 46970 RESPONSE 1-800-424-9300
US 1-800-851-5260 1-703-527-3887
Int'l (11) 1-765-472-4375

### 2. Hazards Identification

#### **GHS Classifications**

Explosive Category 1.4 H204
Skin Irritation Category 2 H315
Eye Irritation Category 2A H319
Skin Sensitization Category 1 H317
STOT-Repeated Exposure Category 1 H372

#### **GHS Label Elements**

Pictograms

Hazard Statements

H204 Fire or projection hazard

H315 Causes skin irritation

H319 Causes serious eye irritation

H317 May cause an alleggic skin reaction

H317 May cause an allergic skin reaction
Causes damage to lungs through
prolonged or repeated exposure

Sig	nal Word	Danger		
Precaut	tionary Statements		P370	In case of fire: use water deluge.
P102	Keep out of reach	of children.	P301/315	IF SWALLOWED: Get immediate medical advice /attention.
P103	Read carefully and	d follow all instructions.	P302/352	IF ON SKIN: Wash with plenty of soap and water.
P210	Keep away from h	eat/sparks/open flames/hot surfaces.	P304/340/342	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a
P232	Protect from moist	ure		POISON CENTER or doctor/physician.
P261	Avoid breathing du	ıst/fumes.	P305/338/351	IF IN EYES: Rinse cautiously with water for several minutes. Remove
P264	Wash hands thoro	ughly after handling.		contact lenses, if present and easy to do. Continue rinsing.
P270	Do not eat, drink o	r smoke when using this product.	P333/313	If skin irritation or rash occurs, get medical advice/attention.
P271	Use only outdoors		P501	Dispose of contents / container in accordance with local and national
P280	Wear protective ev	re protection		Regulations

Hazards Not Otherwise Classified (HNOC): produces hot flame and copious amount of smoke

### 3. Composition / Information on Ingredients

Component	CAS#	EINCS#	Percentage
Solvent Yellow Dye	842-07-9	212-668-2	<40%
Lactose	63-42-3	200-559-2	<40%
Potassium Chlorate	3811-04-9	231-100-4	<25%
Solvent Orange 7 Dye	3118-97-6	221-490-4	<20%
Strontium Carbonate	1633-05-2	216-643-7	<1%
Calcium Carbonate	1317-65-3	215-279-6	<1%
Charcoal	7440-44-0	231-153-3	<1%
Umber	12713-03-0	235-784-5	<1%
Strontium Nitrate	10042-76-9	233-131-9	<1%
Shellac	9000-59-3	232-549-9	<1%
Potassium Nitrate	7757-79-1	231-818-8	<1%
Sawdust (cellulose)	9004-34-6	232-674-9	<1%

Note: Due to Confidential Business Information, "Trade Secrets", the exact percentage of each ingredient has not been disclosed.

CBI information will be shared with appropriate authorities if circumstances warrant.



#### 4. First Aid Measures

#### Description of first aid measures

Inhalation If contents are inhaled, remove to fresh air. Watch for signs of allergic reaction. If other symptoms develop,

get medical aid immediately.

Skin If contents are contacted, wash with area with soap and water for 15 minutes. Remove contaminated clothing

and wash before reuse. Get medical aid if irritation occurs.

Eyes If contents get into eyes, flush with plenty of water for at least 15 minutes, occasionally lifting the upper and lower lids.

Remove contact lenses if easily possible. Get medical aid immediately.

**Ingestion** Get medical aid immediately.

Most important symptoms and effects both acute and delayed

See section 2 labeling and section 11

10 mg/m<sup>3</sup>

Indication of any immediate medical attention and special treatment needed No data available

### 5. Firefighting Measures

Extinguishing Media Water deluge Unsuitable Extinguishing Media Foam and dry chemical extinguishers and suffocation are ineffective.

Protective Equipment and Wear Precautions for Firefighters in the

Wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode. Prevent further propagation of fire by spraying unburnt

nearby product with water. Combat fire from a sheltered position.

Specific Hazards Arising from the Chemical Further Information

Only use outdoors. Contents / dust may form explosive mixtures. Flame and copious amounts of smoke are ejected out the open end of the signal when it functions. Do not point signal at any part of the body or flammable material.

No data available

### 6. Accidental Release Measures

#### Personal Precautions / Protective Equipment / Emergency Procedures

Do not breathe smoke or contents. Avoid contact with skin and eyes. Wear flame retardant clothing with long sleeves, dust mask, rubber or nitrile gloves, safety goggles, safety shoes when cleaning up contents. Avoid friction on the released product. Keep away from ignition sources. Contains strong dyes which will color all exposed areas.

#### **Environmental Precautions**

Prevent dispersion of contents on soil and in water. Prevent contents from spreading or entering into drains, ditches, groundwater or rivers by using appropriate barriers.

#### Methods for Containment and Clean-up

Use caution when cleaning up spilled contents. Remove heat, flames, sparks and other sources of ignition. Use non-sparking tools and equipment. Prevent buildup of electrostatic charges by grounding. Clean spills in a manner that does not disperse dust into the air. When cleaning up contents, use local and/or general exhaust. Clean up avoiding dust generation and place in a well identified container. Do not absorb in sawdust or other combustible absorbents. Mop up exposed area with bleach to destroy color. Wash away remainder with plenty of water. Collect wash water for approved disposal.

# 7. Handling and Storage

#### Precautions for Safe Handling

Hold and point signal away from body when igniting. Hold signal downwind when burning. Avoid breathing smoke. Avoid contact with clothing and other combustible materials. Use outdoors only! Do not ignite or burn product inside a vehicle, boat cabin or building. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Avoid contact with skin and eyes. Avoid contact with heat, sparks, and flame. Contains strong dyes which will color all exposed areas. Signals should be allowed to burn to completion. Unburned and partially burned signals should not be allowed to come into contact with surface and ground water.

#### Conditions for Safe Storage, Including Any Incompatibilities

Store in a dry place away from direct sunlight, heat and incompatible materials. Store away from food and beverages. Store away from flammable materials, sources of heat, flame and sparks. Store at ambient temperature. Do not store partially burned signals in a vehicle, boat, closed container, warehouse, or any other building.

### 8. Exposure Controls / Personal Protection

### **Control Parameters**

Sawdust (cellulose)

**Exposure Limits OSHA PEL ACGIH TLV** Solvent Yellow Dye no information found none Nuisance particulate, 15 mg/m<sup>3</sup> of total dust Nuisance particulate 10 mg/m<sup>3</sup> of total dust Lactose Potassium Chlorate No Airborne Exposure Limits established No Airborne Exposure Limits established Solvent Orange 7 Dye No information found No information found Strontium Carbonate 15 mg/m<sup>3</sup> 10 mg/m<sup>3</sup> Calcium Carbonate 15 mg/m<sup>3</sup> 10 mg/m<sup>3</sup> Charcoal Nuisance dust 15 mg/m<sup>3</sup>. Nuisance dust 15 mg/m<sup>3</sup>. Umber 30 mg/m<sup>3</sup> No information found Strontium Nitrate Not Established Not Established Shellac 1000 ppm 1000 ppm Potassium Nitrate Nuisance dust 15 mg/m<sup>3</sup>. Nuisance dust 15 mg/m<sup>3</sup>.

5 mg/m<sup>3</sup>



**Exposure Controls** 

Engineering Controls Use product outdoors only! When cleaning up contents, use local and/or general exhaust.

Eye / Face Protection Safety glasses or goggles

**Skin Protection** None under normal conditions when using product unless prolonged handling is anticipated. Contains strong dyes

which will color all exposed areas. When cleaning up spilled contents, wear full length impervious protective clothing, including gloves, boots, and a lab coat, apron or coveralls, as appropriate. Wash hands and face before eating,

drinking or using tobaccoproducts

Respiratory Protection None under normal conditions when using product. A particulate respirator (NIOSH t N95 or better filters)

may be worn during the cleanup of spilled contents.

Use product outdoors away from combustible products. For cleanup of spilled contents, emergency showers and eye wash stations should be available. Educate and train employees in the safe use and handling of hazardous materials.

Maintain good housekeeping and safety practices. Do not let contents accumulate in storage or work areas. Clean

spills up promptly.

### 9. Physical and Chemical Properties

General Hygiene

Appearance (color, physical form, shape): orange powder

**Melting Point:** No data available No data available Solubility: No data available pH: **Boiling Point / Range:** Freezing Point: Not applicable Not applicable **Evaporation Rate:** Not applicable Vapor Pressure: Not applicable Specific Gravity: Not applicable Vapor Density: Not applicable Odor: No data available Odor Threshold: No data available Flash Point: No data available Flammability Limits: Flammability: No data available No data available Relative Density: No data available

No data available

Partition Coefficient: No data available Viscosity:

Auto Ignition Temperature: >167°F Decomposition Temperature: No data available

# 10. Stability and Reactivity

Chemical Stability: Stable Reactivity: No information available Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to AvoidIncompatible MaterialsHazardous Decomposition ProductsExcessive temperatures,<br/>moisture, water, acids andStrong oxidizers, strong acids, oxidizing or reducing agents.<br/>Liquid acids of any kind. Hydrogen Fluoride, Ammonia Salts.Carbon monoxide, carbon dioxide,<br/>nitrogen oxides.

### 11. Toxicology Information

ignition sources.

Ingredient acute toxicity information

Oral LD50 Toxicology Skin LD50 LC50 Rat: 5000 mg/kg No information found Solvent Yellow Dye No information found Rat: 10000 mg/kg No information found No information found Lactose Potassium Chlorate Rat: 1870 mg/kg 2000 mg/kg (Rabbit) No information found Solvent Orange 7 Dye Rat: 5000 mg/kg No information found No information found Strontium Carbonate No information found No information found No information found Calcium Carbonate Rat 6450 mg/kg Rabbit 500 mg/kg No information found Charcoal Rat: > 15400 mg/kg Rabbit: 3 g/kg No information found No information found No information found No information found Umber Strontium Nitrate Rat: 2750 mg/kg No information found No information found Rat: 5000 mg/kg No information found No information found Shellac Potassium Nitrate Rat: 3750 mg/kg No information found No information found Rat: > 5000 mg/kg Rabbit: >2000 mg/kg Rat 758 mg/m<sup>3</sup> Sawdust (cellulose)

Product toxicological information

Acute Toxicity
Skin Irritation / Corrosion
Serious Eye Damage / Irritation

Respiratory / Skin Sensitization Category 1 Skin – over 0.1% of ingredients are classified as a Category 1 skin sensitizer

Germ Cell Mutagen
Carcinogen
Reproductive Toxicity
STOT – single exposure
STOT – repeated exposure

Aspiration Hazard Not classified (Based on available data, the classification criteria are not met)

Likely routes of exposure
Symptoms related to the physical,
chemical and toxicological characteristics
Skin, ingestion, inhalation
Irritation to the eyes will cause watering and redness. Reddening, scaling, and itching are
characteristics of skin inflammation. Ingestion of contents may cause gastrointestinal irritation with

nausea, vomiting and diarrhea. Inhalation will cause irritation to the lungs and mucus membrane.

Delayed and immediate effects and chronic

Both the solvent yellow and orange dyes may cause dermatitis in sensitive individuals.

effects from short and long term exposure
Interactive effects

Both the solvent yellow and orange dyes may cause dermatitis in sensitive individue of the solvent yellow and orange dyes may cause dermatitis in sensitive individue of the solvent yellow and orange dyes may cause dermatitis in sensitive individue of the solvent yellow and orange dyes may cause dermatitis in sensitive individue of the solvent yellow and orange dyes may cause dermatitis in sensitive individue of the solvent yellow and orange dyes may cause dermatitis in sensitive individue of the solvent yellow and orange dyes may cause dermatitis in sensitive individue of the solvent yellow and orange dyes may cause dermatitis in sensitive individue of the solvent yellow and orange dyes may cause dermatitis in sensitive individue of the solvent yellow and orange dyes may cause dermatitis in sensitive individue of the solvent yellow and orange dyes may cause dermatitis in sensitive individue of the solvent yellow and orange dyes may cause dermatitis in sensitive individue of the solvent yellow and orange dyes may cause dermatitis in sensitive individue of the solvent yellow and orange dyes may cause dermatitis in sensitive individue of the solvent yellow and orange dyes may cause dermatitis in sensitive individue of the solvent yellow and orange dyes may cause dermatitis in sensitive individue of the solvent yellow and orange dyes may cause dermatitis in sensitive individue of the solvent yellow and orange dyes may cause dermatitis in sensitive individue of the solvent yellow and orange dyes may cause dermatitis in sensitive individue orange dyes orange dyes orange



# 12. Ecological Information

Ingredient toxicity / persistence / degradability / bioaccumulation / mobility in soil and water

Strontium Nitrate: Acute toxicity - Fishes, Carassius auratus, LC100, 9,615 mg/l; Chronic toxicity - Fishes,

Gasterosteus aculeatus, LC100, 2.912 mg/l

Aquatic Toxicity

Potassium Chlorate: fish: LC50 oncorhynchus mykiss (rainbow trout) 1750 mg/l – 96 hr, EC50 daphnia

magna (water flea) 1093 mg/l 24 hr

Potassium Nitrate: fish: Guppy (Poecilia Reticulata) LC50 180 mg/L (96 h); zooplankton: Daphnia magna

LC50 490mg/l - 48hr

Persistence / Degradability Potas

Potassium Nitrate: Soluble in water Persistence is unlikely based on information available.

Bioaccumulation / Accumulation No information found

Strontium Nitrate: Water:: considerable solubility and mobility; Soil/sediments non-significant adsorption

Mobility in Environmental Media

Potassium Nitrate: Will likely be mobile in the environment due to its water solubility.

Other adverse effects No information found

### 13. Disposal Considerations (for spills and leakage)

Flares should be allowed to burn to completion. Dispose of partially burned flares, ash, spilled contents, contaminated product and materials used in cleaning up spills or leaks in the manner approved for pyrotechnic material in accordance with federal, state and local requirements. Open burning is preferred method of disposal for pyrotechnic materials.

### 14. Transportation Information

	ID Number	Proper Shipping Name	Hazard Class	Packing Group	EX Number	Reportable Quantities
Domestic & International	UN0373	Signal devices, hand	1.48	n/a	EX1997080126	none
Marine pollutant: no	)		Special preca	utions for user:	no information availa	able

#### 15. Regulatory Information

US Regulations	TS CA	CERCLA	CWA	CAA	SARA 313	SARA 302	Acute	Chronic	Fire	Reactivity	Pressure
Solvent Yellow Dve	yes	no	no	no	yes	no	yes	yes	no	no	no
Lactose	yes	no	no	no	no	no	no	no	no	no	no
Potassium Chlorate	yes	no	no	no	no	no	yes	no	no	yes	no
Solvent Orange 7 Dye	yes	no	no	no	yes	no	no	yes	no	no	no
Strontium Carbonate	yes				no	no	no	no	no	yes	no
Calcium Carbonate	yes	no			no		no	no	no	yes	no
Charcoal	yes	no	no	no	no	no	no	no	no	no	no
Umber	yes	no			yes		no	no	no	no	no
Strontium Nitrate	yes	no	no	no	no	no	yes	no	no	yes	no
Shellac	yes	no	no	no	no	no	no	no	no	no	no
Potassium Nitrate	yes	no	no	no	yes	no	no	no	no	yes	no
Sawdust (cellulose)	yes	no	no	no	no	no	no	no	no	no	no

US States	Prop 65	NJ	PA	Canada	WHMIS	DLS	Europe	Wgk
Solvent Yellow Dye	yes	0509	yes		D2A Very toxic materials D2B Toxic materials	yes		not listed
Lactose	no	no	no		Non controlled	yes		not listed
Potassium Chlorate	no	1560	yes		C Oxidizing materials D1B Toxic materials	yes		2
Solvent Orange 7 Dye	no	0506	yes		D2B Toxic materials	yes		3
Strontium Carbonate	no	no		yes	No information found			nwg
Calcium Carbonate	no		yes	yes	No information found			nwg
Charcoal	ves	yes	yes		D2A Very toxic materials	yes		nwg
	yos	yes	yos		D2B Toxic materials	yos		iiwg
Umber		yes	yes	yes	No information found			not listed
					C Oxidizing materials			
Strontium Nitrate	no	1743	no		D1B Toxic materials	yes		2
0. "		0044			D2B Toxic materials			
Shellac	no	0844	yes		No information found			not listed
Potassium Nitrate	no	1574	yes		C Oxidizing materials	yes		1
Sawdust (cellulose)	yes	no	no		No results	yes		not listed



#### 16. Other Information

Revision Information: March 2019

NFPA RatingHMIS RatingFlammability2Flammability1Health2Health3Reactivity1Physical Hazard1

Key / Legend

HMIS: hazardous material identification system NFPA: national fire protection association CAS: Chemical Abstracts Service number

EINECS: European inventory of existing chemical substances

OSHA PEL: occupational safety and health administration permissible exposure limit

NIOSH TLV: national institute of occupational safety

and health Threshold Limit Value NTP: National Toxicology Program

IARC: International Agency for Research on Cancer

CWA: clean water act - US

TSCA: toxic substance control act - US CERCLA: comprehensive environmental response

compensation and liability act – US CAA: clean air act - US

SARA: superfund amendments and reauthorization

act – US

PROP 65:California's Proposition 65 list WHMIS: workplace hazardous materials

information system - Canada

DSL: Domestic Substances List - Canada WGK: water hazard classes - Germany

#### **Legal Statement**

This information is accurate to the best knowledge of Orion Safety Products. Orion Safety Products makes no representations or warranties, either express or implied, including without limitation any warranties of merchantability or fitness for a particular purpose, with respect to the information set forth herein or the product to which the information refers. Accordingly, Orion Safety Products will not be responsible for damages resulting from use of or reliance upon this information. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation



# **Safety Data Sheet**

# **Orion Safety Signal Horn**

# Section 1. Identification

Product Identifier Orion Safety Signal Horn

Synonyms 507, 507R, 508, 508R, 509, 509R, 510, 510R

Manufacturer Stock N.

Numbers

N/A

Recommended use Personal Safety - Hand held signaling device. Prior to use, read all label

instuctions and warnings.

children. Intentional misuse by deliberately concentrating and/or inhaling contents

may be fatal.

Manufacturer Contact

Address

Falcon Safety Products, Inc.

25 ImClone Drive Branchburg, NJ, 08876

USA

Phone Emergency Phone Fax (908) 707-4900 (800) 498-7192 N/A

# Section 2. Hazards Identification

Classification FLAMMABLE AEROSOLS - Category 2

GASES UNDER PRESSURE - Compressed gas

Signal Word

Pictogram





Hazard Statements N/A

**Precautionary Statements** 

Response N/A

Prevention Do not spray on an open flame or other ignition source.

Keep away from heat.

Pressurized container: Do not pierce or burn, even after use.

Storage Do not store in enclosed vehicle.

Protect from sunlight. Store in a well-ventilated place.

Store at temperatures not exceeding 120 degrees F/49 degrees C

Disposal N/A

General Keep out of reach of children

Ingredients of unknown

toxicity

0%

Hazards not Otherwise

Classified

N/A

No Data Available

# Section 3. Ingredients

CAS	Ingredient Name	Weight %
75-37-6	Ethane, 1,1-difluoro-	100 %

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First-Aid Measures

General Advice Never give anything by mouth to an unconscious person. When symptoms

persist or in all cases of doubt, seek medical advice.

Inhalation Remove from exposure, lie down. Move to fresh air. Keep patient warm and at

rest. If not breathing, give artificial respiration. If breathing is difficult, give

oxygen. Get immediate medical attention.

Take off all contaminated clothing immediately. Flush area with lukewarm water. Skin

Do not use hot water. If frostbite has occurred, call a physician.

Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get Eye

medical attention.

Ingestion Is not considered a potential route of exposure.

Most important

delayed

Anaesthetic effects: light-headedness, irregular heartbeat with a strange symptoms/effects, acute and sensation in the chest, heart thumping, apprehension, feeling of fainting,

dizziness or weakness.

Protection of First-aiders If potential for exposure exists refer to Section 8 for specific personal protective

equipment.

Notes to Physician Because of possible disturbances of cardiac rhythm catecholamine drugs, such

as epinephrine, which may be used in situations of emergency life support,

should be used with special caution.

# Section 5. Fire Fighting Measures

Suitable Extinguishing

Media

Water spray, water fog, dry chemical, alcohol resistant foam, carbon dioxide

(CO2)

Unsuitable Extinguishing

Media

No applicable data available.

Specific Hazards

Flammable. This substance's fire decomposition by-products will include hydrofluoric acid and possibly carbonyl flouride. Avoid contact with these materials, which are toxic and irritating. Evacuate personnel immediately in the event of a fire involving this substance. Vapors may form explosive mixtures with air. Vapors are heavier than air and may spread along floors. Vapors or gases

may travel considerable distances to ignition source and flash back.

Special protective equipment for firefighters

**Further Information** 

Use personal protective equipment. Wear neoprene gloves during cleaning up work after a fire. Exposure to decompositon products may be a hazard to health. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Cool containers/tanks with water spray.

# Section 6. Accidental Release Measures

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections

before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE

EQUIPMENT during clean-up.

Evacuate personnel to safe areas. Ventilate the area. Refer to protective Safeguards (Personnel)

measures listed in sections 7 and 8.

If this product is spilled and not recovered, or is recovered as a waste for Spill Clean-up

> treatment and disposal, the CERCLA Reportable Quantity is 100 lbs. (release of an Unlisted Hazardous Waste with the Characteristic of Ignitability). Evaporates. Ventilate area using forced ventilation, especially low or enclosed places where

heavy vapors might collect.

Accidental Release Measures

Wear self-contained breathing apparatus (SCBA).

# Section 7. Handling and Storage

Handling (Personnel) Avoid breathing vapors or mist. Avoid contact with skin, eyes and clothing.

Provide sufficient air exchange and/or exhaust in work rooms. For personal protection see section 8. Handle in accordance with good industrial hygiene and

safety practice.

Handling (Physical Aspects) Vapors are heavier than air and may spread along floors. Vapors may form

flammable mixture with air. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropirate standard. No sparking tools should be used. Take measures to prevent the build up of electrostatic charge. Keep away from open flames, hot surfaces and sources of ignition. When using DO NOT SMOKE. Do not use in areas where vapors may accumulate such as

paper shredders.

**Dust Explosion class** 

Storage Period

Storage

Not applicable

Keep container tightly closed and in a dry, well-ventilated location. Store in

original container. The product has an indefinite shelf life when stored properly.

Recommended shelf life - 10 years provided product is stored in a dry location

as directed.

Storage Temperature Do not expose to temperatures above 120 degrees F (49 degrees C) as

overheating could cause can to burst. DO NOT leave in direct sunlight or

enclosed vehicle.

# Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Ethane, 1,1-difluoro-	N/A	N/A	N/A
Personal Protective Equipment	N/A			
Engineering controls	Ensure adequate ventilation, es protection if needed.	specially in confined	l areas. Use respira	tory
Eye/Face Protection	Wear safety glasses with side s frostbite.	shields. Direct conta	act with liquid may o	ause
Respiratory Protection	For rescue use self-contained to and can cause suffication by re			er than air
Skin and body protection	As required by employer code. clothing, gloves, etc. Direct con		· · · · · · · · · · · · · · · · · · ·	tective
General Hygiene Considerations	Handle in accordance with goo	d industrial hygiene	and safety practice	s.

# Section 9. Physical and Chemical Properties

Physical State	Gas
Color	Clear
Odor	slight, ether- like
Odor Threshold	No applicable data available
Solubility	Water - Slightly
Partition coefficient Water/n-octanol	N/A
VOC%	N/A
Viscosity	No applicable data available
Specific Gravity	0.91
Density lbs/Gal	0.9
Pounds per Cubic Foot	N/A
Flash Point	<-58°F (<-50°
	C)
FP Method	N/A
Ph	Neutral
Melting Point	No applicable data available
Boiling Point	-13 °F (-25 ° C)
Boiling Range	N/A
LEL	3.9
UEL	16.9
Evaporation Rate	No applicable data available
Flammability	Flammable
Decomposition Temperature	N/A
Auto-ignition Temperature	No applicable data available
Vapor Pressure	5,960 KPa at 77F (25C)
Vapor Density	2.4 at 77F (25C) (Air=1)

# Section 10. Stability and Reactivity

Reactivity Stable under recommended storage conditions.

Chemical Stability The product is chemically stable under recommended storage conditions.

Conditions to Avoid Aerosol containers are unstable at temperatures above 120 degrees F/49

degrees C

Incompatible Materials Incompatible products include Alkali metals, Alkaline earth metals, powdered

metals, powdered metal salts.

Hazardous Decomposition

Products

Decomposition products are hazardous. This material can be decomposed by high temperatures (open flames, glowing metal surfaces, etc.) forming

hydrofluoric acid and possibly carbonyl fluoride.

# Section 11. Toxicological Information

Component Analysis - LC50 1,1-Difluoroethane - > 64000 ppm rat Component analysis - Oral 1,1-Difluoroethane - 1500 mg/kg rat

LD50

Effects of Acute Exposure - Contact with liquid may cause frostbite

Eye

Effects of Acute Exposure - Contact with liquid may cause frostbite

Skin

Effects of Acute Exposure - Excessive intentional inhalation may cause respiratory tract irritation and central

nervous system effect (headaches, dizziness). Vapors may cause dizziness or

suffocation.

Effects of Acute Exposure -

Ingestion

Inhalation

Not a normal route of exposure

Sensitization Non-hazardous by WHMIS/OSHA criteria.

Carcinogenicity Not classifiable as a human carcinogen. Animal testing did not show

carcinogenic effects. None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA

as a carcinogen.

Mutagenicity Animal testing did not show any mutagenic effects. Did not cause genetic

damage in cultured bacterial cells. Tests on mammalian cell cultures showed

mutagenic effects.

Reproductive Toxicity No toxicity to reproduction. Animal testing showed no reproductive toxicity.

Teratogenicity Animal testing showed no developmental toxicity.

Further Information Cardiac sensitization threshold limit: 405000 mg/m3

# Section 12. Ecological Information

Aquatic Toxicity 1,1-Difluoroethane 96 h LC50 : Fish 295.78 mg/l 96 h EC50 : Algae 47.76 mg/l

48 h EC50: Daphnia (water flea) 146.7 mg/l

# Section 13. Disposal

Waste Disposal Methods Comply with applicable Federal, State/Provincial and Local Regulations. May be

a RCRA Hazardous waste due to the ignitability characteristic. Do not puncture

or incinerate container.

Contaminated Packaging Not Available

# Section 14. Transport Information

**UN Number** 1030

**UN Proper Shipping Name** 1.1-Difluoroethane

**DOT Classification** 2.1 Packing Group

**Packaging Exceptions** Note: Falcon Safety Products has been granted a DOT special permit. A copy of

DOT Special Permit SP-11516 can be obtained by calling Falcon Safety

Products, Inc. at 908-707-4900.

Goods (TDG - Canada)

Transportation of Dangerous Proper Shipping name: 1,1-Difluoroethane Hazard Class: 2.1 UN number: 1030

Packaging Exceptions: Limited quantity (containers up to 125mL)

Proper Shipping Name: 1.1-Difuoroethane, Hazard Class: 2.1, UN Number: IATA/ICAO (Air)

> 1030. Maximum Net Quantity Packaging: Cargo Aircraft only - 150 kg maximum (forbidden on passenger aircraft). Maximum Net Quantity packaging cargo only:

150 kg.

Proper Shipping Name: 1,1-DIFLUOROETHANE. Hazard Class: 2.1. UN IMDG (Marine Transport)

Number: 1030.

**Additional Information** TDG Canada: Falcon Safety Products has been granted Equivalency Certificate

SU 9211 (ren. 1) by the TCSS, TDGD to offer for transport by road, rail and

# Section 15. Regulatory Information

This product has been classified in accordance with the hazard criteria of the Canadian Federal Regulations

Controlled Products Regulations and the SDS contains all the information

required by the Controlled Products Regulations.

WHMIS Status

WHMIS Classification Class A - Compressed Gas, Class B - Division 1 - Flammable Gas

**TSCA** On the inventory, or in compliance with the inventory.

SARA 313 Regulated This material does not contain any chemical components with known CAS Chemical(s)

numbers that exceed the threshold (De Minimis) reporting levels established by

SARA Title III, Section 313.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard **US Federal Regulations** 

Communication Standard, 29 CFR 1910.1200.

Chemical(s)

NJ Right to Know Regulated Substances on the New Jersey Workplace Hazardous Substance List present at a concentration of 1% or more (0.1% for substances identified as carcinogens,

mutagens or teratogens): 1,1-Difluoroethane.

This product does not contain a chemical known to the State of California to California Prop. 65

cause cancer, birth defects or other reproductive harm.

Canada Domestic

This product is listed on the DSL inventory list and complies with the inventory

Substances List (DSL) requirements administered by the governing country.

# Section 16. Other Information

Revision Date 2/17/2017

Disclaimer Information contained herein was obtained from sources considered technically

accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any

information contained in this document.

Prepared By Falcon Safety Products, Inc. 908-707-4900