

SAFETY DATA SHEET

EFFECTIVE DATE: 01/31/2017

ITEM: Kayak Aerial Kit

PART# UPC

769 077403107698

CONTENTS:

Skyblazer XLT / SAR Red Aerial Signal SDS

SHIPPING INFORMATION

Flares, Aerial 1.4G,UN0403,PGII (ERG 114) EX2002110107



SAFETY DATA SHEET

Product and Company Identification

Skyblazer II, XLT and XLT, Twin

SAR Red Aerial Signal

Orion Safety Products 3157 North 500 West Peru. IN 46970

Emergency signal

Phone Number: US 1-800-851-5260 Intl (11) 1-765-472-4375

EMERGENCY CHEMTREC 1-800-424-9300

Hazards Identification

Emergency Overview







GHS Classifications

Explosive Division 1.4 Acute Toxicity Category 5 Skin Corrosion / Irritation Product- Category 1A Contents - Category 2 Serious Eye Damage / Irritation Product-Category 1 Contents - Category 2B

Hazard Statements:

Precautionary Statements:	Reactivity	
Harmful if inhaled or swallowed	Health	
Causes severe skin burns and eye damage (product when burning) Causes skin and eye irritation (contents)	Flammability	
Fire or projection hazard		

Keep out of reach of children.

Keep away from heat/sparks/open flames/hot surfaces. - no smoking. **HMIS Rating** Keep/Store away from combustible materials

Keep cool. Do not expose long term to temperatures exceeding 167°F Flammability Avoid breathing dust/smoke Use only outdoors. Do not ignite inside a building, vehicle or boat cabin. Wear eye protection.

Physical Hazard In case of fire; use water deluge. Do not use dry powder or foam extinguishers

3 Health

NFPA Rating

3. Composition / Information	on on Ingredients		
Component	CAS#	EINCS#	%age
Strontium Nitrate	10042-76-9	233-131-9	<50%
Magnesium	7439-95-4	231-104-6	<50%
Strontium Peroxide	1314-18-7	215-224-6	<50%
Polyvinyl chloride	9002-86-2	none	<20%
Black Powder	mixture	mixture	<20%
Dextrin	9004-53-9	232-675-4	<20%
Primer	n/a	n/a	n/a

First Aid Measures

Eyes

If smoke or contents are inhaled, remove to fresh air. If not breathing, give artificial respiration and get medical aid. Inhalation

For burns, cool with water and bandage appropriately. If contents are contacted, wash with area with soap and water for 15 Skin

minutes. Remove contaminated clothing and wash before reuse. Get medical aid if burned or irritation occurs.

If burned, cover eye and get medical help immediately. If smoke or contents get into eye, flush with plenty of water for at least

15 minutes, occasionally lifting the up and lower lids. Remove contact lenses if easily possible Get medical aid immediately.

Get medical aid immediately. Ingestion

Firefighting Measures

Extinguishing Media Water Deluge

Unsuitable Extinguishing Media

Foam and dry chemical extinguishers and suffocation are ineffective

Protective Equipment and Precautions for Firefighters Wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode. Prevent further propagation of fire by spraying unburnt nearby product with water. Combat fire from a sheltered position.

Specific Hazards Arising from the Chemical Only use outdoors. Use copious amounts of water to extinguish fire. Using small quantities of water on contents / broken product can cause auto / re-ignition as contents contain magnesium. Use of water on a magnesium fire will generate hydrogen gas that may cause an explosion. Irritating fumes. Flaming projectiles may be ejected during a fire. Trace amounts of lead vapor may be produced (from ignition primer) in a fire situation.

Flashpoint Flammability Limits **Ignition Temperature** >180F Not Applicable Not Applicable

Accidental Release Measures 6.

Personal Precautions

Environmental Precautions Prevent dispersion of contents on soil and in water. Prevent contents from spreading or entering into drains, ditches, groundwater or rivers by using appropriate barriers.

Do not breathe smoke or contents and avoid contact with skin and eyes. Wear flame retardant clothing with long sleeves, dust mask, rubber or nitrile gloves, safety goggles, safety shoes when cleaning up contents. Avoid friction on the released product. Keep away from ignition sources. Contains strong dyes which will color all exposed areas.



Methods for Containment and Clean-up

Use caution when cleaning up spilled product contents. Remove heat, flames, sparks and other sources of ignition. Use non-sparking tools and equipment. Prevent buildup of electrostatic charges by grounding. Clean spills in a manner that does not disperse dust into the air. Do not absorb in sawdust or other combustible absorbents. Pick up spill for recovery or disposal and place in an approved container. Wash away remainder with plenty of water. Collect wash water for approved disposal. Be very careful - magnesium powder may spontaneously ignite in presence of moisture. Magnesium powder reacts with water, producing flammable hydrogen gas.

7. Handling and Storage

Handling

Point product away from body, other people, animals or combustible products when firing. Wear appropriate eye protection when using. Follow instructions on package! Do not disassemble signal. Avoid contact with clothing and other combustible materials. Use outdoors only. Do not remove bottom cap unless you are outdoors and preparing to activate signal. Do not ignite or launch product inside a vehicle, boat cabin, or building. Avoid ingestion and inhalation of smoke and contents. Wash thoroughly after handling. Avoid contact with heat sparks, and flame.

Storage

Store in a cool area out of direct sunlight. Do not allow long-term exposure to temperatures in excess of 180°F. Avoid long-term immersion in water, exposure to moisture, open flames or extremely high temperature. Store away from flammable materials, sources of heat, flame and sparks. Do not store partially burned signals in a vehicle, boat, closed container, warehouse, or any other building.

8. Exposure Controls / Personal Protection			
Exposure Limits	OSHA PEL	ACGIH TLV	
Strontium Nitrate	Not Established	Not Established	
Magnesium	unknown	unknown	
Strontium Peroxide	nuisance dust 15 mg/m³.	nuisance dust 15 mg/m³.	
Polyvinyl chloride	5mg/ml for the respirable portion and 15mg/ml' for total dust.	5 and 10mg/ml, respectively	
Black Powder	Not established	Not established	
Dextrin	15 mg/m³ total dust	10 mg/m³	

Engineering Controls Eye / Face Protection Skin Protection

Use product outdoors only! When cleaning up contents, use local and/or general exhaust.

Turn face from product when firing. Wear safety glasses or goggles during use and when cleaning up spilled contents. None under normal conditions when using product unless prolonged handling is anticipated. Contains strong dyes which will color all exposed areas. When cleaning up spilled contents, wear full length impervious protective clothing, including gloves, boots, and a lab coat, apron or coveralls, as appropriate. Wash hands and face before eating, drinking or using tobacco

products.

Respiratory Protection

None under normal conditions when using product. A particulate respirator (NIOSH t N95 or better filters) may be worn during

the cleanup of spilled contents.

General Hygiene

Use product outdoors away from combustible products. For cleanup of spilled contents, emergency showers and eye wash stations should be available. Educate and train employees in the safe use and handling of hazardous materials. Maintain good housekeeping and safety practices. Do not let contents accumulate in storage or work areas. Clean spills up promptly.

Physical and Chemical Properties

Appearance (color, physical form, shape): Orange plastic tube.

pH: Not available **Melting Point:** >500°F Solubility: Slight Not applicable Not applicable Freezing Point: **Evaporation Rate:** Not applicable

Boiling Point Vapor Pressure: Not applicable **Specific Gravity** Not applicable Vapor Density: Not applicable

Stability and Reactivity

Chemical Stability

Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

Conditions to Avoid

Excessive temperatures, moisture, water, acids,. Exposure of the signal to temperatures in excess of 180°F may cause weakening of the signal body. Avoid open flames, extremely high temperatures, wet conditions, and ignition sources

Incompatible Materials

Strong oxidizers, strong acids, oxidizing or reducing agents. Liquid acids of any kind. Hydrogen Fluoride, Avoid exposure to organic solvents which might weaken the signal body.

Hazardous Decomposition Products

Carbon monoxide, Nitrous oxides, Carbon dioxide. Magnesium hydroxides and oxides

11. Toxicology Informatio	n		
Toxicology	Oral LD50	skin LD50	LC50
Strontium Nitrate	Rat 2750 mg/kg	Not Established	Not Established
Magnesium	Not Established	Not Established	Not Established
Strontium Peroxide	Not Established	Not Established	Not Established
Polyvinyl chloride	Not Established	Not Established	Not Established
Black Powder	Not Established	Not Established	Not Established
Dextrin	Not Established	Not Established	Not Established



Acute Dose Effects

Burning signal can cause severe burns if in contact with body - product burns at an extremely high temperature. Particles from firing may be harmful if inhaled. Contact with contents may cause moderate skin and eye irritation. Inhalation of smoke or contents will cause irritation to the lungs and mucus membrane. Exposure to smoke during use may aggravate asthma if inhaled.

Irritation Irritating to the skin and eyes on contact. Inhalation will

cause irritation to the lungs and mucus membrane.

Carcinogenicity No information found

Genetic Effects No information found

Developmental **Effects**

Target Organ Effects Eye, skin, and lungs

Repeated Dose Effects No known chronic effects. Repeated or prolong exposure to this compound is not known to aggravate medical conditions.

> Corrosivity May cause eye or skin burns if in

contact with burning signal.

Reproductive Effects No information found

Neurological Effects No information found

> Sensitization No information found

12. **Ecological Information**

Aquatic Toxicity

No information found

Persistence / Degradability No information found

Bioaccumulation / Accumulation No information found Mobility in Environmental Media No information found

Strontium Nitrate: Acute toxicity - Fishes, Carassius auratus, LC100, 9,615 mg/l; Chronic toxicity - Fishes, Gasterosteus aculeatus, LC100, 2.912 mg/l

Disposal Considerations (for spills and leakage)

Dispose of contaminated product and materials used in cleaning up spills or leaks in the manner approved for pyrotechnic material. Consult appropriate federal, state, and local regulatory agencies to ascertain proper disposal procedures. Open burning is preferred method of disposal for pyrotechnic materials..

14. Transportation Information						
shipping name hazard class ID Number packing group EX Number Reportable Quanti				Reportable Quantities		
United States & International	Flares, aerial	1.4G	UN0403	II	XLT & SAR -EX2002110107 TWIN -EX2002110148	none

15. Regulatory Information SARA SARA **US Regulations TSCA CERCLA CWA** CAA Acute Chronic Fire Reactivity Pressure 313 302 Strontium Nitrate yes no Magnesium no no no no no yes no no no no no Strontium Peroxide no no no no no not state not state not state not state not state yes Polyvinyl chloride no no no no no no yes no no Black Powder mixture Dextrin ves no no no no no no no no

US States	Prop 65	NJ	PA
Strontium Nitrate	no	1743	no
Magnesium	no	1136	yes
Strontium Peroxide	no	1745	no
Polyvinyl chloride	no	3622	no
Black Powder	mixture	mixture	mixture
Dextrin	no	no	no

oai	iaua	

WHMIS	DSL
No results	yes
mixture	mixture
No results	yes

Europe	
--------	--

wgk
2
nwg
not listed
not listed
mixture
1

Other Information

Revision Information: October 2016

Risk and Safety Phrases:

R10 Flammable R38 Irritating to skin (contents)

R20 Harmful by inhalation. R21 Harmful in contact with skin R22 Harmful if swallowed.

R34 Causes burns R36 Irritating to eyes

R37 Irritating to respiratory system. S17 Keep away from combustible material

S16 Keep away from sources of ignition S2 Keep out of the reach of children

S8 Keep container dry. S13 Keep away from food, drink and animal S24 Avoid contact with skin

S25 Avoid contact with eyes. S29 Do not empty into drains.

S41, In case of fire and / or explosion do not breathe fumes S43 In case of fire use water

S51 Use only in well ventilated areas S39 Wear eye / face protection.

Key / Legend:

HMIS: hazardous material identification system NFPA: national fire protection association CAS: Chemical Abstracts Service number EINECS: European inventory of existing chemical substances

OSHA PEL: occupational safety and health administration permissible exposure limit NIOSH TLV: national institute of occupational safety

and health Threshold Limit Value NTP: National Toxicology Program

IARC: International Agency for Research on Cancer

TSCA: toxic substance control act - US CERCLA: comprehensive environmental response.

compensation and liability act - US

CWA: clean water act - US CAA: clean air act - US

SARA: superfund amendments and reauthorization

act - US PROP 65:California's Proposition 65 list WHMIS: workplace hazardous materials

information system - Canada DSL: Domestic Substances List - Canada WGK: water hazard classes - Germany

Legal Statement:

This information is accurate to the best knowledge Orion Safety Products. Orion Safety Products makes no representations or warranties, either express or implied, including without limitation any warranties of merchantability or filness for a particular purpose, with respect to the information set forth herein or the product to which the information refers. Accordingly, Orion Safety Products will not be responsible for damages resulting from use of or reliance upon this information. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.