

SAFETY DATA SHEET

Effective Date: SEPTEMBER 2025

ITEM: Boat Trailer Roadside Safety kit

PART # 8960 **UPC** 039147089609

Contents
SDS for each of the following:
Red Emergency Flares

SHIPPING INFORMATION

UN3178, Flammable solid, inorganic, n.o.s., 4.1, PG II Allowed to ship as Limited Quantity according to Exceptions for Class 4 stated in 49CFR 173.151



SAFETY DATA SHEET

1. Product and Company Identification

Red Emergency Flare – No Perchlorate (NPC) Identification: The NPC Flare will have the following symbol on it.

Formulation

Synonyms: Emergency Road Flare, Railway Flare

NSN#: 1370-01-009-2593

Identified Use: Emergency signal Use Advised Against: Do not use indoors or inside of a vehicle.

Manufacturer's Information: Orion Safety Products

 3157 N 500 W
 EMERGENCY
 CHEMTREC

 Peru, Indiana 46970
 RESPONSE
 1-800-424-9300

 US 1-800-851-5260
 1-703-527-3887

Int'l (11) 1-765-472-4375

2. Hazards Identification

GHS Classifications

Explosive
Skin Irritation
Explosive
Skin Irritation
Category 2
Eye Irritation
STOT-Single Exposure
Category 3

GHS Label Elements

Hazard Statements

H204 Fire or projection hazard
 H315 Causes skin irritation
 H319 Causes serious eye irritation
 H335 May cause respiratory irritation

Pictograms





Signal Word Warning

Precautionary Statements

P102	Keep out of reach of children.	P301/315	IF SWALLOWED: Get immediate medical advice /attention.
P103	Read carefully and follow all instructions.	P302/352	IF ON SKIN: Wash with plenty of soap and water.
P210	Keep away from heat, sparks, open flames, hot surfaces.	P304/340/342	IF INHALED: Remove victim to fresh air and keep at rest in a
P261	Avoid breathing dust/fumes.		comfortable for breathing. If experiencing respiratory symptoms: Call
P264	Wash hands thoroughly after handling.		POISON CENTER or doctor/physician.
P270	Do not eat, drink or smoke when using this product.	P305/338/351	IF IN EYES: Rinse cautiously with water for several minutes. Remove
P271	Use only outdoors.		contact lenses, if present and easy to do. Continue rinsing.
P280	Wear protective eye protection.	P332/313	If skin irritation or rash occurs, get medical advice/attention.
P370	In case of fire use water deluge.	P501	Dispose of contents / container in accordance with local and national

Hazards Not Otherwise Classified (HNOC): produces hot flame

3. Composition/Information on Ingredients

Component	CAS#	EINCS #	Percentage
Strontium Nitrate	10042-76-9	233-131-6	<75%
Sulfur	7704-34-9	231-722-6	<25%
Potassium Nitrate	7757-79-1	231-818-8	<25%
Paraffinic Oil	64742-54-7	232-384-2	<10%
Potassium Chlorate	3811-04-9	231-100-4	<5%
Sawdust (cellulose)	9004-34-6	232-674-9	<5%
Polyvinyl Chloride	9002-86-2	200-831-0	<5%
Charcoal	1333-86-4	231-153-3	<1%

Note: Due to Confidential Business Information, "Trade Secrets", the exact percentage of each ingredient has not been disclosed. CBI information will be shared with appropriate authorities if circumstances warrant.

4. First Aid Measures

Description of first aid measures

Inhalation If contents are inhaled, remove to fresh air. Watch for signs of allergic reaction. If other symptoms develop, get medical aid immediately.

Skin If contents are contacted, wash with area with soap and water for 15 minutes. Remove contaminated clothing and wash before reuse. Get medical aid if irritation occurs.

Eyes If contents get into eyes, flush with plenty of water for at least 15 minutes, occasionally lifting the upper and lower lids. Remove contact lenses if easily possible. Get medical aid immediately.

Ingestion Get medical aid immediately

1



Most important symptoms and effects both acute and delayed

Indication of any immediate medical attention and special treatment needed

See section 2 labeling and section 11
Burning flare can cause severe burns if in contact with body. For burns to skin, cool with water and bandage appropriately. Seek medical attention. If eye is burned, cover eye and get medical aid immediately.

5. Firefighting Measures

Extinguishing Media

Water deluge

Unsuitable Extinguishing Media

Foam and dry chemical extinguishers and suffocation are ineffective.

Wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated

Protective Equipment and
Precautions for Firefighters
Wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operate
in the pressure demand or other positive pressure mode. Prevent further propagation of fire by spraying unburnt
nearby product with water. Combat fire from a sheltered position. Use copious amounts of water to extinguish

nearby product with water. Combat fire from a sheltered position. Use copious amounts of water to extinguish fire comprised of flares. Flares contain oxidizers and will continue to burn unless a significant amount of water

is used. Do not breathe smoke.

Specific Hazards Arising Only use outdoors. Flame and sparks are ejected out the open end of the flare when it functions. Do not point flare at any

from the Chemical part of the body or flammable material.

Further Information No data available

6. Accidental Release Measures

Personal Precautions / Protective Equipment / Emergency Procedures

Do not breathe smoke or contents. Avoid contact with skin and eyes. Wear flame retardant clothing with long sleeves, dust mask, rubber or nitrile gloves, safety goggles, safety shoes when cleaning up contents. Avoid friction on the released product. Keep away from ignition sources.

Environmental Precautions

Prevent dispersion of contents on soil and in water. Prevent contents from spreading or entering into drains, ditches, groundwater or rivers by using appropriate barriers.

Methods for Containment and Clean-up

Use caution when cleaning up spilled contents. Remove heat, flames, sparks and other sources of ignition. Use non-sparking tools and equipment. Prevent buildup of electrostatic charges by grounding. Clean spills in a manner that does not disperse dust into the air. Do not absorb in sawdust or other combustible absorbents. Pick up spill for recovery or disposal and place in an approved container. Wash away remainder with plenty of water. Collect wash water for approved disposal.

7. Handling and Storage

Precautions for Safe Handling

Hold and point flare away from body when igniting. Exercise caution when using the product since molten flecks may be emitted. Produces hot flame. Burning flare can cause severe burns if in contact with body. Avoid contact with clothing and other combustible materials. Wear eye protection during use. Follow instructions on package. Use outdoors only! Do no ignite or bun product inside a vehicle or building. Avoid inhalation of smoke. Do not dismantle. Do not allow contents to touch eyes, skin or clothing. Do not ingest contents as they may be harmful if swallowed. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Avoid contact with heat, sparks, and flame.

Conditions for Safe Storage, Including Any Incompatibilities

Store in a dry place away from direct sunlight, heat and incompatible materials. See section 10. Store away from food and beverages. Store away from food and beverages. Store away from flammable materials, sources of heat, flame and sparks. Store at ambient temperature. Do not store partially burned signals in a vehicle, warehouse, or any other building. Plastic bags are provided for moisture protection. Keep partially used bags sealed at all times.

8. Exposure Controls / Personal Protection

Control Parameters

ACGIH TLV Exposure Limits OSHA PEL Strontium Nitrate Not established Not established Sulfur Not established Not established Potassium Nitrate Nuisance dust. 15 mg/m3 Nuisance dust. 15 mg/m3 Paraffinic Oil 5 mg/m³ 5 mg/m³ TWA Potassium Chlorate No Airborne Exposure Limits established No Airborne Exposure Limits established 10 mg/m³ Sawdust (cellulose) 5 mg/m³ No known hazardous components above No known hazardous components above Polyvinyl Chloride regulatory thresholds in this product. regulatory thresholds in this product.

Exposure Controls

Charcoal

Engineering Controls Use product outdoors only! When cleaning up contents, use local and/or general exhaust.

Nuisance dust, 15 mg/m³

Eye / Face Protection Safety glasses or goggles
Skin Protection None under normal condition

 None under normal conditions when using product unless prolonged handling is anticipated. Impervious protective clothing, including gloves, boots, and a lab coat, apron or coveralls, as appropriate, when cleaning up spilled product.

Nuisance dust, 15 mg/m³

Wash hands and face before eating, drinking or using tobaccoproducts

Respiratory Protection None under normal conditions when using product. A particulate respirator (NIOSH t N95 or better filters)

may be worn during the cleanup of spilled contents.

General Hygiene Use product outdoors away from combustible products. For cleanup of spilled contents, emergency showers and eye

wash stations should be available. Educate and train employees in the safe use and handling of hazardous materials. Maintain good housekeeping and safety practices. Do not let contents accumulate in storage or work areas. Clean

spills up promptly.



9. Physical and Chemical Properties

Appearance (color, physical form, shape):

pH: No data available Melting Point: No data available Solubility: No data available Boiling Point / Range: Not applicable Freezing Point: Not applicable Evaporation Rate: Not applicable Vapor Pressure: Not applicable Specific Gravity: Not applicable Vapor Density: Not applicable Odor. No data available Odor Threshold: No data available Flash Point: No data available Flammability: No data available Flammability Limits: No data available Relative Density: No data available

Partition Coefficient: No data available Viscosity: No data available

Auto Ignition Temperature: No data available **Decomposition Temperature:** No data available

10. Stability and Reactivity

Chemical Stability: Stable Reactivity: No information available Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Incompatible Materials Hazardous Decomposition Products Conditions to Avoid Combustible materials, heat, Strong acids, strong fuels, ammonia salts and strong bases. Carbon monoxide, carbon dioxide, sulfur flames, sparks and other Strong oxidizers; chlorate salts. oxides and nitrogen oxides. sources of ignition. Moisture.

11. Toxicology Information

Ingredient acute toxicity information Oral LD50 Skin LD50

Toxicology LC50 Strontium Nitrate Rat: 2750 mg/kg No information found No information found Sulfur Rat:>2000 mg/kg Rat:>2000 mg/kg Rat: 79.23 mg/L 4hr Potassium Nitrate Rat: 3750 mg/kg No information found No information found Rat: >2000 mg/kg Paraffinic Oil Rat: >2000 mg/kg No information found Rat: 1870 mg/kg Potassium Chlorate Rabbit: >2000 mg/kg No information found Sawdust (cellulose) Rat: > 5000 mg/kg Rabbit: >2000 mg/kg Rat 758 mg/m³

Rat: > 5000 mg/kg Polyvinyl Chloride no known hazardous components above no known hazardous components above regulatory thresholds in this product regulatory thresholds in this product

Charcoal No information found Rat: > 15400 mg/kg Rabbit: 3 g/kg

Product toxicological

information

Acute Toxicity Not classified - Acute Toxicity Estimate yields oral LD50 over 5000 mg/kg bw Skin Irritation / Corrosion Category 2 – over 10% of ingredients classified as a Category 2 skin irritant Serious Eye Damage / Irritation Category 2A - over 10% of ingredients classified as a Category 2A eye irritant Respiratory / Skin Sensitization Not classified (Based on available data, the classification criteria are not met) Germ Cell Mutagen Not classified (Based on available data, the classification criteria are not met) Carcinogen Not classified (Based on available data, the classification criteria are not met)

Reproductive Toxicity Not classified (Based on available data, the classification criteria are not met) STOT - single exposure Category 3 - respiratory-over 10% of ingredients classified as a Category 3 respiratory STOT hazard

STOT - repeated exposure Not classified (Based on available data, the classification criteria are not met)

Aspiration Hazard Not classified (Based on available data, the classification criteria are not met) Likely routes of exposure Skin, ingestion, inhalation

Symptoms related to the Contents irritating to eyes due to chemical and physical properties of the mixture. Ingestion of contents may cause physical, chemical and gastrointestinal irritation with nausea, vomiting and diarrhea. Individuals with known allergies to sulfide drugs may also have toxicological characteristics allergic reactions to elemental sulfur. Delayed and immediate effects

Inhalation of contents or smoke from burning flare will cause irritation to the lungs and mucus membrane. Prolonged or and chronic effects from short repeated skin contact with contents may cause dermatitis. and long term exposure

Interactive effects No information found

12. Ecological Information

Ingredient toxicity / persistence / degradability / bioaccumulation / mobility in soil and water

Strontium Nitrate: Acute toxicity - Fishes, Carassius auratus, LC100, 9,615 mg/l; Chronic toxicity - Fishes, **Aquatic Toxicity**

Gasterosteus aculeatus, LC100, 2.912 mg/l

Sulfur: Toxicity to fish LC50 - Oncorhynchus mykiss (rainbow trout) - > 180 mg/l - 96 h Toxicity to daphnia

and other aquatic invertebrates: EC50 - Daphnia magna (Water flea) - > 5,000 mg/l - 48 h

Potassium Chlorate: fish: LC50 oncorhynchus mykiss (rainbow trout) 1750 mg/l – 96 hr, EC50 daphnia

magna (water flea) 1093 mg/l 24 hr

Paraffinic Oil: Oil Mist, Mineral Lepomis macrochirus (LC50) 96 hour(s) >100 mg/l Oncorhynchus mykiss

(LC50) 96 hour(s) >100 mg/l

Potassium Nitrate: fish: Guppy (Poecilia Reticulata) LC50 180 mg/L (96 h); zooplankton: Daphnia magna

LC50 490mg/I - 48hr

Potassium Nitrate: Soluble in water Persistence is unlikely based on information available. Persistence / Degradability

Bioaccumulation / Accumulation No information found

Strontium Nitrate: Water: considerable solubility and mobility; Soil/sediments non-significant adsorption Mobility in Environmental Media

Potassium Nitrate: Will likely be mobile in the environment due to its water solubility.

Other adverse effects No information found



13. Disposal Considerations (for spills and leakage)

Disposal methods

Flares should be allowed to burn to completion. Partially burned or unburned flares, spilled contents, and ash from burned flares should be disposed of in accordance with federal, state, and local requirements. Consult factory for any additional disposal concerns.

14. Transportation Information

Packaging Description	ID Number	Proper Shipping Name	Hazard Class	PG	EX Number	Reportable Quantities	Comments		
Competent Authority Approval / Classification Reference #EX1992090001									
Inner Packaging (bag)	UN0373	Signal devices, hand	1.4S	n/a	EX1992090001	none	Allowed by Passenger Aircraft, Ground, Vessel		
Allowed for Domestic Shipments / Noted on Original classification shown above									
No Inner Package Required	NA1325	Fusee	4.1	II	n/a	none	Allowed for Domestic shipments only		
Allowed when package	ed as specifie	d on Approval / Reference	ce #EX2002110	<u>114)</u>					
*Specific on Approval	**UN3178	Flammable solid, inorganic, n.o.s.	4.1	II	EX2002110114	none	*Up to 4 fusees per inner package, up to 144 fusees per outer package.		

^{**}According to 49CFR, Exceptions for Class 4, Limited Quantities of flares properly packaged and classed as UN3178, Flammable solid, inorganic, n.o.s. are excepted from several requirements unless offered for transport by air or until Dec. 31st 2020, they may be renamed "Consumer Commodity" and reclassed as ORM-D and offered for transport in accordance with the applicable provisions of that subchapter.

Marine Pollutant: no

Special precautions for user: No information available.

15. Regulatory Information

US Regulations	TS CA	CERCLA	CWA	CAA	SARA 313	SARA 302	Acute	Chronic	Fire	Reactivity	Pressure
Strontium Nitrate	yes	no	no	no	no	no	yes	no	no	yes	no
Sulfur	yes	no	no	no	no	no	yes	no	yes	no	no
Potassium Nitrate	yes	no	no	no	yes	no	no	no	no	yes	no
Paraffinic Oil	yes	no	no	no	no	no	no	no	no	no	no
Potassium Chlorate	yes	no	no	no	no	no	yes	no	no	yes	no
Sawdust (cellulose)	yes	no	no	no	no	no	no	no	no	no	no
Polyvinyl Chloride	yes	no	no	no	no	no	yes	no	no	no	no
Charcoal	yes	no	no	no	no	no	no	no	no	no	no
US States	Pro	p 65 NJ	PA	Can	ıada	WH	MIS	DLS	6	Europe	Wgk
Strontium Nitrate	r	io 1743	no no		C Oxidizing materials D1B Toxic materials D2B Toxic materials		yes	i	·	2	
Sulfur	r	1757	yes			B4 Flamm D2B Toxio	nable solid materials	yes	i		1 / nwg
Potassium Nitrate	r	io 1574	yes			C Oxidizing	g materials	yes	i		1
Paraffinic Oil	r	io 1437	no			No re	esults	yes	i		not listed
Potassium Chlorate	y	es 1560	yes			C Oxidizino D1B Toxid	g materials c materials	yes	i		2
Sawdust (cellulose)	y	es no	no			No re	esults	yes	i		not listed
Polyvinyl Chloride	r	io 3622	no no			No re	esults	yes	i		not listed
Charcoal	y	es yes	yes			D2A Very To D2B Toxio	oxic materials c materials	yes	i		Nwg



16. Other Information

Revision Information: March 2019

NFPA RatingHMIS RatingFlammability1Flammability1Health2Health2Reactivity1Physical Hazard1

Key / Legend

HMIS: hazardous material identification system NFPA: national fire protection association CAS: Chemical Abstracts Service number

EINECS: European inventory of existing chemical substances

OSHA PEL: occupational safety and health administration permissible exposure limit

NIOSH TLV: national institute of occupational safety

and health Threshold Limit Value NTP: National Toxicology Program

IARC: International Agency for Research on Cancer

CWA: clean water act - US

TSCA: toxic substance control act - US CERCLA: comprehensive environmental response compensation and liability act – US CAA: clean air act - US SARA: superfund amendments and reauthorization

act – US PROP 65:California's Proposition 65 list WHMIS: workplace hazardous materials

information system - Canada

DSL: Domestic Substances List - Canada WGK: water hazard classes - Germany

Legal Statement

This information is accurate to the best knowledge of Orion Safety Products. Orion Safety Products makes no representations or warranties, either express or implied, including without limitation any warranties of merchantability or fitness for a particular purpose, with respect to the information set forth herein or the product to which the information refers. Accordingly, Orion Safety Products will not be responsible for damages resulting from use of or reliance upon this information. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation